



FOR INFORMATION: Riveting Hammer CP4444-1 discontinued

Concerned Products:

Riveting Hammer CP4444-1, part 205 147 938 4



Description:

We are pleased to inform you that we have discontinued the riveting hammer CP4444-1, part number 205 147 938 4 with immediate effect.

The CP4444-1 is no more available for sales.

The following types are still available.



PIC REF	MODEL	PART NUMBER	AIR FRAME REF	BLOW PER MINUTE	BORE & STROKE	ENERGY PER BLOW	CHISEL SHANK	RIVET CAPACITY	WEIGHT	AIR INLET	HOSE INT. Ø
					mm (in.)	J ft.lb	mm in.	mm (in.) mm (in.)	kg lb	in.	mm in.
Standard											
	CP4444-1	205 147 938 4	2X	2580	12.7 x 50.8 (1/2 x 2)	4.0 2.9	10.2 0.401	3.2 2.4 (1/8) (3/32)	1.0 2.2	1/4	10 3/8
B	CP4444-RURAB	T022961	2X	2580	12.7 x 50.8 (1/2 x 2)	4.0 2.9	10.2 0.401	3.2 2.4 (1/8) (3/32)	1.0 2.2	1/4	10 3/8
B	CP4444-RUSAB	T022962	3X	2160	12.7 x 76.2 (1/2 x 3)	6.1 4.5	10.2 0.401	4.8 4.0 (3/16) (5/32)	1.1 2.3	1/4	10 3/8
B	CP4444-RUTAB	T022963	4X	1740	12.7 x 101.6 (1/2 x 4)	8.1 6.0	10.2 0.401	6.4 4.8 (1/4) (3/16)	1.3 2.7	1/4	10 3/8
C	CP4447-RUSAB	T022965	5XB	1560	19.1 x 68.3 (3/4 x 2-11/16)	12.3 9.1	12.7 0.498	6.4 4.8 (1/4) (3/16)	2.2 4.7	1/4	10 3/8
C	CP4447-RUTAB	T022912	7XB	1140	19.1 x 98.4 (3/4 x 3-7/8)	17.8 13.1	12.7 0.498	7.9 6.4 (5/16) (1/4)	2.3 5.1	1/4	10 3/8
C	CP4447-RUVAB	T022964	9XB	900	19.1 x 147.6 (3/4 x 5-13/16)	26.6 19.6	12.7 0.498	9.5 7.9 (3/8) (5/16)	2.7 9.0	1/4	10 3/8
Vibration reduced											
D	CP4450-2	T025189	2X	2580	12.7 x 50.8 (1/2 x 2)	4.0 2.9	10.2 0.401	3.2 2.4 (1/8) (3/32)	1.2 2.7	1/4	10 3/8
D	CP4450-3	T025190	3X	2160	12.7 x 76.2 (1/2 x 3)	6.1 4.5	10.2 0.401	4.8 4.0 (3/16) (5/32)	1.3 2.8	1/4	10 3/8
D	CP4450-4	T025191	4X	1740	12.7 x 101.6 (1/2 x 4)	8.1 6.0	10.2 0.401	6.4 4.8 (1/4) (3/16)	1.5 3.2	1/4	10 3/8
E	CP4475-3	T025241	5XB	2000	19.1 x 76.2 (3/4 x 3)	13.7 10.1	12.7 0.498	6.4 4.8 (1/4) (3/16)	1.8 3.9	1/4	10 3/8
E	CP4475-4	T025242	7XB	1700	19.1 x 101.6 (3/4 x 4)	18.3 13.5	12.7 0.498	7.9 6.4 (5/16) (1/4)	2.4 5.3	1/4	10 3/8
E	CP4475-6	T025243	9XB	1250	19.1 x 152.4 (3/4 x 6)	27.5 20.3	12.7 0.498	9.5 7.9 (3/8) (5/16)	2.8 6.2	1/4	10 3/8
F	CP4450-S-2	205 146 712 4	2X	2580	12.7 x 50.8 (1/2 x 2)	4.0 2.9	10.2 0.401	3.2 2.4 (1/8) (3/32)	1.25 2.8	1/4	10 3/8
F	CP4450-S-3	205 146 713 4	3X	2160	12.7 x 76.2 (1/2 x 3)	6.1 4.5	10.2 0.401	4.8 4.0 (3/16) (5/32)	1.35 3.0	1/4	10 3/8
F	CP4450-S-4	205 146 714 4	4X	1740	12.7 x 101.6 (1/2 x 4)	8.1 6.0	10.2 0.401	6.4 4.8 (1/4) (3/16)	1.45 3.2	1/4	10 3/8

In case of questions, please contact us under
desoutter.gmbh@desouttertools.com +49 (0) 6181 411 0



ZUR INFORMATION: Abkündigung Niethammer CP4444-1

Betroffene Produkte:

Niethammer CP4444-1, Artikel 205 147 938 4



Beschreibung:

Hiermit möchten wir Sie informieren, dass wir ab sofort den Niethammer CP444444-1, Teilenummer 205 147 938 4 mit sofortiger Wirkung eingestellt haben.

Der CP444444-1 ist für den Verkauf nicht mehr verfügbar.

Folgende Modelle sind weiterhin verfügbar:



BILD	MODELL	ARTIKEL-NUMMER	BEZ. LUFT-FAHRT	SCHLÄGE PRO MIN.	BOHRUNG & HUB	ENERGIE JE SCHLAG	EINSTECK-ENDE	NIET-KAPAZITÄT	GEWICHT	LUFT-EIN-LASS	MIN. SCHLAUCH-Ø
					mm (in.)	J ft.lb	mm in.	mm (in.) mm (in.)	kg lb	in.	mm in.
STANDARD											
A	CP4444-1	205 146 938 4	2X	2580	12.7 x 50.8	4.0	2.9	10.2 0.401	3.2 2.4	1.0 2.2	1/4 10 3/8
B	CP4444-RURAB	T022961	2X (200)	2580	12.7 x 50.8 (1/2 x 2)	4.0	2.9	10.2 0.401 (1/8) (3/32)	3.2 2.4	1.0 2.2	1/4 10 3/8
B	CP4444-RUSAB	T022962	3X (300)	2160	12.7 x 76.2 (1/2 x 3)	6.1	4.5	10.2 0.401 (1/8) (3/32)	4.8 4.0	1.1 2.3	1/4 10 3/8
B	CP4444-RUTAB	T022963	4X (240)	1740	12.7 x 101.6 (1/2 x 4)	8.1	6.0	10.2 0.401 (3/16) (5/32)	6.4 4.8	1.3 2.7	1/4 10 3/8
C	CP4447-RUSAB	T022965	5XB (500)	1560	19.1 x 68.3 (3/4 x 2-11/16)	12.3	9.1	12.7 0.498 (1/4) (3/16)	6.4 4.8	2.2 4.7	1/4 10 3/8
C	CP4447-RUTAB	T022912	7XB (700)	1140	19.1 x 98.4 (3/4 x 3-7/8)	17.8	13.1	12.7 0.498 (5/16) (1/4)	7.9 6.4	2.3 5.1	1/4 10 3/8
C	CP4447-RUVAB	T022964	9XB (800)	900	19.1 x 147.6 (3/4 x 5-13/16)	26.6	19.6	12.7 0.498 (3/8) (5/16)	9.5 7.9	2.7 9.0	1/4 10 3/8
VIBRATIONSGEDÄMPFT											
D	CP4450-2	T025189	2X (200)	2580	12.7 x 50.8 (1/2 x 2)	4.0	2.9	10.2 0.401 (1/8) (3/32)	3.2 2.4	1.2 2.7	1/4 10 3/8
D	CP4450-3	T025190	3X (300)	2160	12.7 x 76.2 (1/2 x 3)	6.1	4.5	10.2 0.401 (3/16) (5/32)	4.8 4.0	1.3 2.8	1/4 10 3/8
D	CP4450-4	T025191	4X (400)	1740	12.7 x 101.6 (1/2 x 4)	8.1	6.0	10.2 0.401 (1/4) (3/16)	6.4 4.8	1.5 3.2	1/4 10 3/8
E	CP4475-3	T025241	5XB (500)	2000	19.1 x 76.2 (3/4 x 3)	13.7	10.1	12.7 0.498 (1/4) (3/16)	6.4 4.8	1.8 3.9	1/4 10 3/8
E	CP4475-4	T025242	7XB (700)	1700	19.1 x 101.6 (3/4 x 4)	18.3	13.5	12.7 0.498 (5/16) (1/4)	7.9 6.4	2.4 5.3	1/4 10 3/8
E	CP4475-6	T025243	9XB (800)	1250	19.1 x 152.4 (3/4 x 6)	27.5	20.3	12.7 0.498 (3/8) (5/16)	9.5 7.9	2.8 6.2	1/4 10 3/8
F	CP4450-S-2	205 146 712 4	2X	2580	12.7 x 50.8 (1/2 x 2)	4.0	2.9	10.2 0.401 (1/8) (3/32)	3.2 2.4	1.25 2.8	1/4 10 3/8
F	CP4450-S-3	205 146 713 4	3X	2160	12.7 x 76.2 (1/2 x 3)	6.1	4.5	10.2 0.401 (3/16) (5/32)	4.8 4.0	1.35 3.0	1/4 10 3/8
F	CP4450-S-4	205 146 714 4	4X	1740	12.7 x 101.6 (1/2 x 4)	8.1	6.0	10.2 0.401 (1/4) (3/16)	6.4 4.8	1.45 3.2	1/4 10 3/8

Bei Fragen gerne auf uns zukommen

desoutter.gmbh@desouttertools.com +49 (0) 6181 411 0