PRODUCT ENVIRONME

AXON




Energy supply	Auto Sending Voltage 110-240V	
Part number	615 932 780 0	615 932 783 0
MODEL	AXON DRIVE	MODULE SX

PRODUCTION LOCATION


- Made in France (Low-carbon plant)
- Main component supply locations:



SOURCES OF CO₂ EMISSIONS across lifetime / AXON only



CO₂ EMISSIONS PER MATERIAL CATEGORY



AXON

CUSTOMER DELIVERY





20%



Transport emissions

PRODUCT CARBON FOOTPRINT

Based on the ISO 14067:2018 standard, Product Carbon Footprint [PCF] sums up the total greenhouse gas emissions generated by a product over the different stages of its life cycle.





AXON

PCF value

182 kg / 401 lbs

CO2e/unit*

for 500 000 cycles

[Manufacturing and usage included]

PRODUCT ENVIRONMENTAL CARD

MORE THAN 20% CO₂ SAVING WITH EPD20 AND AXON

compared to an EPD20 and CVI3 Vision



1 EPD20 + 1 AXON (AXON Drive + Module SX) + 1 EPD tool cable 500 000 cycles – 1,84 sec cycle time





CONTROLLER SOLUTION


PCF value

322 kg / 710 lbs

CO₂e/unit

1 EPD20 + 1 CVI3 Vision + 1 EPD tool cable 500 000 cycles – 1,856 sec cycle time

CARBON FOOTPRINT SCALE







Equivalent to yearly carbon sequestered by a forest of **312 m²**



Equivalent to energy used to charge **6 225 smartphones**

Sources: U.S Environmental Protection Agency / International Energy Agency

^{*}PCF values for 500 000 cycles (inc. battery and charger). Values based on generic usage and C02 emission average of Desoutter sales. For a customized result please contact your local Desoutter representative.