



Product data
Floorify® Performance Underlay
 Underlay for Floorify® Rigid Vinyl Planks & Tiles

Version:









1-01-2024 (EN)

Size and basic information

Floorify® Performance Underlay is especially designed to be used in combination with Floorify® Rigid Vinyl Planks & Tiles and exceeds on all parameters the minimum requirements on underlayments. Floorify® Performance Underlay is manufactured without CFCs and HFCCs and contains neither plasticizers nor heavy metals or other hazardous substances

m ² /roll:	10	m ²
length	10	m
width	1	m
thickness	EN823	1,5 mm
qty/pallet	40	rolls 400 m ²

Technical data

		Norm Requirements	Floorify® results
	Impact sound improvement	ISO 10140 / ISO717-2 ΔLw18Db	In combination with Floorify® Rigid Vinyl Planks & Tiles: ΔLw16Db
	Compressive strength	EN826 ≥ 10kPa (MMFA)	≥ 450 kPa
	Compressive creep	EN1606 ≥ 2kPa	87 kPa
	Dynamic load	EN13793 load number of load cycles	75kPa >3.000.000
	Castor chair test	EN ISO4918 >25000 rotaties, non delminiation, no visible changes	Tested in combination with Floorify® Rigid Vinyl Planks & Tiles: pass
	Impact resistance:	EN13329 ≥ 1 200 mm	In combination with Floorify® Rigid Vinyl Planks & Tiles: 1800mm - IC3
	Fire classification:	EN 13501-1 EN ISO 11925-2	Efl
	Thermal resistance (floor + underlay)	EN12667 <0,15R (m ² K/W)	0,0213 R24 (m ² K/W) (Floorify® in combination with Floorify® Performance underlay) Underlay only: 0,0093 R24 (m ² K/W)
	Floor heating:	appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films.	

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality
 Floorify NV, Kruisboommolenstraat 30A 8800 ROESELARE, BELGIUM - Email: hello@floorify.com -T+32(0)5140180