



**Product data**  
**Floorify® Rigid Vinyl Planks & Tiles**  
 click

version: 1/07/2024

EN

**Dimensions and basic data**

		Large Planks	Planks XL	Herringbone	Tiles	Twist	
Width	ISO24342	225	240	125	600	123	mm
Length	ISO24342	1524	2000	750	900	1524	mm
Number of panels per pack	-	8	5	24	4	12	pc
m <sup>2</sup> per pack	-	2,74	2,4	2,25	2,16	2,25	m <sup>2</sup>
Weight per pack	ISO23997	22	20	20,08	17,6	19,8	kg
Total thickness	ISO24346	4,5	4,5	4,5	4,5	4,5	mm
Top Layer thickness	ISO24340	0,55	0,55	0,55	0,55	0,55	mm
Core	-	Sound reducing, robust and waterproof Floorify® Rigid Core					
Finish	-	Protected with stain resistant Floorify® Quiet Sense Technology					
Locking method	-	Traditional glueless click under license of Unilin.					



**Warranty**

	Usage class	ISO10582	33
	CE	EN 14041	DoP FF001
	Warranty	Residential / Commercial	Residential: 25 years (30 years when installed on Floorify® Performance subfloor) Commercial: 5 years

**Technical data**

	Norm	Norm Requirements	Floorify® results
	Wear resistance ISO24338 Procedure A	≥ 2000 cycles	≥ 4000 cycles - AC4
	Impact resistance EN13329	≥ 1600 mm	In combination with Floorify underlays: > 1800mm - IC3
	Residual indentation ISO24343-1	≤ 0,2 mm	In combination with Floorify underlays: no visible changes
	Stain resistance EN438-2	Groups 1 and 2: grade 5; Group 3: grade 4	Groups 1, 2 and 3: grade 5
	UV resistance ISO 105-B02:2014, Method 3	≥ 6	> 6
	Fire classification EN 13501-1 9239-1	ISO -	Bfl-s1
	Dimensional stability EN ISO23999 6uur bij 80C	≤ 0,15 % Curling ≤ 2mm	≤ 0,10 %
	Locking strength ISO24334	Long side: ≥ 1kN/m Short side: ≥ 1,5kN/m	Long side: > 5kN/m Short side: > 5kN/m
	Displacement of furniture feet EN ISO16581	Foot 0,1mm / 32kg	No changes
	Castor chairs EN ISO 4918	≥ 25000 cycles: No delamination, no disturbance	In combination with Floorify underlays: no visible changes
	Slip resistance EN13893 EN 16165	-	DS R10
	Thermal resistance (floor + underlay) EN12667	< 0,15R (m <sup>2</sup> K/W)	0,0239 R24 (m <sup>2</sup> K/W) (0,0146 floor + 0,0093 Performance underlay) 0,0686 R24 (m <sup>2</sup> K/W) (0,0146 floor + 0,0540 Comfort underlay)
	Floor heating	Appropriate for all standard heating systems IN cement flooring. NOT appropriate for heating films.	
	Impact sound improvement ISO 10140 / ISO717-2	ΔLw18dB	In combination with Floorify® Comfort underlay: ΔLw21dB (ΔLlin10dB)

**Dangerous Substances**

	Formaldehyde emission	EN14041 / EN717-1	-	E1
	TVOC 28 days	< 1000µg/m³	-	< 10µg/m³
	Emissions in the interior air	Decree n° 2011-321	-	A+
	REACH	-	-	Floorify® floors and accessories are fully REACH compliant
	Plasticizers	-	-	DOTP - virgin PVC - 100% orthophtalate free

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality  
Floorify NV, Kruisboommolenstraat 30A 8800 ROESELARE, BELGIUM - Email: hello@Floorify.com - T +32 (0)51 140 180