



Product data  
**Floorify® Gluedown Planks & Tiles**

version: 1/12/2024

EN

| General                   | Norm        | Long planks | Herringbone | XL tiles |
|---------------------------|-------------|-------------|-------------|----------|
| Measurements (mm)         | ISO24342    | 1524x225    | 750x125     | 900x600  |
| Top Layer thickness (mm)  | ISO24340    | 0.55        | 0.55        | 0.55     |
| Total thickness (mm)      | ISO24346    | 2.5         | 2.5         | 2.5      |
| Number of panels per pack | -           | 10          | 24          | 8        |
| m² per pack               | -           | 3.43        | 2.25        | 4.32     |
| Weight per pack           | EN ISO23997 | 14.5        | 9.5         | 18       |
| Locking method            | -           | glued       | glued       | glued    |

**Technical specifications**

|                       |              |             |
|-----------------------|--------------|-------------|
| Classification        | ISO10582     | Class 33    |
| Fire classification   | EN13501-1    | Bfl-S1      |
| Slip resistance       | EN 13893     | R10         |
| Dimensional stability | EN ISO 23999 | <0,15%      |
| Thermal resistance    | EN 12667     | 0,02 m² K/W |

**Dangerous Substances**

|                       |         |                                                            |
|-----------------------|---------|------------------------------------------------------------|
| CE                    | EN14041 | DOP FFY002                                                 |
| Emissions             | -       | A+                                                         |
| TVOC 28 days          | -       | <10µg/m³                                                   |
| Formaldehyde emission | -       | E1                                                         |
| REACH                 | -       | Floorify® floors and accessories are fully REACH compliant |

