



Product data
Floorify® Gluedown Planks & Tiles

version: 21/11/2025

EN

General	Norm	Long planks	Herringbone	XL tiles
Measurements (mm)	ISO24342	1524x225	750x125	900x600
Top Layer thickness (mm)	ISO24340	0.55	0.55	0.55
Total thickness (mm)	ISO24346	2.5	2.5	2.5
Number of panels per pack	-	10	24	8
m² per pack	-	3.43	2.25	4.32
Weight per pack	EN ISO23997	14.5	9.5	18
Locking method	-	glued	glued	glued

Technical specifications

Classification	ISO10582	Class 33
Fire classification	EN13501-1	Bfl-S1
Slip resistance	EN 13893	R10
Dimensional stability	EN ISO 23999	<0,15%
Thermal resistance	EN 12667	0,02 m² K/W

Dangerous Substances

CE	EN14041	DOP FFY002
Emissions	-	A+
TVOC 28 days	-	<10µg/m³
Formaldehyde emission	-	E1
REACH	-	Floorify® floors and accessories are fully REACH compliant



Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality
Floorify NV, Kwadestraat 151, 8800 Roeselare, BELGIUM - Email: hello@Floorify.com - T+32 (0)51 140 180