



Product data
Floorify® Rigid Vinyl Planks & Tiles
 click

version: 21/11/2025

EN

Dimensions and basic data				
	Width	ISO24342	Small tiles 305	
	Length	ISO24342	610	
	Number of panels per pack	-	12	
	m ² per pack	-	2,23	
	Weight per pack	ISO23997	17,42	
	Total thickness	ISO24346	4	
	Top Layer thickness	ISO24340	0,55	
	Core	-	Sound reducing, robust and waterproof Floorify® Rigid Core	
	Finish	-	Protected with stain resistant Floorify® Quiet Sense Technology	
	Locking method	-	Traditional glueless click under license of Unilin.	
Warranty				
	Usage class	ISO10582	33	
	CE	EN 14041	DoP FF001	
	Warranty	Residential / Commercial	Residential: 20 years (Lifetime when installed on Floorify® Performance underlay) Commercial: 5 years only when installed on Floorify® Performance underlay	
Technical data				
		Norm	Norm Requirements	Floorify values
	Wear resistance	ISO24338, Procedure A	≥ 2000 cycles	≥ 4000 cycles - AC4
	Impact resistance	EN13329	≥ 1600 mm	In combination with Floorify underlays: 1800mm - IC3
	Residual indentation	ISO24343-1	≤ 0,2 mm	In combination with Floorify underlays: no visible changes
	Stain resistance	EN438-2	Groups 1 and 2: grade 5; Group 3: grade 4	Groups 1, 2 and 3: grade 5;
	UV resistance	ISO 105-B02:2014, Method 3	≥ 6	> 6
	Fire classification	EN 13501-1 ISO 9239-1		Bfl-s1

	Dimensional stability	EN ISO23999 6uur bij 80C	$\leq 0,15 \%$ Curling $\leq 2\text{mm}$	$\leq 0,10 \%$ OK
	Locking strength	ISO24334	Long side: $\geq 1\text{kN/m}$ Short side: $\geq 1,5\text{kN/m}$	Long side: $> 4,5\text{kN/m}$ Short side: $> 4,5\text{kN/m}$
	Displacement of furniture feet	EN ISO16581	Foot 0,1mm / 32kg	No changes
	Castor chairs	EN ISO4918	≥ 25000 cycles: No delamination, no disturbance	In combination with Floorify underlays: no visible changes
	Slip resistance	EN13893 EN 16165	-	DS R10
	Thermal resistance (floor + underlay)	EN12667	$< 0,15\text{R (m}^2\text{K/W)}$	0.0213 R24 (m ² K/W) (0.0120 floor + 0.0093 Performance Underlay) 0.0660 R24 (m ² K/W) (0.0120 floor + 0.0540 Comfort Underlay)
	Floor heating	Appropriate for all standard heating systems IN cement flooring. NOT appropriate or tested with heating films.		
	Impact sound improvement	ISO 10140 / ISO717-2	$\Delta\text{Lw}18\text{dB}$	In combination with Floorify® Comfort underlay: $\Delta\text{Lw}20\text{dB}$ ($\Delta\text{Llin}10\text{dB}$)
Dangerous Substances				
	Formaldehyde emission	EN14041 / EN717-1		E1
	TVOC 28 days	$< 1000\mu\text{g/m}^3$		$< 10\mu\text{g/m}^3$
	Emissions in the interior air	Decree n° 2011-321		A+
	REACH	-	Floorify® floors and accessories are fully REACH compliant	
	Plasticizers	-	DOTP - virgin PVC - 100% orthophtalate free	