



Product data

**Floorify® Comfort Underlay**

Underlay for Floorify® Rigid Vinyl Planks & Tiles

Version:

29/05/2026









EN

**Size and basic information**

Floorify® Comfort Underlay is especially designed to be used in combination with Floorify® Rigid Vinyl Planks & Tiles and exceeds on all parameters the minimum requirements on underlayments. Floorify® Comfort Underlay is manufactured without CFCs and HFCCs and contains neither plasticizers nor heavy metals or other hazardous substances.

m <sup>2</sup> /roll:	15	m <sup>2</sup>
length	15	m
width	1	m
thickness	EN823	2 mm
qty/pallet	20	rolls 300 m <sup>2</sup>

**Technical data**

			<b>Norm Requirements</b>	<b>Floorify® results</b>
	Impact sound improvement	ISO 10140 / ISO717-2	ΔLw18Db	In combination with Floorify® Rigid Vinyl Planks & Tiles: ΔLw21Db (ΔLlin10Db)
	Compressive strength	EN826	≥ 10kPa (MMFA)	> 100 kPa
	Compressive creep	EN1606	≥ 2kPa	15kPa
	Dynamic load	EN13793		
			alternating load cycles from Omin = 0,1 to Omax	25Kpa
			number of load cycles	100'000
			max deformation / thickness loss Δd	<=0,5mm
	Castor chair test	EN ISO4918	>25000 rotaties, non delminiation, no visible changes	Tested in combination with Floorify® Rigid Vinyl Planks & Tiles: pass
	Impact resistance:	EN13329	≥ 1 200 mm	In combination with Floorify® Rigid Vinyl Planks & Tiles: 1800mm - IC3
	Fire classification:	EN 13501-1 EN ISO 11925-2		Efl
	Thermal resistance (floor + underlay)	EN12667	<0,15R (m <sup>2</sup> K/W)	0,0686 R24 (m <sup>2</sup> K/W)(Floorify® in combination with Floorify®Comfort underlay) Underlay only: 0,054 R24 (m <sup>2</sup> K/W)
	Floor heating:	Appropriate for all standard heating systems IN cement flooring. NOT appropriate or tested with heating films.		