



Product data
Floorify® Rigid Vinyl Planks & Tiles
click

version: 27/05/2026

EN

Dimensions and basic data				
		Big tiles		
Width	ISO24342	600	mm	
Length	ISO24342	900	mm	
Number of panels per pack	-	3	pc	
m² per pack	-	1,62	m²	
Weight per pack	ISO23997	17,8	kg	
Total thickness	ISO24346	5,5	mm	
Top Layer thickness	ISO24340	0,55	mm	
Core	-	Sound reducing, robust and waterproof Floorify® Rigid Core		
Finish	-	Protected with stain resistant Floorify® Quiet Sense Technology		
Locking method	-	Traditional glueless click under license of Unilin and Välinge		
Warranty				
	Usage class	ISO10582	33	
	CE	EN 14041	DoP FF001	
	Warranty	Residential / Commercial	Residential: 25 years (Lifetime when installed on Floorify® Performance subfloor) Commercial: 5 years (10 years when installed on Floorify® Performance subfloor)	
Technical data				
		Norm	Norm Requirements	Floorify® results
	Wear resistance	ISO24338 Procedure A	≥ 2000 cycles	≥ 4000 cycles - AC4
	Impact resistance	EN13329	≥ 1600 mm	In combination with Floorify underlays: > 1800mm - IC3
	Residual indentation	ISO24343-1	≤ 0,2 mm	In combination with Floorify underlays: no visible changes
	Stain resistance	EN438-2	Groups 1 and 2: grade 5; Group 3: grade 4	Groups 1, 2 and 3: grade 5
	UV resistance	ISO 105-B02:2014, Method 3	≥ 6	> 6
	Fire classification	EN 13501-1 ISO 9239-1	-	Bfl-s1

	Dimensional stability	EN ISO23999 6uur bij 80C	≤ 0,15 % Curling ≤ 2mm	≤ 0,10 %
	Locking strength	ISO24334	Long side: ≥ 1kN/m Short side: ≥ 1,5kN/m	Long side: > 5kN/m Short side: > 5kN/m
	Displacement of furniture feet	EN ISO16581	Foot 0,1mm / 32kg	No changes
	Castor chairs	EN ISO 4918	≥ 25000 cycles: No delamination, no disturbance	In combination with Floorify underlays: no visible changes
	Slip resistance	EN13893 EN 16165	-	DS R10
	Thermal resistance (floor + underlay)	EN12667	< 0,15R (m²K/W)	0,0263 R24 (m²K/W) (0,0170 floor + 0,0093 Performance underlay) 0,0710 R24 (m²K/W) (0,0170 floor + 0,0540 Comfort underlay)
	Floor heating	Appropriate for all standard heating systems IN cement flooring. NOT appropriate or tested with heating films.		
	Impact sound improvement	ISO 10140 / ISO717-2	ΔLw18dB	TBC
Dangerous Substances				
	Formaldehyde emission	EN14041 / EN717-1	-	E1
	TVOC 28 days	< 1000µg/m³	-	< 10µg/m³
	Emissions in the interior air	Decree n° 2011-321	-	A+
	REACH	-	-	Floorify® floors and accessories are fully REACH compliant
	Plasticizers	-	-	DOTP - virgin PVC - 100% orthophthalate free