



WD-40 SPECIALIST[®] DRY LUBE

PRODUCT DESCRIPTION

WD-40 Specialist[®] Dry Lube provides superior lubrication and long-lasting corrosion protection with no sticky residue. Best used where cleanliness and maximum performance are required as it dries quickly leaving behind a lubricating film that resists dirt and dust buildup. Great for reducing friction and wear on blades and bits, door and window tracks, slides, conveyor belts, rollers, hinges, table saws, lathes, power tools and equipment. Keeps your equipment running smoothly with long-lasting corrosion protection.

PACKAGING



APPLICATIONS

- Blades & Bits
- Door & Window Tracks
- Slides
- Rollers
- Hinges
- Conveyor Belts
- Power Tools & Equipment

FEATURES & BENEFITS

- Lubricates Blades & Bits
- Resists Dirt & Dust
- Great for Table Saws, Drills & Lathes
- Safe on multiple surfaces including most metals and plastics
- NSF H2 Reg# 146856

PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	90-140°C (194-284°F)	SPECIFIC GRAVITY:	0.72
SOLUBILITY IN WATER:	Insoluble in water	pH:	Not Applicable
VAPOR PRESSURE:	40-50 psi @ 70°F	VAPOR DENSITY:	Greater than 1 (air=1)
PERCENT VOLATILE:	>90%	VOC:	90.7%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not Determined	APPEARANCE/ODOR:	Colorless. Pleasant Odor.
FLASHPOINT:	<-29.2°F Tag Closed Cup	FLAMMABLE LIMITS:	LEL: 0.9% UEL: 9.5%

PERFORMANCE RESULTS

TEST METHOD	PROPERTY	RESULTS
ASTM D4172-Modified (30min; Ti = 70°F)	Lubricates	0.55 mm
ASTM D3233	Extreme Pressure Lubrication	3000 lbs.
ASTM B117	Corrosion Protection	< 5% surface corrosion in 72hrs

TEST LAB: WD-40 Co. Technical Center (Pine Brook, NJ); Test dates: 04/2024.

DIRECTIONS

Flip straw up for pinpoint **STREAM** or down for wide angle **SPRAY**. Apply by spraying directly on surface to be lubricated and protected. Dries in seconds.



WD-40 SPECIALIST[®] DRY LUBE

PACKAGING SPECIFICATIONS

ORDER#	CASE# / GTIN#	ITEM# / UPC#	DESCRIPTION	INDIVIDUAL UNIT					CASE PACK					PALLET						
				APPROX WT (OZ)	DIMENSIONS (IN)			CUBE	CASE PACK	APPROX WT (LBS)	DIMENSIONS (IN)			CUBE	APPROX WT (LBS)	CASES/LAYER	LAYERS	TOTAL QTY	APPROX HT (IN)	CUBE
				WIDTH	DEPTH	HEIGHT				WIDTH	DEPTH	HEIGHT								
300059	1 00 79567 30005 9	0 79567 30005 2	10oz Dry Lube	14.6	2.625	2.625	8.25	0.033	6	5.88	5.63	8.38	8.63	0.24	1188	39	5	195	48.4	53.75

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture, crush or incinerate containers, even when empty.

SPECIAL USE WARNINGS

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty. **FIRST AID: Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately. **Eye Contact:** Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention. **Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist. **Signs and Symptoms of Exposure:** Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye and respiratory irritation. Inhalation may cause coughing, headache and dizziness. Skin contact may cause irritation and drying of the skin. **Indication of Immediate Medical Attention/Special Treatment Needed:** Immediate medical attention is needed for ingestion. **CAS Numbers:** Heptane 64742-89-8/142-82-5; Propane 74-98-6.

REGULATORY INFORMATION

U.S. Federal Regulations: CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations. **SARA TITLE III: Hazard Category For Section 311/312:** Refer to Section 2 for the OSHA hazard classification **Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None **Section 302 Extremely Hazardous Substances (TPQ):** None **EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory **VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules. **California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not contain chemicals regulated under California Proposition 65. **Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.



