



WD-40 SPECIALIST® PENETRANT WITH EZ-REACH®

PRODUCT DESCRIPTION

WD-40 Specialist® Penetrant contains a proprietary blend of ingredients that work fast to free rusted bolts and other stuck parts. The capillary action penetrates into tight crevices, threads, and seams to break the bonds that hold stuck parts together. It helps prevent rust and corrosion from re-forming and leaves behind a lubricating layer. The professional-grade formula is low odor, working effectively without harsh, lingering scents.

Now the job is even easier with the EZ-Reach® 8" flexible straw that bends and keeps its shape, allowing unlimited access to hard-to-reach places.

Use Penetrant on nuts, bolts, pipe threads and rusted things that are stuck and won't move! It is safe to use on most common application surfaces, including most metals, plastics, and rubbers when used as directed. If unsure, test on a small area first.

PACKAGING



APPLICATIONS

- Nuts & Bolts
- Pipe Threads
- Locks
- Chains
- Rusted Parts and Stuck Components

FEATURES & BENEFITS

- Fast acting
- Low Odor
- Works on Contact
- 8" Flexible Straw gets into hard-to-reach spaces
- Does not require California Prop 65 Warning
- 50-state VOC Compliant

PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	221°C (430°F)	DENSITY:	Not Determined
SOLUBILITY IN WATER:	Insoluble in water	pH:	Not Applicable
VAPOR PRESSURE:	2.03mmHg @ 20°C (Petroleum Solvent)	VAPOR DENSITY	5.3 (Petroleum Solvent)
PERCENT VOLATILE:	>80%	VOC:	24.51%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not Determined	APPEARANCE/ODOR:	Clear liquid with a pleasant odor.
FLASHPOINT	64°C (147°F) (CC ASTM D3828)	FLAMMABLE LIMITS:	LEL: 0.6% UEL: 5.6%

DIRECTIONS

SHAKE CAN WELL before each spray. Flip straw up for pinpoint **STREAM** or down for wide angle **SPRAY**. Saturate the surface to be loosened and let soak for several minutes. Re-apply if necessary.



WD-40 SPECIALIST® PENETRANT WITH EZ-REACH®

PACKAGING SPECIFICATIONS

				INDIVIDUAL UNIT					CASE PACK						PALLET					
ORDER#	CASE# / GTIN#	ITEM# / UPC#	DESCRIPTION	APPROX WT (OZ)	DIMENSIONS (IN)			CUBIC FT	CASE PACK	APPROX WT (LBS)	DIMENSIONS (IN)			CUBE	APPROX WT (LBS)	CASES/LAYER	LAYERS	TOTAL QTY	APPROX HT (IN)	CUBIC FT
300486	1 00 79567 30048 6	0 79567 30048 9	13.5oz Penetrant with EZ-REACH	18.833	2.625	2.625	9.750	0.039	6	7.51	5.750	8.375	10.375	0.29	1431	37	5	185	56.880	63.2

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

DISPOSAL

If this product becomes a waste, it would not be expected to meet the criteria of RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture, crush or incinerate containers, even when empty.

SPECIAL USE WARNINGS

CONTENTS ARE FLAMMABLE: Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. **ELECTRICITY CAN BURN A HOLE IN THE CAN AND CAUSE CONTENTS TO BURST INTO FLAMES.** To avoid serious burn injury, do not let **THE CAN** touch battery terminals, electrical connections on motors or appliances or any other source of electricity. **CONTENTS UNDER PRESSURE:** Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat or store above 120°F. Avoid eye contact. Avoid prolonged or repeated contact with skin and clothing. Avoid breathing vapors or spray mists. Use in well ventilated area. Wash thoroughly with soap and water after use. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID: CONTAINS PETROLEUM DISTILLATES AND CARBON DIOXIDE PROPELLANT

Ingestion (Swallowed): Do not induce vomiting unless directed to do so by medical personnel. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water for 15 minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation persists, get medical attention.

Inhalation (Breathing): If irritation develops, discontinue use and move to fresh air. Get medical attention if irritation or other symptoms persist.

REGULATORY INFORMATION

U.S. Federal Regulations: CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act, and many states have more stringent release reporting requirements. Report spills re-quired under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None;

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All the components of this product are listed on the TSCA inventory

Canadian WHMIS Classification: Class B-5 (Flammable Aerosol), Class D-2-B (Toxic material causing other toxic effects)

R&D: 4012100

TDS Updated: 11/18/2025