



WD-40 SPECIALIST® PENETRANT WITH EZ-REACH®

PRODUCT DESCRIPTION

WD-40 Specialist Penetrant with EZ-Reach contains a proprietary blend of ingredients that work fast to free rusted bolts and other stuck parts. The capillary action penetrates tight crevices, threads, and seams to break the bonds that hold stuck parts together. It helps prevent rust and corrosion from re-forming and leaves behind a lubricating layer. The professional-grade formula is low odor, working effectively without harsh, lingering scents. Now the job is even easier with EZ-Reach, the permanently attached 8-inch flexible straw that bends and keeps its shape, giving you nearly unlimited access to hard-to-reach places.

Safe to use on most common application surfaces, including most metals, plastics, and rubbers when used as directed. If unsure, test on a small area first.

APPLICATIONS

- Rusted parts and stuck components
- Nuts, bolts, pipe threads
- Locks and chains

FEATURES & BENEFITS

- Fast-acting and low odor
- Equipped with EZ-Reach flexible straw to access hard-to-reach places
- 50-state VOC Compliant
- Does not require California Prop 65 Warning

PACKAGING



PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	221°C (430°F)	DENSITY:	Not Determined
SOLUBILITY IN WATER:	Insoluble	pH:	Not Applicable
VAPOR PRESSURE:	2.03mmHg @ 20°C (Petroleum Solvent)	VAPOR DENSITY	5.3 (Petroleum Solvent)
PERCENT VOLATILE:	>80%	VOC:	24.51%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not Determined	APPEARANCE/ODOR:	Clear liquid with a characteristic odor.
FLASHPOINT:	64°C (147°F)(CC ASTM D3828)	FLAMMABLE LIMITS:	LEL: 0.6% UEL: 5.6%

DIRECTIONS

Shake can well before each spray. Flip straw up for pinpoint stream or down for wide angle spray. Saturate the surface to be loosened and let soak for several minutes. CAUTION: Extreme pinching of straw can cause breakage.

PACKAGING SPECIFICATIONS

DESCRIPTION:	WD-40 Specialist Penetrant with EZ-Reach 13.5oz 6ct
ORDER NUMBER:	300486
CASE# / GTIN#:	1 00 79567 30048 6
ITEM# / UPC#:	0 79567 30048 9

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.



WD-40 SPECIALIST® PENETRANT WITH EZ-REACH®

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture, crush or incinerate containers, even when empty.

HAZARD WARNINGS



DANGER!

Extremely Flammable Aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or vapors. Use only outdoors or in a well-ventilated area.

Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with local and national regulations.

LINK TO SDS

[LINK TO SDS](#)

URL:

<https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-rust-release-penetrant-spray-with-straw-us-ghs-sds.pdf>

REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state, and local regulations.

SARA TITLE III:

Hazard Category for Section 311/312: Refer to Section 2 for the OSHA Hazard Classification.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None.

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All the components of this product are listed on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning.

R&D: 4012100

TDS Updated: 08/2026