



WD-40 SPECIALIST® SILICONE

PRODUCT DESCRIPTION

WD-40 Specialist Silicone leaves behind a lubricating film that resists water and protects against wear and corrosion. The resulting film is clear and free of messy or sticky residue, reducing the attraction of dirt and debris. The professional-grade formula can be relied on to lubricate even at extreme temperatures (-100° F to 500° F.). The permanently attached Smart Straw® Sprays 2 Ways® delivery system allows for pinpoint application or a wider spray, giving you different options to fit the job.

Safe to use on most common application surfaces including most metals, plastics, rubbers, and vinyl when used as directed. If unsure, test on a small area first.

APPLICATIONS

- Cables and pulleys
- Linkages and hinges
- Guide Rails
- Valves

FEATURES & BENEFITS

- Lubrication without messy or sticky residue
- Resists water
- NSF Nonfood Compounds Program Listed H2 #146863
- 50-state VOC Compliant
- Does not require California Prop 65 Warning

PACKAGING



Nonfood Compounds
Program Listed H2
146863

NO FOOD CONTACT

PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	221°C (430°F)	DENSITY:	Not Determined
SOLUBILITY IN WATER:	Insoluble	pH:	Not Applicable
VAPOR PRESSURE:	0.07 mmHg @ 25°C	VAPOR DENSITY	5.3 (Petroleum Solvent)
PERCENT VOLATILE:	>80%	VOC:	20%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not Determined	APPEARANCE/ODOR:	Clear yellow liquid with a petroleum odor.
FLASHPOINT:	<-30°C (-22°F) (CC ASTM D3828)	FLAMMABLE LIMITS:	LEL: 0.6% UEL: 5.6%

DIRECTIONS

Shake can well before each spray. Flip straw up for pinpoint stream or down for wide angle spray. Apply by spraying directly on surface to be lubricated and protected.

PACKAGING SPECIFICATIONS

DESCRIPTION:	WD-40 Specialist Silicone 11oz 6ct
ORDER NUMBER:	300012
CASE# / GTIN#:	4 00 79567 30001 2
ITEM# / UPC#:	0 79567 30001 4



WD-40 SPECIALIST® SILICONE

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate containers, even empty.

HAZARD WARNINGS



DANGER!

Extremely Flammable Aerosol. May be fatal if swallowed and enters airways.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition source. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents and container in accordance with local and national regulations.

LINK TO SDS

[LINK TO SDS](https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-water-resistant-silicone-lubricant-us-ghs.pdf)

URL:

<https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-water-resistant-silicone-lubricant-us-ghs.pdf>

REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Refer to Section 2 for the OSHA Hazard Classification.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None **Section 302 Extremely Hazardous Substances (TPQ):** None **EPA Toxic Substances Control Act (TSCA)**

Status: All of the components of this product are listed on the TSCA inventory. **VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules. **California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not require a California Proposition 65 warning.

Canadian Environmental Protection Act: One of the components is listed on the NDSL. All of the other ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

R&D: 2051200

TDS Updated:08/2026

wd40.com

9715 Businesspark Ave, San Diego, CA 92131 USA • WD-40 Safety Hotline: 1-888-324-7596

