



WD-40 SPECIALIST® CONTACT CLEANER

PRODUCT DESCRIPTION

WD-40 Specialist Contact Cleaner is designed to clean sensitive electronics and electrical equipment for optimal performance¹. The quick-drying formula cleans oil, dirt, flux residue, and condensation without leaving residue behind. The permanently attached Smart Straw® Sprays 2 Ways® delivery system allows for pinpoint application or a wider spray, giving you different options to fit the job.

Safe for use on most plastics², rubbers, and metals, including steel, galvanized steel, copper, brass, magnesium, nickel, tinplate, titanium, and zinc.

¹Follow equipment manufacturer's instructions for cleaning.

²Test on plastic before using and avoid adhesives, device screens, and keyboards.

APPLICATIONS

- Electric motors and generators
- Armatures and relays
- Electrical panels
- Printed circuit boards
- Controls, switches, tape heads
- Precision instruments

FEATURES & BENEFITS

- Quick drying, leaves no residue
- Dielectric strength: 206 kV/in
- Kauri Butanol (KB): >300
- NSF Nonfood Compounds Program Listed K2 #146857
- 50-state VOC Compliant
- Does not require California Prop 65 Warning

PACKAGING



Nonfood Compounds
Program Listed K2
146857

PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT:	180°F (82°C)	DENSITY:	0.71
SOLUBILITY IN WATER:	Partially soluble in water	pH:	Not Applicable
VAPOR PRESSURE:	37.5 mmHg @ 20°C (heptane)	VAPOR DENSITY	> 2 (air=1)
PERCENT VOLATILE:	100%	VOC:	45%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not Determined	APPEARANCE/ODOR:	Clear and colorless liquid. Hydrocarbon/alcohol odor.
FLASHPOINT:	16°F (-9°C) estimated	FLAMMABLE LIMITS:	LEL: 1.1%, UEL: 16.9%

DIRECTIONS

Shut off all power and allow any hot surfaces to cool. Make sure all stored power is drained from the system. Shake can well. Flip straw up for pinpoint stream or down for wide angle spray. Hold can 6 to 8 inches away from the surface and spray directly on to the electronic device or circuit board to eliminate and remove any contaminants that may cause loss of electrical contact. Tilt surface while cleaning and allow any excess cleaner to run off. Allow product to dry completely and thoroughly vent the system before restoring power.

PACKAGING SPECIFICATIONS

DESCRIPTION:	WD-40 Specialist Contact Cleaner 11oz 6ct
ORDER NUMBER:	300554
CASE# / GTIN#:	1 00 79567 30055 4
ITEM# / UPC#:	0 79567 30055 7



WD-40 SPECIALIST® CONTACT CLEANER

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 1 Aerosol. Store away from oxidizers.

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations.

HAZARD WARNINGS



DANGER!

Extremely Flammable Aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Do not breathe vapors or mists. Wash thoroughly with soap and water after handling.

Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection.

Response

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

IF exposed or concerned: Get medical advice.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with local and national regulations.

LINK TO SDS

[LINK TO SDS](https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-electrical-contact-cleaner-spray-us-ghs.pdf)

URL:

<https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-electrical-contact-cleaner-spray-us-ghs.pdf>



WD-40 SPECIALIST® CONTACT CLEANER

REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting. Oil spills are reportable to the National Response Center under the Clean Water Act. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category for Section 311/312: Refer to Section 2 for the OSHA hazard classification

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification

R&D: 3016100
TDS Updated: 08/2026

