



WD-40 SPECIALIST® CORROSION INHIBITOR

PRODUCT DESCRIPTION

WD-40 Specialist Corrosion Inhibitor is an anti-rust spray used to protect metal parts from corrosion for up to 1 year outdoors or 2 years indoors.¹ It contains metal-seeking Vapor Corrosion Inhibitors that seal & protect metals from the air and moisture that can cause rust. These Vapor Corrosion Inhibitors continue to work even if some of the sprayed surface gets rubbed off and can reseal the vulnerable surface to continue providing protection.

Safe on most metals and plastics when used as directed. Avoid prolonged contact with rubber.

¹Independent testing conducted in salt spray and humidity chambers. Results may vary depending on actual conditions.

APPLICATIONS

- Any untreated metal or iron exposed to the elements or damp storage conditions.
- Tools and locks
- Propane tanks
- Hinges, chains, cables
- Car parts

FEATURES & BENEFITS

- Ideal for use prior to long-term storage
- Long-lasting protection against corrosion
- NSF Nonfood Compounds Program Listed A7 #146726
- 50-state VOC Compliant
- Does not require California Prop 65 Warning

PACKAGING



Nonfood Compounds
Program Listed A7
146726

PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	Not Determined	DENSITY:	0.90-0.91 @ 68°F (20°C)
SOLUBILITY IN WATER:	Insoluble	pH:	Not Applicable
PERCENT VOLATILE:	>80%	VAPOR DENSITY	Greater than 1
		VOC:	34%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not established	APPEARANCE/ODOR:	Tan liquid with petroleum odor.
FLASHPOINT:	Not established	FLAMMABLE LIMITS:	LEL: 1.7% UEL: 10.9%
VISCOSITY:	1000 cps @ 100°F (38°C)	IGNITION TEMPERATURE:	860°F (460°C)

DIRECTIONS

Shake can well before each spray. Apply by spraying directly on the surface to be protected. For tight spaces, attach the straw for pinpoint accuracy.

PACKAGING SPECIFICATIONS

DESCRIPTION:	WD-40 Specialist Corrosion Inhibitor 6.5oz 6ct
ORDER NUMBER:	300035
CASE# / GTIN#:	100 79567 30003 5
ITEM# / UPC#:	0 79567 30003 8



WD-40 SPECIALIST® CORROSION INHIBITOR

STORAGE

Do not store above 120°F or in direct sunlight. U.F.C (NFPA 30B) Level 3 Aerosol.

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture cans, even when empty.

HAZARD WARNINGS



DANGER!

Extremely Flammable Aerosol. Pressurized container: may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist, vapors or spray. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and eye protection.

Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents and container in accordance with local and national regulations.

LINK TO SDS

[LINK TO SDS](https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-long-term-corrosion-inhibitor-us-ghs.pdf)

URL:

<https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-long-term-corrosion-inhibitor-us-ghs.pdf>

REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Refer to Section 2 for the OSHA hazard classification.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None **Section 302 Extremely Hazardous Substances (TPQ):** None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning. **VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules. **Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

R&D: 2063100

TDS Updated: 08/2026