



WD-40 SPECIALIST® CARB/THROTTLE BODY CLEANER

PRODUCT DESCRIPTION

WD-40 Specialist Carb/Throttle Body & Parts Cleaner with attachable precision straw is the only all-in-one carburetor cleaner spray you will need to clean your carburetor, throttle body, and unpainted metal parts. This cleaner uses a dual-action system: powerful solvents break up tough, baked-on carbon deposits while a high-pressure spray blasts away the loosened material. The results are engines that start up fast and easy, and level to a smooth, consistent idle with less stalling. This formula has been proven to improve performance at high RPMs. Great for both old and new vehicles and equipment, including cars, trucks, tractors, motorcycles, boats, lawn mowers, weed trimmers, and other gas-powered lawn outdoor equipment. Safe for use on most unpainted metals and will not affect oxygen (O₂) sensors or catalytic converters upon incidental contact.

APPLICATIONS

- Cars and trucks
- Tractors
- Motorcycles
- Boats
- Gas powered outdoor equipment

FEATURES & BENEFITS

- Powerful, solvent-based cleaner
- Dries quickly without leaving residue
- 50-state VOC Compliant
- Does not require California Prop 65 Warning

PACKAGING



PHYSICAL & CHEMICAL PROPERTIES

BOILING POINT (INITIAL):	56°C (133°F) (Acetone)	SPECIFIC GRAVITY:	0.78
SOLUBILITY IN WATER:	Miscible in water	pH:	Not Applicable
VAPOR PRESSURE:	231 mmHg @ 25°C (Acetone)	VAPOR DENSITY	>1
PERCENT VOLATILE:	100%	VOC:	10%
COEFFICIENT OF WATER/OIL DISTRIBUTION:	Not established	APPEARANCE/ODOR:	Clear liquid/solvent odor
FLASHPOINT:	-20° C (-4°F) (Acetone)	FLAMMABLE LIMITS:	LEL: 0.9% UEL: 12.8%

DIRECTIONS

SHAKE CAN WELL before each spray. **CARBURETOR CLEANING: With engine off and cool:** Remove the air cleaner, spray and flush the outside of the carburetor and all linkage and allow to dry. Avoid spraying electrical connections. **With engine running:** When dry, start engine and spray down and around the carburetor throat in short bursts to remove deposits from automatic choke valve and throttle plate area. PCV Valve: Disconnect crankcase side of the valve. Insert straw and spray into the open end of the valve while working the plunger back and forth. **THROTTLE BODY:** Remove air intake bellows. Spray to coat residue build-up on throttle plate and surrounding surface. Reattach bellows, start engine and with vehicle in park, depress the gas pedal about halfway a few times to clean. **METAL PARTS:** Spray on metal parts. If necessary, wipe clean. Only use on unpainted metal surfaces. Will not affect oxygen (O₂) sensors or catalytic converters upon incidental contact.

PACKAGING SPECIFICATIONS

DESCRIPTION:	WD-40 Specialist Carb/Throttle Body Cleaner 13.5oz 6ct
ORDER NUMBER:	300134
CASE# / GTIN#:	1 00 79567 30013 4
ITEM# / UPC#:	0 79567 30013 7



WD-40 SPECIALIST® CARB/THROTTLE BODY CLEANER

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials and heat, sparks or open flame. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 2 Aerosol. Store away from oxidizers.

DISPOSAL

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations. Do not puncture cans, even when empty.

HAZARD WARNINGS



DANGER!

Extremely flammable Aerosol. Pressurized container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

Prevention

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapors or mists. Wash thoroughly with soap and water after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with local and national regulations.

LINK TO SDS

[LINK TO SDS](https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-carb-throttle-body-parts-cleaner-us-ghs-sds.pdf)

URL:

<https://files.wd40.com/pdf/sds/specialist/wd-40-specialist-carb-throttle-body-parts-cleaner-us-ghs-sds.pdf>

REGULATORY INFORMATION

U.S. Federal Regulations: CERCLA 103 Reportable Quantity: This product has an RQ of 5,555 lbs. based on the RQ for acetone of 5000 lbs. In addition, oil spills are reportable to the National Response Center under the Clean Water Act. Report spills required under federal, state and local regulations. **SARA TITLE III: Hazard Category for Section 311/312:** Refer to Section 2 of the SDS for the OSHA hazard classification. **Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None **Section 302 Extremely Hazardous Substances (TPQ):** None **EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory or exempt from reporting; **VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules. **California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not require a California Proposition 65 warning. **Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

R&D: 3030200

TDS Updated: 08/2026