# SAVOX

SAVO



#### **Push-to-talk unit**

Reliable communication in harsh fireground environments

The Savox C-C440 control unit is a push-to-talk (PTT) unit, specifically designed for use with a two-way radio in challenging environments. Its extra-large push-to-talk button ensures a seamless user experience, even when the product is worn underneath protective clothing. Combined with a Savox headset, the solution enhances team communication, efficiency, and safety of operations. The Savox C-C440 can also be used with Dräger's and MSA's mask communication units.

#### **TECHNICAL INFORMATION**

Dimensions (L//H/W)	88mm/90mm/31mm (without the clip)
Weight	Approx. 140 g without radio connector cable
Fixing options	Clothing clip, rotating 180°
Material	Thermoplastics based polyamide (PA66)
Color	PTT button: red, housing: black
Emergency button option	Available in certain models, located close to headset connector
Supply voltage	3.010.0VDC (0VDC for dynamic microphone)
Current drain	~0.5mA @ 6VDC

### CONNECTIVITY

Headset support	Savox headsets with quick-release 4-pole connector (QR4) and with Savox headset wiring
Headset connector	Quick-release 4-pole female connector (QR4)
Radio connector cable	Fixed coiled cable
Radio compatibility and product codes	Please visit Savox website for more information

## **COMPLIANCE STANDARDS**

Environmental and testing	
IP rating	IP66 / IP67
Drop resistance	Drop to flat, hard surface from 1 m
Operation temperature	-40°C+85°C
Storage temperature	-25°C+70°C
Button switch component lifecycle	500.000 operations
Flammability rating	All materials according to UL94-V0

Regulatory information	
ROHS	2011/65/EU + (EU) 2015/863
REACH	1907/2006