


Auto Tip Dresser BAYO **CDK-BAYO**

Feature

1. Simultaneous dressing the upper and lower electrodes enables to reduce dressing time and be always alignment of the face after dress.
2. Balancer unit is a standard requirement, enables to reduce the load on the welding gun and the dresser.
3. Dresser with built-in rotation confirmation function by proximity sensor(Optional).
4. Splash proof construction for terminal box.
5. High torque, high-speed rotation(1 sec. dressing).
6. KTW cutter dresses upper and lower electrode simultaneously ensuring tip face alignment and its life span is long.
7. Correspond to international safety standard, CCC & CE.
8. Adopt one touch holder which does not require any tool.

※ Please contact our sales for special requirement or other products.

Installation



Before placement



After placement



One touch holder

Specification

Model	CDK-BAYO			CDK-BAYO-400						CDK-BAYO-480
Power AC(V)	200	220		380	400	415	400	440	460	480
Frequency(Hz)	50	60		50					60	
Current(A)	4.6	4.4	4.2	2.4	2.3	2.3	2.2	2.1	2.0	2.0
Revolution(RPM)	228	273	276	225	228	230	273	276	281	283
Torque(N・m)	34.4	28.7	28.7	38.3	37.7	37.5	31.5	31.1	30.6	30.4
Power(W)	1000									
Rated Time	Continuous use 5 minutes									
Weight(kg)	15.7									

※ Specification and design are to be changed without notice for improvement.
※ Movie is available on Kyokutoh web page.