

# Dual Head Auto Tip Dresser **CDK-DUAL**



## Feature

1. Simultaneous dressing the upper and lower electrodes enables to reduce dressing time and be always alignment of the face after dress.
2. Balancer unit is a standard requirement, enables to reduce the load on the welding gun and the dresser.
3. Dresser with built-in rotation confirmation function by proximity sensor(Option).
4. Splash proof construction for terminal box.
5. High torque, high-speed rotation (1 sec. dressing).
6. KTW cutter dresses upper and lower electrode simultaneously ensuring tip face alignment and its life span is long.
7. Correspond to international safety standard, CCC & CE.

※ Please contact our sales for special requirement or other products.

## Installation



Before placement

After placement

One touch holder

## Specification

Model	CDK-DUAL			CDK-DUAL-400					CDK-DUAL-480	
Power AC(V)	200	220		380	400	415	400	440	460	480
Frequency(Hz)	50	60		50			60			
Current(A)	4.6	4.4	4.2	2.4	2.3	2.3	2.2	2.1	2.0	2.0
Revolution(RPM)	216	259	262	214	216	218	259	262	266	268
Torque(N · m)	36.1	30.1	30.1	40.2	39.6	39.4	33.0	32.6	32.1	31.9
Power(W)	1000									
Rated Time	Continuous use 5 minutes									
Weight(kg)	15.9									

※ Specification and design are to be changed without notice for improvement.  
※ Movie is available on Kyokutoh web page.