



Laser Resection

26Fr. Laser Resection

Exclusive quick lock system allows for easy connection of inner and outer sheath.

Compatible with all major camera systems, the viewfinder eyepiece provides clearly defined, precise images.



High quality black ceramic tip that eliminates virtually all reflections.



Low-maintenance non coated stainless steel stop cocks provides for increased flow.



Ergonomic handle with cable connection pointing downward to provide less Interference and better handling.

Cystoscopes

| Part Number | Diameter | View | Length |
|----------------|----------|------|--------|
| STS-2040-302BA | 4.0 mm | 30° | 302 mm |

26 Fr. Laser Bayonet-Lock Sheaths

| Part Number | Description | Size |
|--------------------|--|--------|
| STS-URO-340-20-SET | Rotatable continuous flow sheath rotatable | 26 Fr. |
| Consisting of: | | |
| STS-URO-209-06 | 26Fr. outer sheath | |
| STS-URO-209-26 | Rotatable inner sheath with ceramic tip | |
| STS-URO-320-10 | Obturator | |

Working Elements

| Part Number | Description |
|----------------|---|
| STS-URO-047-08 | Laser-working element for 0.8mm fiber laser |
| STS-URO-047-10 | Laser-working element for 1.2mm fiber laser |

Laser Adapters

| Part Number | Description |
|----------------|---------------------|
| STS-URO-047-26 | Laser adapter |
| STS-URO-047-82 | Tuohy Borts adapter |

22Fr. Laser Resection

Exclusive quick lock system allows for easy connection of inner and outer sheath.

Compatible with all major camera systems, the viewfinder eyepiece provides clearly defined, precise images.



High quality black ceramic tip that eliminates virtually all reflections.

Low-maintenance non coated stainless steel stop cocks provides for increased flow.



Cystoscopes

| Part Number | Diameter | View | Length |
|----------------|----------|------|--------|
| STS-2029-302BA | 2.9 mm | 30° | 302 mm |

22 Fr. Laser Bayonet-Lock Sheaths

| Part Number | Description | Size |
|--------------------|---|--------|
| STS-HYS-310-22-SET | Rotatable continuous flow sheath rotatable | 22 Fr. |
| Consisting of: | | |
| STS-HYS-309-01 | 22Fr. outer sheath | |
| STS-HYS-315-21 | 19Fr. rotatable inner sheath with ceramic tip | |
| STS-HYS-310-19 | Obturator | |

Working Elements

| Part Number | Description |
|----------------|--|
| STS-HYS-046-08 | Passive laser-working element for up 0.8mm fiber laser |
| STS-HYS-046-12 | Passive laser-working element for up 1.2mm fiber laser |


Laser Adapters

| Part Number | Description |
|----------------|---------------|
| STS-URO-047-26 | Laser adapter |



Exclusive quick lock system allows for easy connection of inner and outer sheath.

Compatible with all major camera systems, the viewfinder eyepiece provides clearly defined, precise images.



Low-maintenance non coated stainless steel stop cocks provides for increased flow.

Ergonomic handle with cable connection pointing downward to provide less Interference and better handling.

Cystoscopes

| Part Number | Diameter | View | Length |
|----------------|----------|------|--------|
| STS-2029-302BA | 2.9 mm | 30° | 302 mm |

18.5 Fr. Laser Bayonet-Lock Sheaths

| Part Number | Description | Size |
|--------------------|---|--------|
| STS-HYS-175-18-SET | Rotatable continuous flow sheath rotatable | 22 Fr. |
| Consisting of: | | |
| STS-HYS-175-23-BP | 18.5 Fr. obturator | |
| STS-HYS-175-24-BP | 17.5/18.5 Fr. outer sheath | |
| STS-HYS-175-26-BP | 17.5/18.5 Fr. rotatable inner sheath with ceramic tip | |

Working Elements

| Part Number | Description |
|----------------|--|
| STS-HYS-175-08 | Passive laser-working element for up 0.8mm fiber laser |

Laser Adapters

| Part Number | Description |
|----------------|---|
| STS-URO-047-26 | Laser adapter |
| STS-URO-047-82 | Tuohy-borst laser adapter, for ø 061.4mm laser probes |



3020 NW 82nd Avenue Miami, Florida USA 33122 sales@endoscopia.com | Tel: +1 (305) 436-0599 | Fax: +1 (305) 436-0399 ISO 13485:2016 – Certified Quality Management System