



Ethanol E85

Product description

Ethanol E85 consists of approximately 85% bioethanol and approximately 15% petrol.

Benefits

The high proportion of bioethanol means that the fuel contributes less to the greenhouse effect than fossil fuels.

Applications

Ethanol E85 is a fuel intended for use in engines designed for this purpose. Use in other types of engines is not recommended.

Storage

All petrol products must be stored in tanks approved for the intended purpose. Light-transmitting tanks must not be used, as light exposure may impair product quality.

Health, environment and safety

See safety data sheet

Specifications

- SS-EN 15293

Article code

- 42 (summer)
- 582 (winter)

Information

For more information about the product, see the [product site](#). There you will find **FAQ**, as well as information about where to turn if you have further questions.



Ethanol E85

Property	Unit	Requirement acc. to SS-EN 15293	Typical analysis data summer / winter
Research octane number (RON)	-	-	101-104 / 99-102
Density at 15°C	kg/m ³	755,0 – 800,0	785 / 775
Ethanol and higher alcohols	vol-%	70 - 85	85 / 75
Vapour pressure at 37.8°C	kPa	35,0 – 60,0 (summer) 50,0 – 80,0 (winter)	37 51

The information in typical data does not constitute a specification but is an indication based on current production and may be affected by permitted production tolerances. The right to make changes is reserved. This replaces all previous issues and the information contained therein.