



Petrol 98

max 5% etanol

Product description

98 Octane Petrol is a 98-octane gasoline that complies with the applicable petrol standard and Swedish fuel legislation. The product may contain up to 5% ethanol and includes additives that help prevent the build-up of deposits on valves and fuel injectors.

Benefits

98 Octane Petrol, with its higher octane rating, is optimal for engines that can take advantage of the fuel's octane level to achieve maximum performance. In addition, **98 Octane Petrol** contains a detergent additive that helps prevent the build-up of deposits on valves and fuel injectors, thereby helping to optimize engine power, emissions, and fuel consumption.

Storage

All petrol must be stored in storage tanks approved for this purpose. Light-transmitting tanks must not be used, as light exposure may impair product quality.

Health, environment and safety

See safety data sheet

Applications

98 Octane Petrol is formulated for engines that require a higher octane rating. Using the correct octane rating for the engine helps optimize engine performance. 98 Octane Petrol contains a maximum of 5% ethanol and is therefore also suitable for vehicles that cannot run on petrol containing 10% ethanol.

The product is intended for engines equipped with a catalytic converter for exhaust emission control. For engines without a catalytic converter that require a lead replacement additive, there are products available at Preem service stations. When selecting a petrol grade, always follow the engine manufacturer's recommendations.

Specifications

- SS-EN 228

Article code

- 567 / 584 * (Petrol 98 max 5% etanol)

Information

For more information about the product, see the [product site](#). There you will find **FAQ**, as well as information about where to turn if you have further questions.

* Depending on depot



Petrol 98 max 5% etanol

Property	Unit	Requirement acc. to SS-EN 228	Typical analysis data
Research octane number (RON)	-	min 98,0	98,2
Motor octane number (MON)	-	min 87,5	88,0
Ethanol content	vol-%	max 5	0
Density at 15°C	kg/m ³	720,0 - 775,0	743
Distillation: Evaporated at 100°C	vol-%	47-71 (summer) 50-71 (winter)	52-63 54-65
Vapour pressure at 37.8°C	kPa	45-70 (summer)	69
		65-95 (winter)	94

The information provided in the typical data does not constitute a specification but is an indication based on current production. It may be affected by permitted production tolerances. We reserve the right to make changes without prior notice. This document supersedes all previous editions and the information contained therein.