Xiamen Kingfeels Energy Technology Co.,Ltd


Add: Unit A, 7th Floor, Rihua Building, No.8, Xinfeng 2nd Road, Huli District, Xiamen, Fujian, China

Factory Add: Hengkeng Village, Hengkou Town, Yongchun County, Quanzhou, China Tel: 0086–592–2393103 Email: info@kingfeels.com









12 Years Products Warranty 25 Years Life Time







Xiamen Kingfeels Energy Technology Co., Ltd (the main subsidiary of Fujian Shuangheng Group)

Established time: Feb, 1992.

Employees: 1500

Registered Capital: 30 Million USD Covering Area: 2,000,000 square meters

27 years history company, 9 years in PV mounting industry, 4 years OEM service + 5 years experience for own brand -Kingfeels Energy.

Product range: Solar mounting structures, Industrial aluminum extrusion, Construction aluminum extrusion, New building

materials and sanitary products.

Headquaters: Fujian Shuangheng Group Co., Ltd

Top 3

Top 3 company for

solar mounting

structure in

Xiamen

Branch office in Xiamen: Xiamen Kingfeels Energy Technology

8GW

Deployed

worldwide

12 Years

Products Warranty

25 years life time

One of

The largest


aluminum

extrusion

actories in Soutl

of China

Branch office in Japan: 株式会社キングフィールズ・ジャパン



Initial stage

Set up Shuangheng Cement Co,.Ltd

100%

Full anodizing for

components

20+

Countries with

Kingfeels

installations

Make the first move

Set up Shuangheng Group Co,.Ltd Shuangheng Aluminum Profile Co,.Ltd Face to domestic market Start selling industrial and construction aluminum profile

Gain trust by credit standing, get benefit by efficiency

Take sharp

ISO9001 certification

Service on demand

Thoroughly quality control

Abundant corporate culture

Reorganize and expand

Expanding aluminum extrusion factory to better satisfy customer requirements

Continuous improvement

Set up a new assembly factory

Set up Xiamen Kingfeels Energy Technology Co,.Ltd

Promote overseas sales of aluminum profiles

Do everything possible to plan the layout and accelerate the

developing-steps of the company

2016

Set up branch office in Japan: 株式会社キングフィールズ・ジャパン A thoroughly understanding of customer needs, timely and continuously

Challenge for tomorrow combine customer's feedback with our work History of development

Sand Bag Test The only company in China passed the Sand Bag Test of SHARP ENERGY

Background: Sharp Energy requested manufacturer to do the Sand Bag Test, which is putting 13 tons of sandbags (equals to 2400mm snow load) on the mounting structure. Outstanding design makes Kingfeels the only company in China that has passed the test.

Kingfeels not only has excellent design theories, but also has very convincing test results.













CONTENTS



A Projects & Produce Process

Project Case	1-14
Manufacturing Process	15-16

B Roof Systems

Tile Roof System	17-18
Standing Seam Roof System	19-20
Tin Metal Roof System	21-25
Flat Roof System	26-28

C Ground Systems

Aluminum Ground Mounting System	29~30
Aluminum Pile Ground Mounting System	31
Steel Mounting Systems	32
Solar Carport Systems	33
Solar Agriculture-farm System	34
Ground Screw	35~36
Components List	37~45
Warranty & Certificates	46





Site: Miyagi, Japan Capacity: 14.0MW Heavy Snow & Slope Hill Approached the Audit by the Tohoku Economic Ministry







Site: South Korea Capacity: 3000.0KW






















































































Site: South Korea Capacity: 10.0MW







Site : Dubai, UAE Capacity: 1000.0KW





























Company Information


Xiamen Kingfeels Energy Technology is the main subsidiary of Fujian Shuangheng Group who has accumulated 27 years of experience in manufacturing aluminum products.

We have mold making center and develop all molds by ourselves. The whole processing procedures including extrusion, machining, anodizing, powder coating, inspection, and packing should pass our strict quality control management system and be completed in our own factory.

Therefore, we can guarantee "Higher quality & Shorter delivery" as promised.



Manufacturing Process




Advantages of Aluminum Mounting structure compared with Steel Mounting structure:

- a. Affordable price: With reasonable design, price of aluminum mounting system will not be very higher than Steel Mounting System (only about 25% price difference).
- **b. Save installation time and labor cost:** Aluminum mounting structure has higher machining accuracy, much lighter weight, and part pre-assembly in factory (save 30% installation cost).
- c. Save maintenance cost: With better anti-corrosion, aluminum mounting structure will have about 25 years duration lifetime, almost no need to maintenance cost. But Steel structure will have to be repainted and re-welded to keep its service life.
- d. High priced recycling: Scrap aluminum can be sold in high price after using (about 40% purchase price of aluminum mounting), while Steel structure will be valueless for years severe corroded.

















Application:

Pitched roof with tiles

Fastening:

Roof hooks onto rafters

Roof Pitch:

Up to 60°

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single/double layer, cross rail installation


Advantages:

Low fitting costs

Every size of module array possible

For all common rafter distances









CR 1# Rail Splice Kit KS-CR1-SP





End Clamp KS-EC2-F40

Middle Clamp KS-IC2-F40



Application:

Pitched roof with tiles

Fastening:

Roof hooks onto rafters

Roof Pitch:

Up to 60°

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:

Low fitting costs


Every size of module array possible

For all common rafter distances





Standing Seam Roof







CR Rail Clamp KS-CRC-2AN



Middle Clamp KS-IC2-F40



Application:

Standing Seam Roof

Fastening:

Roof hooks on Standing Seam Rib

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:


Single/double layer, cross rail installation

Advantages:

Low fitting costs

Every size of module array possible

For all common rafter distances





Standing Seam Hook #10 KS-HK-S10



End Clamp KS-EC2-F40

Middle Clamp KS-IC2-F40



Application:

Standing Seam Roof

Fastening:

Roof hooks on Standing Seam Rib

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single layer

Advantages:


Low fitting costs

Every size of module array possible For all common rafter distances



TING FEELS

Tin Metal Roof







CR Rail Splice Kit KS-CR1-SP

Tin Interface Kit L feet 1# Type KS-HK-L01-ZS80





Middle Clamp KS-IC2-F40

End Clamp KS-EC2-F40



Application:

Trapezoidal and corrugated sheet metal

Fastening:

Riveted or screwed onto raised corrugations

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:


Low fitting costs

Every size of module array possible

Height adjustable via elongated hole in the sheet

metal bracket

Tin Metal Roof



CR3# Rail KS-CR3-XXX



CR 1#Rail Splice Kit KS-CR1-SP



Hanger Bolt Hook #2 KS-HK-L02



Middle Clamp KS-IC2-F40



Application:

Trapezoidal and corrugated sheet metal

Fastening:

Hanger bolts onto rafters

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:


Single/double layer, cross rail installation

Advantages:

Low fitting costs

Height adjustable


Suitable for large distances between rafters







Trapezoidal Metal Roof













CR 1# Rail Clamp KS-CRC-2AN

End Clamp KS-EC2-F40

Application:

Trapezoidal and corrugated sheet metal

Fastening:

Riveted or screwed onto raised corrugations

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single layer

Advantages:

Low fitting costs


Every size of module array possible

With rail / railess solution

Height adjustable via elongated hole in the sheet

metal bracket

Trapezoidal Metal Roof





Middle Clamp KS-IC2-F40



End Clamp KS-EC2-F40

Application:

Trapezoidal and corrugated sheet metal

Fastening

Riveted or screwed onto raised corrugations

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single layer

Advantages:


Low material / Low fitting costs Every size of module array possible With rail / railess solution

Quick mounting





Tin Metal Roof—UR Solution









CR 1#Rail Splice Kit KS-CR1-SP

End Clamp KS-EC2-F40





Middle Clamp KS-IC2-F40

Application:

Trapezoidal and corrugated sheet metal

Riveted or screwed onto raised corrugations

Module Type:

Framed and frameless modules

Module orientation:


Landscape/portrait

Layers of Rails:


Single layer

Advantages:

Low material / Low fitting costs Every size of module array possible No Rails necessary Quick mounting









CR 1#Rail KS-CR1-XXX



CR 1#Rail Splice Kit KS-CR1-SP



Triangle Bracket 1# KS-TR10-XX



CR 1#Rail Clamp with flange nut KS-CRC-01



End Clamp KS-EC2-F40



Application:

Cements Roof / Metal Roof

Fastening:

Riveted or screwed onto raised corrugations, or mounted onto the Concrete block

Tilt angle:

Up to 60 degrees

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single layer

Advantages:

Highly pre-assembly, easy installation Perfect also for small systems of 1,2,4 or 8 modules

Fixed angle, adjustable angle both available


Load bearing reserve of the roof has to be checked prior to installation





Adjustable Tilt Solution









End Clamp KS-EC2-F40





Middle Clamp KS-IC2-F40



Application:

Cements Roof / Metal Roof

Fastening:

Riveted or screwed onto raised corrugations, or mounted onto the Concrete block

Tilt angle:

KS-AJ-RL01: Adjustable rear leg 10-15° KS-AJ-RL02: Adjustable rear leg 15-30° KS-AJ-RL03: Adjustable rear leg 30-60°

Module Type:

Framed and frameless modules

Module orientation:

Portrait

Layers of Rails:


Single layer

Advantages:

Flexible tilt angle choices Anti-slip and anti-out design Double side lock, better strength Cheapest solution for adjustable mounting

12 Years Product Warranty / 25 Years Life Time

Ballasted Tilt Solution





Middle Clamp KS-IC2-F40





Ballast Triangle Bracket KS-KTR15-XXXX



Application:

Flat Concrete Roof

Tilt angle:

5°-20°

Module Type:

Framed modules

Module orientation:

Landscape

Layers of Rails:

Single layer

Building height:

20m max

Edge clearance:

Fitting in the roof edge and corner regions possible

Advantages:

Simple structure with high strength


No need rails, save material cost and installation

It's no penetration solution on concrete rooftop





Aluminum ground mounting system—Concrete foundation











End Clamp KS-EC2-F40

Application:

Open Field Area

Tilt angle:

Up to 45°

Material:

Al6005-T5 for aluminum profiles and clamps. Stainless steel for fasten bolt and nut.

Module Type:

Framed or Frameless modules

Module orientation:

Landscape/Portrait

Layers of Rails:

Single/double layer, cross rail installation

12 Years Product Warranty / 25 Years Life Time

Advantages:

Much Easier to install

Excellent wind resistant

Excellent anti-corrosion

Aluminum ground mounting system—ground screw foundation






BR9 Rail Splice Kit KS-BR9-SP

BR1 Rail Clamp KS-BR1-2A-C50





Ground Screw KS-F76-XXX-T3





Application:

Open Field Area

Tilt angle:

Up to 45°

Material:

Al6005-T5 for aluminum profiles and clamps. Stainless steel for fasten bolt and nut.

Module Type:

Framed or Frameless modules

Module orientation:

Landscape/Portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:

Much Easier to install

Excellent wind resistant


Excellent anti-corrosion





Ground mounting system —Pile Mounting System








U Pile and Tube Connector





BR1 Rail Clamp KS-BR1-2A-C50





VR Support Beam KS-VR4-XXXX

BR5 Rail Splice



VR Connect Jacket KS-108H-XXX

Application:

Open Field Area, Level Ground or Slope Ground Tilt angle:

Up to 45°

Material:

Al6005-T5 for aluminum profiles and clamps Stainless steel for fasten bolt and nut

Hot Dip galvanized Q235 for U Pile Post

Module Type:

Framed or Frameless modules

Module orientation:

Landscape/Portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:

Much better choice for uneven location

Much Easier to install

Excellent wind resistant

Ground mounting system —Steel Mounting System







Steel Rail KS-CBCL-XXXX





Brace Bar KS-CBCL-XXXX





End Clamp KS-EC-CBC-001

Application:

Open Field Area

Tilt angle:

Up to 45°

Material:

Al6005-T5 for aluminum clamps Q235 for Steel Rail & "C" Support Leg Stainless steel for fasten bolt and nut

Anti-corrosion:

Anodizing for Al6005-T5
Hot Dip galvanizing for Q235

Module Type:

Framed or Frameless modules

Module orientation:

Landscape/Portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:

High strength

Long durability

Low-cost /Eco-cost solution

Less base






Ground mounting system

—Carport Solution









Carport Rail Splice Kit KS-BR3-SP

Carport Rail Clamp KS-BR1-2AN-C35





Middle Clamp KS-CIC15-F40







Carport Support Beam KS-VR3-XXXX

Application:

Open Field Area, or Supper Mall Parking Area

Tilt angle

Up to 20° or Customized tilt angle

Ground Clearance:

Over 2000mm

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single/double layer, cross rail installation

Economic layout:


3 rows of modules with vertical assembly 6 rows of modules with horizontal assembly

Advantages:

Simple structure with high strength
Corrosion-resistant aluminum construction
(anodized aluminum alloy)
The customized solution makes good utiliza

The customized solution makes good utilization of ground and sunshine resources.

Save installation time and labor cost on site



VR Support Beam KS-VR4-XXXX



66

Support Tube Connect Jacket KS-UL-80

VR Support Tube KS-JT132-T-XXXX

Support Beam Connect Jacket KS-85H100-NP-AN





End Clamp KS-EC2-F40

Middle Clamp KS-IC2-F40

G

Application:

Open Field Area, Above the planting land

Tilt angle:

Up to 30° or Customized tilt angle

Ground Clearance:

Over 1800mm

Module Type:

Framed and frameless modules

Module orientation:

Landscape/portrait

Layers of Rails:

Single/double layer, cross rail installation

Advantages:

Dual-use of land improve the economic benefit A solution with adjustable tilt angle, to increase the sunshine amount


A solution with enough space, benefits to the machine work

Pre-assembled components, to save the installation time and cost





Ground Screw



The most appropriate foundation for solar project installed on open ground . Featured with high anti-corrosion, high strength, short delivery time,

very competitive prices.



Clay soil(screw pile)

Sandy soil(double blade)

Ground Screw Load Capability									
		Dia. of	Thickness of	200mm above ground, Pulling force (KN)					
Item No.	Dia. of Tube (mm)	Flange	Tube	Cla	y Soil N Va	alue	San	dy Soil N \	/alue
	(mm)	(mm)	(mm)	3	5	10	3	5	10
KS-F76-T3-1600	76	200	3	11.49	19.08	38.06	4.47	7.38	14.66
KS-F76-T3-1800	76	200	3	12.92	21.47	42.83	4.9	8.1	16.09
KS-F76-T3-2000	76	200	3	14.36	23.86	47.61	5.33	8.81	17.52
KS-22F76-T3-1600	76	220	3	11.49	19.08	38.06	4.47	7.38	14.66
KS-22F76-T3-1800	76	220	3	12.92	21.47	42.83	4.9	8.1	16.09
KS-22F76-T3-2000	76	220	3	14.36	23.86	47.61	5.33	8.81	17.52

Notes:

- ★ The value of the ground screw is the experimental value.
- * While installation condition changes, the data of ground screw change.









Torque test for ground screw

SGS test of flange torsion



SGS test of torsion of adjustable ground screw



















Possibility of adjustable





Components List

Photo	Item No	Name	Description	Packing
Roof PartRai	1			
	KS-CR1-length	CR Rail	Spec: 28*50mm Customized Length Material: Al 6005-T5	8pcs/bundle 512pcs/pallet
	KS-CR3-length	CR3 Rail	Spec: 28*45mm Customized Length Material: Al 6005-T5	8pcs/bundle 512pcs/pallet
	KS-CR1-SP	CR Rail Splice Kit	Spec:150mm Connect two pieces CR Rail Material: Al6005-T5 & A2-70	50pcs/box 4boxes/CTN
*	KS-CR1-SP-01	CR Rail Splice Kit with Ground Washer	Spec:150mm Connect two pieces CR Rail with Ground Washer	50pcs/box 4boxes/CTN
*	KS-IC2-F_	Middle Clamp	Middle Clamp Spec: 31/35/40/46/50 Pre-assembly	120pcs/box 4boxes/CTN
G	KS-EC2-F_	End Clamp	End Clamp Spec: 31/35/40/46/50 Pre-assembly	120pcs/box 4boxes/CTN
	KS-CIC15-F_	Inter Clamp	Inter Clamp Spec: 31/35/40/46/50 Pre-assembly	120pcs/box 4boxes/CTN
6	KS-CEC15-F_	End Clamp	End Clamp Spec: 31/35/40/46/50 Pre-assembly	120pcs/box 4boxes/CTN
	KS-TIC-03A	Thin Film Middle Clamp Kits	Aluminum & Rubber Pad Socket Head Screw Pre-assembly	80pcs/box 4boxes/CTN
	KS-TEC-03A	Thin Film End Clamp Kits	Aluminum & Rubber Pad Socket Head Screw Pre-assembly	80pcs/box 4boxes/CTN
. 6	KS-CRC-2AN	CR Rail Clamp	Rail Clamp with C nut Socket head screw Pre-assembly	120pcs/box 4boxes/CTN

	KS-CRC-01	CR Rail Clamp	Rail Clamp with Flange nut Socket head screw Pre-assembly	120pcs/box 4boxes/CTN
Standing Seam	Hook			
44	KS-HK-S03	Standing Seam Roof Hook 3#	Zambelli-Rib Roof Al6005-T5, A2-70 Pre-assembly	30pcs/box 4boxes/CTN
	KS-HK-S04	Standing Seam Roof Hook 4#	Bulter-Roof Al6005-T5, A2-70 Pre-assembly	30pcs/box 4boxes/CTN
	KS-HK-S07	Standing Seam Roof Hook 7#	Length: 50mm Al6005, A2-70 Pre-assembly	20pcs/box 4boxes/CTN
	KS-HK-S08	Standing Seam Roof Hook 8#	Klip-lok 406 Roof Al6005, A2-70 Pre-assembly	30pcs/box 4boxes/CTN
	KS-HK-S09	Standing Seam Roof Hook 9#	Klip-lok 700 Roof Al6005, A2-70 Pre-assembly	25pcs/box 4boxes/CTN
	KS-HK-S09-06	Standing Seam Roof Hook 9# A Type	Standing Seam Hook 9# with big flange	15pcs/box 4boxes/CTN
and the same of th	KS-HK-S10	Standing Seam Roof Hook 10#	Length: 50mm Al6005, A2-70 Pre-assembly	20pcs/box 4boxes/CTN
	KS-HK-S12	Standing Seam Roof Hook 12#	Length: 80mm Pre-assembly	20pcs/box 4boxes/CTN
44	KS-HK-S20	Standing Seam Roof Hook 20#	Bulter-Roof Al6005-T5, A2-70 Pre-assembly	20pcs/box 4boxes/CTN
	KS-HK-S21	Standing Seam Roof Hook 21#	Long Line Roof Stainless Steel, Length:110mm Pre-assembly	10pcs/box 4boxes/CTN

3/ 38





Tin Roof Hook				
	KS-HK-T01	88 T Metal Roof Hook	88 T Metal Roof hook Self-tapping Bolt st6.3*80	10pcs/box 4boxes/CTN
	KS-HK-CU01	Universal trapezoid Metal Roof Hook 1#	Aluminum Parts & Stainless Steel Self-tapping bolt st6.3*25 & Rubber Pad, Pre-assembly	20pcs/box 4boxes/CTN
	KS-HK-T07N-01	Trapezoid Metal Roof Hook 7#	Aluminum Roof Hook & Selff-tapping bolt st6.3*25 & Rubber Pad Tin Roof	180pcs/CTN
	KS-HK-C01	Trapezoid metal roof hook 1#	Spec: 100mm Material: Stainless Steel 4*st6.3*25 Self-tapping screw & Rubber pad	25pcs/box 4boxes/CTN
	KS-HK-C02	Trapezoid metal roof hook 1#	Spec: 100mm Material: Stainless Steel 4*st6.3*25 Self-tapping screw & Rubber pad	25pcs/box 4boxes/CTN
4	KS-HK-L01	Tin Interface Kit 1#Type	L feet & Rubber Pad Wood Bolt st6.3*80 Pre-assembly	60pcs/box 4boxes/CTN
	KS-HK-L02	Tin Interface Kit 2#	L feet & Rubber Pad Hanger Bolt Hook 2#, M10*200 Tin Roof Pre-assemly	20pcs/box 4boxes/CTN
E .	KS-HK-L06	Tin Interface Kit 6#	L feet & Rubber Pad Hanger Bolt Hook 6#, M10*300 Tin Roof Pre-assemly	20pcs/box 4boxes/CTN
	KS-UR2-120	U Type Rail	Aluminum U Type Rail 2x Wood Bolt st6.3*80 Slate Tile & Tin Roof	50pcs/box 4boxes/CTN
Tile Roof Hook				
	KS-HK-R01	Tile Roof Hook 1#		10pcs/box 4boxes/CTN
	KS-HK-R02	Tile Roof Hook 2#	Roman Tile Roof Stainless Steel Hook 3x Wood Bolt st6.3*80	10pcs/box 4boxes/CTN
	KS-HK-R03	Adjustable tile roof hook 3#		10pcs/box 4boxes/CTN

				- 101111 27
1	KS-HK-R04	Tile roof hook 4#	Roman Tile Roof Stainless Steel Hook 3x Wood Bolt st6.3*80	10pcs/box 4boxes/CTN
11	KS-HK-F01	Slate roof hook 1#	Slate Roof Stainelss Steel Hook	20pcs/box 4boxes/CTN
111	KS-HK-F04	Slate roof hook 4#	3x wood Bolt st6.3*80	20pcs/box 4boxes/CTN
Tilt Bracket				
	KS-AJ-FL	Adjustable front leg	Anodized Al6005-T5 2x Wood Bolt st6.3*80 Pre-assembly	20pcs/box 4boxes/CTN
	KS-AJ-RL01	Adjustable rear leg 10/15Deg	Anodized Al6005-T5 2x Wood Bolt st6.3*80 Adjusted solution can adjust the angle anti-slip & anti-out design	24pcs/CTN
	KS-AJ-RL02	Adjustable rear leg 15/30Deg		16pcs/CTN
	KS-AJ-RL03	Adjustable rear leg 30/60Deg		Package on request
	KS-TR10-01	Fix Triangle Bracket 10Deg	Anodized Al6005-T5 Pre-assembly	380pcs/pallet
	KS-TR30-01	Fix Triangle Bracket 30DegType	Anodized Al6005-T5 Pre-assembly	380pcs/pallet
	KS-TR45-01	Fix Triangle Bracket 45Deg	Anodized Al6005-T5 Pre-assembly	380pcs/pallet
<u> </u>	KS-TR-AJ-01	Adjustable triangle bracket 1#	Anodized Al6005-T5 2x Wood Bolt st6.3*80 Adjusted solution can adjust the angle 10-15 deg Pre-assembly	380pcs/pallet
	KS-TR-AJ-02	Adjustable triangle bracket 2#	Anodized Al6005-T5 2x Wood Bolt st6.3*80 Adjusted solution can adjust the angle 20-30 deg Pre-assembly	380pcs/pallet





	KS-KTR15-1800	Fix Triangle Bracket For Horizontal placement	No need more rail Eco-solution Pre-assembly	100pcs/pallet
Grounding Acc	cessories			
	KS-BR1-GC	Grounding Clip 1#	Stainless Steel Plate	1000pcs/box 4boxes/CTN
FIL	KS-BR2-GC	Grounding Clip 2#	Stainless Steel Plate	1000pcs/box 4boxes/CTN
	KS-BR-GL	Grounding Lug	Stainless Steel Plate Aluminum Lay-in Lug Fasten Pre-assembly	200pcs/box 4boxes/CTN
*	KS-BJ-03	Bonding Jumper	Braider Copper Wire Stainless Steel Plate & Socket Head Screw Pre-assembly	200pcs/box 4boxes/CTN
Accessories				
b	KS-CC-01	Cable Clip	SUS 304 For 2pcs OD3~5mm Cable line	500pcs/box 4boxes/ CTN
O	KS-SC-01	Cable Tie	SUS 304 Black Plastic appearance	100pcs/bag
	KS-2AN-01	C Nut	Aluminum 6005-T5 Clean Anodized M8 Threaded Hole	1000pcs/box 4boxes/CTN
	KS-F-SW8	Spring Washer	Spring Washer, M8 Stainless Steel A2-70	
0	KS-F-13DW8	Lock washer	Lock washer OD13 Stainless Steel A2-70	Package on
	KS-F-8DW8	Lock washer	Lock washer OD8 Stainless Steel A2-70	request
/	KS-FA-WSD -M10200	Hanger Bolt	Stainless Steel Hanger Bolt M10*200	

				TAIN 7 FEELS
Marie	KS-FA-WSD -M10300	Hanger Bolt Assembly	Stainless Steel Hanger Bolt & 3 flange nuts M10*300	
1	KS-FA-S245 KS-FA-S290 KS-FA-S2140	Hex Screw Hex Screw	Stainless Steel A2-70	
1	KS-F-S825 KS-F-S845 KS-F-S850	Socket head Screw Socket head Screw Socket head Screw	Stainless Steel A2-70	Package on request
	KS-F -ZST6025-A2	Self-tapping bolt	Stainless Steel st6.3*25	
-	KS-F -ZST6350-A1-01	Self-tapping bolt	Stainless Steel St6.3*50	
	KS-F -ZST6375-01	Self-tapping bolt	Stainless Steel St6.3*75	
	KS-F -ZST6380-A1	Self-tapping bolt	Stainless Steel St6.3*80	
4	KS-F-ST6380	Wood Bolt	Stainless Steel St6.3*80	
Ground PartR	Rail			
	KS-BR1-length	BR1 Support Rail	Customized Length Aluminum 6005-T5 W50*H115	168pcs/pallet
	KS-BR3-length	BR3 Carport Support Rail	Customized Length Aluminum 6005-T5 W80*H180	70pcs/pallet
	KS-BR5-length	BR5 Support Rail	Customized Length Aluminum 6005-T5 W50*H80	192pcs/pallet
	KS-BR7-length	BR7 Support Rail	Customized Length Aluminum 6005-T5 W50*H115	168pcs/pallet





	KS-BR13-length	BR13 Support Rail	Customized Length Aluminum 6005-T5 W56*H95	120pcs/pallet
	KS-BR14-length	BR14 Support Rail	Customized Length Aluminum 6005-T5 W75*H90	150pcs/pallet
	KS-BR19-length	BR19 Support Rail	Customized Length Aluminum 6005-T5 W67*H76	165pcs/pallet
	KS-BR1-SP	BR1 Support Rail Splice Kit	Spec:400mm Connect two pieces BR1 Rail Material: Al6005-T5 & A2-70	20pcs/CTN
1	KS-BR3-SP	Carport Support Rail Splice Kit	Spec: 500mm Connect two pieces BR3 Rail Material: Al6005-T5 & A2-70	8pcs/CTN
	KS-BR5-SP	BR5 Support Rail Splice Kit	Spec:400mm Connect two pieces BR5 Rail Material: Al6005-T5 & A2-70	20pcs/CTN
13.73.	KS-BR7-SP	BR7 Support Rail Splice Kit	Spec:400mm Connect two pieces BR7 Rail Material: Al6005-T5 & A2-70	20pcs/CTN
	KS-BR9-SP	BR9 Support Rail Splice Kit	Spec:400mm Connect two pieces BR9 Rail Material: Al6005-T5 & A2-70	12pcs/CTN
	KS-BR13-SP	BR13 Support Rail Splice Kit	Spec:400mm Connect two pieces BR13 Rail Material: Al6005-T5 & A2-70	20pcs/CTN
	KS-BR14-SP	BR14 Support Rail Splice Kit	Spec:400mm Connect two pieces BR14 Rail Material: Al6005-T5 & A2-70	15pcs/CTN
	KS-BR19-SP	BR19 Support Rail Splice Kit	Spec:400mm Connect two pieces BR19 Rail Material: Al6005-T5 & A2-70	15pcs/CTN
Support Beam				
	KS-VR1-length	VR Support Beam	Customized Length Aluminum 6005-T5 W50*H95	Package on request

	KS-VR3-length	Carport Support Beam	Customized Length Aluminum 6005-T5 W80*H160	
	KS-VR4-length	VR4 Support Beam	Customized Length Aluminum 6005-T5 W50*H90	Package on request
	KS-VR6-leghth	VR6 Support Beam	Customized Length Aluminum 6005-T5 W50*75	
Support Tube				
	KS-AG-T-length	AG Support Tube	Customized Length Aluminum 6005-T5 W50*H60	
	KS-CT-length	Carport Support Tube	Customized Length Aluminum 6005-T5 W80*H90	
	KS-AG6-T-length	AG6 Support Tube	Customized Length Aluminum 6005-T5 W50*H60	Package on request
	KS-JT132-T	Support Tube 1 #	Customized Length Aluminum 6005-T5 W50*H50	
	KS-JT133-T	Support Tube 2 #	Customized Length Aluminum 6005-T5 50*60	
Support Access	sories			
	KS-BR1-2AN-C50	BR Rail Clamp Splice	BR Rail Clamp with C nut Socket head screw Pre-assembly	120pcs/box 4boxes/CTN
	KS-BR14-2AN-C50	BR14 Rail Clamp Splice	BR14 Rail Clamp with C nut Socket head screw Pre-assembly	120pcs/box 4boxes/CTN
	KS-108H-100	H type connector	Connected Support beam on support Tube Aluminum 6005-T5	Package on
4 4	KS-108H-140	H type connector	Connected Support beam on support Tube Aluminum 6005-T5	request
				22





TIA.	KS-JT134-110B	VR Bottom Base 110	VR Bottom Base 110 W160*H100*L110 Aluminum 6005-T5, A2-70	
100	KS-JT134-140B	VR Bottom Base 140	VR Bottom Base 140 W160*H100*L140 Aluminum 6005-T5, A2-70	
	KS-CB200-01	Carport Bottom Base 200	Carport Bottom Base 200 Aluminum 6005-T5, A2-70	Package on request Package on request
	KS-CB300-01	Carport Bottom Base 300	Carport Bottom Base 200 Aluminum 6005-T5, A2-70	
	KS-AG4-NFL	Front Support Leg	Front Support Leg Spec: H75 Aluminum 6005-T5, A2-70	
	KS-AS-Length	Aluminum Brace Bar	Customized Length Clean Anodized Al 6005-T5	
	KS-AK-01	Rotary Bracket	Rotary Bracket Adjust the north-south or east- west orientation Al 6005-T5 Slope Hill	
2 60	KS-OP-HC	Open Post Connector	Connected Support beam on Pile Post Clean Anodized Al 6005-T5, A2-70	
4	KS-OP-SZ	Diagonal Tie Rod Pivot Assembly	Connected Brace Tube from Pile Post to Support beam	
	KS-OP- Length	Pile	Open post Hot-Dip Galvanized Q235	Package on request
	Steel Rail	Steel "C" Type Rail	Steel "C" Type Rail Customized Length Hot-Dip Galvanized Q235	Package on request
	Steel Support Leg	Steel "C" Type Rail Support Leg	Steel "C" Type Rail Support Leg Customized Length Hot-Dip Galvanized Q235	Package on request
	KS-F76-XXX-T3	Ground Screw	Hot-Dip Galvanized Q235 Ground Screw	80pcs/pallet

Warranty & Certificate







