

Make life full of hope

51.2V

LiFePO4 Battery Pack

Low-voltage

25kWh

Features

- Scalable expansion up to 375kWh in parallel.
- Flexible Installation: floor-mounted.
- LiFePO4: Higher safe performance and longer cycle life.
- Multiple Protection with built-in smart BMS, breaker and fuse.
- Compatible with leading inverter brands.
- Up to 7-year long warranty.



FLA48500













Model	FLA48500
Battery Type	LiFePO4
Nominal Energy	25kWh
Nominal Voltage	51.2V
Operating Voltage	44.8-57.6V
Recommend Charge/Discharge Current[1]	≤200A
Recommend Charge/Discharge Power[1]	≤10000W
Maximum Charge/Discharge Current(15s)	300A
Maximum Charge/Discharge Power(15s)	15000W
Depth of Discharge(DOD)	≥95%
Scalability	Max.15 pcs in Parallel(375kWh)
Communication	RS485/CAN
Protection Degree	IP21
Cycle Life[2]	≥6,000 Cycles
Charging Temperature Range	0°C-55 °C
Discharging Temperature Range	-20°C-60°C
Display	LCD+LED
Installation Style	Floor-Mounted
Protection	Built-in Smart BMS, Breaker, Fuse
Warranty	7 Years
Certification	UN38.3、CE-EMC、IEC 62619
Product Weight	218KG
Package Weight	248KG
Product Dimension	718X380X990MM
Package Dimension	825X498X1162MM
[1] Recommend Charge/Discharge Current/Pow	er is Affected by Temperature and SOC.
[2] Test Conditions: 0.2C Charging/Discharging @25°C, 80% DOD.	

^{*}Product specifications may vary during continuous improvements. Please contact us for latest details.

Product Display



Longer Lasting LiFePO4 Battery



Real-time Status via LCD Display



Support 15 Pcs in Parallel



Wide Inverter Compatibility





 $^{{}^{\}star}\mathsf{Refer}\ \mathsf{to}\ \mathsf{Felicitysolar's}\ \mathsf{Warranty}\ \mathsf{Policy}\ \mathsf{for}\ \mathsf{applicable}\ \mathsf{conditions}.$