



Advanced managerial armchair with upholstered back.

Seat & Backrests

The backrest is made with a black or white polypropylene frame that supports a padded thermoformed membrane made as a composite structure with differentiated stratigraphy consisting of a central core in polyurethane rubber 1 cm thick. This layer acts as an internal air chamber, ensuring high breathability and constant elastic recovery under compressive load, enclosed between two outer layers of Chili fabric in the following colors:



470 gr/mtl
100% post-consumer recycled polyester
Classe1 - 60.000 +/- cicli Maltindale

Thermal Performance: The internal mesh section facilitates the dissipation of body heat, preventing the accumulation of moisture typical

of monoblock polyurethane foam padding.

Equipped with height-adjustable lumbar support in nylon or soft polyurethane.

The fully upholstered seat, with double side stitching, is made of 5 cm thick cold-foamed polyurethane.

The anatomical front shape provides anti-stress relief for the legs.

Armrests

Black polypropylene armrests with soft polyurethane pads, 2D height adjustable

Black or white polypropylene armrests with soft black polyurethane pads, 3D height adjustable

That's it Light soft cover

4D adjustable armrests in black or white polypropylene with soft black polyurethane pads and polished aluminum trim

Mechanism

That's It has two options for the mechanism:



1 - Synchronized tilt adjustment mechanism seat back with anti-shock system lockable in 4 positions adjustable. Elevation and synchron lock of the seat by small levers. Sliding seat (All controls are integrated in the underseat with small levers.)
Seat easily removable and replaceable without the use of tools.

2 – Synchron self weight adjustable with levers, synchronized adjustment of the seat back tilt with Anti-shock system lockable in 4 positions. Angle swing backrest 20°. Seat oscillation 6.5°. Seat slider.

The gas column complies with DIN 4550 standard and exceeds the 4th level

Base

The basis to be associated is usually of three types:

- "TREND" 5-spoke on polished aluminium wheels [d. 680 mm]
- "TREND" 5-spoke on black polypropylene wheels [d. 680 mm]
- "TREND" 5-spoke on white polypropylene wheels [d. 680 mm]

Standard black nylon double tread wheels with 65 mm diameter.



Measures	Seat height	Total height	Width	Depth
cm	42/53	103/115	68/49	68/48-56

Product's certificate



Disassemblability

All products have been designed in such a way that they can be disassembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Guarantee and safety

QUINTI guarantees that the products will keep their characteristics for 6 years from delivery, save normal wear and provided they are used according to the indications given. QUINTI will replace any product found not to comply with this warranty at no cost, without bearing any other responsibility. The application of the component warranty is excluded; external accessories or materials provided by the buyer and applied to products for the purpose of a customization of the same. For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, Some simple attentions are required.

All the sessions offered are SAFE according to the provisions of the EU Regulation 2023/988, on general product safety (GPSR), reinforced by UNI EN certifications.

The company is not liable for misuse (Stand up or use products such as ladders and oscillations that could affect the operation and safety of the user. To lift or move the product, grasp firmly on the supporting structure. The product must not be subjected to decentralized loads, is designed to be used in normal standing conditions on 4 legs or on the base).

Use & Maintenance

For an optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

THE TEXTILES

Cleaning: consult the recommendations for maintenance and washing given in the fabric sheet of the color chart. Use: It is recommended to pay attention to the use as it can be torn or cut.

THE LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use high-quality leather care products according to the manufacturer's instructions. In case of doubt, test the product on a part hidden from view to verify the result, waiting at least 24 hours for possible problems. Use: remember that the leather is a delicate material therefore it is recommended to take care during use.

THE METALS

Cleaning: both metal surfaces made of steel or aluminium, as well as painted surfaces, must be cleaned with a damp and soft cloth soaked in hot water. For the most stubborn stains, you can dilute liquid neutral soap in water with moderation. Always dry after cleaning with a soft cloth or deer leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and sponges that can scratch metal surfaces. Use: be careful of food stains such as coffee, cola, fruit juices that can leave indelible stains on surfaces.