



Base

1. Black PP base "Loop". [d. 680]
2. Polish aluminum base "Loop". [d. 680]

Castors & foot

Double tread with diameter 65 mm., standard [as standard] or rubberized. Both can be free [as standard] or braking cars. The polyamide feet are interchangeable with the wheels with the same fixing pin to the base.

Elevation

All Quinti gas columns comply with DIN 4550 and exceed 4° level.

Mechanics

Syncron self-weighing mechanism synchronized with seat height and synchronized adjustment of the backrest inclination in 5 positions.

Adjusting the oscillation voltage using a handwheel located under the seat.

Arms

Available with and without armrests. The armrests are provided height adjustable (B02) or height and depth adjustable with black PU pad (B09N).

Seat & backrest

Seat: Made with a high-strength polypropylene interior with 2 steel bars inserted inside. Properly padded with high density polyurethane, the seat is covered in all fabrics of the Quinti Colours System.

Backrest: Wide and welcoming black structure. The backrest supports both our Goal and Gabriel mesh and features adjustable lumbar support with **Up-Down system**.

Accessories

Optional seat slide
Height adjustable coated headrest



Measures	Seat height	Total height	Width	Depth
cm	45/57	106/118	68/46	68/44

Product's certificates



The session far exceeds the minimum requirements of DL 626/94, and DL.81. Complies with EN1335A and 1IM approved - CAM declaration.

Disassembly

All products have been designed in such a way as to allow them to be assembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Warranty & safety

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. E' excluding the application of the warranty on external components, accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it was designed to be used under normal conditions of support on 4 legs or on the base).

Use & maintenance

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart. Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation.

Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Use: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

Upholsteries

LASER

CATEGORY 2

560 gr/mtl
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

ECOPELLE

CATEGORY 2

630 g/lin.m
83% PVC 17% Sintetico
Classe 1
30.000 +/- 10% cicli Maltindale

JET

CATEGORY 3

365 +/- 5% g/lin.m
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

ONE RECICLE

CATEGORY 3

525 gr/mt2
100% recycled poliester
CLASSE 1IM
100.000 CICLI

LYRA

CATEGORY 3

550 g/lin.m
100% Poliestere
Classe 1
60.000 +/- 10% cicli Maltindale

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- cicli Maltindale

DREAM

CATEGORY 3

375 gr/mtl
100% Poliestere tinto in massa
melange effetto bouclè
OEKO TEST
Classe 1 - 100.000 +/- cicli Maltindale

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Classe 1
80.000 +/- 10% cicli Maltindale

VELOURS

CATEGORY 3

611 gr/mtl
100% Poliestere
Oeko test
50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Superficie 100% POLIURETANO,
Base Poliestere 85%.17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

COCOON

CATEGORY 5

980 gr/mtl
43% viscosa 33% cotone 24% li-pl
35.000 +/- 10% cicli Maltindale

LANA

CATEGORY 5

500 gr/mt2
75% Lana, 25% poliammide
Classe 1
100.000 cicli Maltindale

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Poliestere Recycled
EN 1021-1/2
80.000 % cicli Maltindale

TECHNICOLOUR kvadrat

CATEGORY 5

430 g/lin. M
100% new English wool, worsted
80.000 % cicli Maltindale
Ecolabel
Classe 1

MAIN LINE camira

CATEGORY 5

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

PELLE

CATEGORY 5/6

620 g/lin.m
100% Pelle bovina
Classe 1, EN 1021-1/2

PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% Pelle bovina Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

MONOCHROME SETT camira

CATEGORY 7

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

BOUCLET RUBELLI

CATEGORY 7

860 g/lin.m
40% PC, 25% PL, 20% VI, 15% CO
Classe 1, EN 1021-1/2
50.000 % cicli Maltindale

VELLUTO DECONTRACTE' RUBELLI

CATEGORY 7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10% VI
40.000 % cicli Maltindale

HORO RUBELLI

CATEGORY 7

495 g/lin.m
44% PL 29% CO 24% JU 3% PC
30.000 % cicli Maltindale

PELLE SETA

CATEGORY 8

100% Pelle bovina SPESSORE 1,8-2 mm
Primo fiore CONCIA ALL' ANILINA
EN1021-1/2

ZERO

CATEGORY 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cicli Maltindale

RETE GABRIEL

510 g/lin.m

100% Poliestere

Classe 1

70.000 +/- 10% cicli Maltindale

RETE NEW GOAL

350 g/lin.m

100% Poliestere

Classe 1

100.000 +/- 10% cicli Maltindale