



Visitor armchair with back made with breathable mesh membrane.

Seat & Backrest

The backrest has a black or white polypropylene load-bearing structure with integrated armrests that supports a breathable mesh membrane of 2 types:

- Gabriel 100% polyester – Thickened membrane
- Goal New 100% Polyester – Thickened Membrane

The seat is made with a high-strength polypropylene inner support with a white or black polypropylene seat support, adequately padded with 5 cm thick, non-deformable high-density polyurethane, anatomically shaped padding and anti-fatigue thickness, glued to the rubber to prevent wrinkles over time and double-seamed.

Arms

Black or white polypropylene armrests integrated into the body

Base

Stackable cantilever structure up to 4 pcs, made of tubular diam 25 mm thick 2 mm painted with black or chrome epoxy powders equipped with black Nylon stabilizing feet.

Measures	Seat height	Total height	Width	Depth
cm	45	90	46/60	48/62

Product certificates



UPHOLSTERIES

LASER

CATEGORY 2

560 gr/mtl
100% Polyester FR
Class 1
80.000+/- 10% maltindale cycles

ECOPELLE

CATEGORY 2

630 g/lin.m
83% PVC 17% Sintetico
Class 1
30.000 +/- 10% maltindale cycles

JET

CATEGORY 3

365+/- 5% g/lin.m
100% Polyester FR
Class 1
80.000+/- 10% maltindale cycles

ONE RECICLED

CATEGORY 3

525 gr/mt2
100% recycled poliester
CLASS IIM
100.000 CICLI

LYRA

CATEGORY 3

550 g/lin.m
100% Polyester
Class 1
60.000 +/- 10% maltindale cycles

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- maltindale cycles

DREAM

CATEGORY 3

375gr/mtl
100% Polyester tinto in massa
melange effetto bouclè
OEKO TEST
Class 1 - 100.000 +/- maltindale cycles

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% maltindale cycles

VELOURS

CATEGORY 3

611 gr/mtl
100% Polyester
Oeko test
50.000 +/- 10% maltindale cycles

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Superficie 100% POLYURETHANE,
Base Polyester 85%,17% Cotone
EN1021-1/BSS5852 PART 1
>100.000 EN ISO 5470-2

COCOON

CATEGORY 5

980 gr/mtl
43% viscose 33% cotone 24% li-pl
35.000 +/- 10% maltindale cycles

LANA

CATEGORY 5

500 gr/mt2
75% Lana, 25% poliammide
Class 1
100.000 maltindale cycles

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Polyester Recycled
EN 1021-1/2
80.000 % maltindale cycles

TECHNICOLOUR kvadrat

CATEGORY 5

430 g/lin. M
100% new English wool, worsted
80.000 % maltindale cycles
Ecolabel
Class 1

MAIN LINE camira

CATEGORY 5

437 g/lin.m
75% Virgin wool, 25% Lino
Class 1, Ecolabel
50.000 +/- maltindale cycles

PELLE

CATEGORY 5/6

620 g/lin.m
100% Cowhide
Class 1, EN 1021-1/2

PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% prime grain cowhide
Spessore 1,2/1,4 mm
EN1021-1/2

MONOCHROME SETT camira

CATEGORY 7

437 g/lin.m
75% Virgin wool, 25% Lino
Class 1, Ecolabel
50.000 +/- maltindale cycles

BOUCLET RUBELLI

CATEGORY 7

860 g/lin.m
40% PC, 25%PL,20%VI, 15% CO
Class 1, EN 1021-1/2
50.000 % maltindale cycles

VELLUTO DECONTRACTE' RUBELLI

CATEGORY 7

590 g/lin.m
19% CO, 61% PC,10% PL, 10% VI
40.000 % maltindale cycles

HORO RUBELLI

CATEGORY 7

495 g/lin.m
44%PL 29%CO 24%JU 3%PC
30.000 % maltindale cycles

PELLE SETA

CATEGORY 8

100% Cowhide SPESSORE1,8-2 mm
First flower ANILINE TANNING
EN1021-1/2

ZERO

CATEGORY 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % maltindale cycles

SEAT CERTIFICATE

- CL1 fire reaction homologation
- IIM fire reaction approval
- Complies with the CAM Ministerial Decree

GPP CRITERIA SITTING

All materials used to make the product are low emissives in accordance with the UNI EN 16000-9 Standard, less than 500 µg/m³.

- Plastics
- Painted metals

For this reason too, the product offered complies with the requirements required in the CAM Ministerial Decree

DISASSEMBLY

DEEP has been designed in such a way that it can be assembled at the end of its useful life, so that its parts and components can be reused, recycled or recovered for energy purposes

USE & MAINTENANCE

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart.

Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

PLASTICS

Cleaning: Plastic surfaces should generally be cleaned with a damp, soft cloth soaked in water. It is not recommended to use dry cloths, which, when rubbed, could electrostatically charge the plastic surface, attracting dust. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Absolutely avoid using acetone, trielin, ammonia, or detergents that contain even a small amount of these detergents because they can dull the shine of surfaces.

Avoid all abrasive substances, such as detergent powders, abrasive pastes, scouring pads, or rough sponges, absolutely.

Use: Avoid dragging objects that can line the material onto surfaces. Remember furthermore, that plastic materials cannot withstand direct heat sources on the surface

THE METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Usage: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

WARRANTY

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. The application of the warranty on components, external accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them is excluded. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it was designed to be used under normal conditions of support on 4 legs or on the base).