

Advanced task chair from the Quinti Sedute collection. Available in both white and black variants.



FRAME

High strength embossed polypropylene structure

SEAT & BACKREST

Seat: Made with a high-strength polypropylene interior with 2 steel bars inserted inside. A characteristic of the seat is its assembly and easy removal, also without screws. The seat is always equipped with a translator and is removable. Cold density foamed polyurethane rubber padding 58 thickness 50 mm for the seat.

Backrest: Made with thin rubber padding and exposed photo-engraved polypropylene backrest, it features height-adjustable lumbar support.

ARMS

- o Height-fixed, depth-adjustable armrests with soft polyurethane pads anchored to the backrest
- o 3D adjustable armrests at “T” anchored to the black polypropylene underseat with soft polyurethane pad

MECHANISM

CHANCE has a dedicated heavy-duty Synchron weight-activated mechanism.

Seat height adjustment and synchronized adjustment of the backrest / seat inclination equipped with an anti-shock system that can be locked in 5 positions. Seat slide.

All controls are integrated into the under seat with small levers.

The gas column complies with DIN 4550 and exceeds 4° level

Chance comes standard with the new Soft Lift, the latest generation gas column with running retarder and self-cleaning.

BASE

It's available with 3 different bases:

- “TREND” 5-spoke on polished aluminum wheels [d. 680 mm]
- “TREND” 5-spoke on wheels in black polypropylene [d. 680 mm]
- “TREND” 5-spoke on wheels made of polypropylene White [d. 680 mm]

Standard 65mm diameter double-tread black nylon wheels

Optional with the same fixing pin diameter diam 11mm:

- o Wheeled wheels, black (R06) or grey with chrome sump (R07),
- o Black wheeled wheels and self breaking (R06A),
- o Wheeled wheels “pole” with central hole
 - o Black Nylon Feet (R08)

| Measures | Seat height | Total height | Width | Depth |
|----------|-------------|--------------|-------|-------|
| cm | 42/52 | 97/107 | 68/59 | 68/40 |

SEAT CERTIFICATE

- o IIM fire reaction approval
- o EN1335-A
- o CAM

GPP CRITERIA SEAT

All materials used to make the product are low emissives in accordance with the UNI EN 16000-9 Standard, less than 500 µg/m3.

- Plastics
- Fabrics
- Faux leathers
- Padding

For this reason too, the product offered complies with the requirements required in the CAM Ministerial Decree

DISASSEMBLY

All products have been designed in such a way as to allow them to be assembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

USE & MAINTENANCE

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart.

Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

THE METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Usage: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

WARRANTY

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. The application of the warranty on components, external accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them is excluded. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it was designed to be used under normal conditions of support on 4 legs or on the base).

LASER
CATEGORY 2
560 gr/mtl
100% Polyester FR
Class 1
80.000+/- 10% maltindale cycles

ECOPELLE
CATEGORY 2
630 g/lin.m
83% PVC 17% Sintetico
Class 1
30.000 +/- 10% maltindale cycles

JET
CATEGORY 3
365+/- 5% g/lin.m
100% Polyester FR
Class 1
80.000+/- 10% maltindale cycles

ONE RECYCLED
CATEGORY 3
525 gr/mt2
100% recycled poliester
CLASS IIM
100.000 CICLI

LYRA
CATEGORY 3
550 g/lin.m
100% Polyester
Class 1
60.000 +/- 10% maltindale cycles

CHILI
CATEGORY 3
470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- maltindale cycles

DREAM
CATEGORY 3
375gr/mtl
100% Polyester tinto in massa
melange effetto bouclè
OEKO TEST
Class 1 - 100.000 +/- maltindale cycles

MELANGE
CATEGORY 3
390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% maltindale cycles

VELOURS
CATEGORY 3
611 gr/mtl
100% Polyester
Oeko test
50.000 +/- 10% maltindale cycles

ECOPELLE SOUL
CATEGORY 3
760 gr/mt2
Superficie 100% POLYURETHANE,
Base Polyester 85%, 17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

COCOON
CATEGORY 5
980 gr/mtl
43% viscose 33% cotone 24% li-pl
35.000 +/- 10% maltindale cycles

LANA
CATEGORY 5
500 gr/mt2
75% Lana, 25% poliammide
Class 1
100.000 maltindale cycles

GLAMOUR
CATEGORY 5
700 g/lin.m
100% Polyester Recycled
EN 1021-1/2
80.000 % maltindale cycles

TECHNICOLOUR kvadrat
CATEGORY 5
430 g/lin. M
100% new English wool, worsted
80.000 % maltindale cycles
Ecolabel
Class 1

MAIN LINE camira
CATEGORY 5
437 g/lin.m
75% Virgin wool, 25% Lino
Class 1, Ecolabel
50.000 +/- maltindale cycles

PELLE
CATEGORY 5/6
620 g/lin.m
100% Cowhide
Class 1, EN 1021-1/2

PELLE PREMIUM UP/ELEGANCE
CATEGORY 7
100% prime grain cowhide
Spessore 1,2/1,4 mm
EN1021-1/2

MONOCHROME SETT camira
CATEGORY 7
437 g/lin.m
75% Virgin wool, 25% Lino
Class 1, Ecolabel
50.000 +/- maltindale cycles

BOUCLET RUBELLI
CATEGORY 7
860 g/lin.m
40% PC, 25% PL, 20% VI, 15% CO
Class 1, EN 1021-1/2
50.000 % maltindale cycles

VELLUTO DECONTRACTE' RUBELLI
CATEGORY 7
590 g/lin.m
19% CO, 61% PC, 10% PL, 10% VI
40.000 % maltindale cycles

HORO RUBELLI
CATEGORY 7
495 g/lin.m
44% PL 29% CO 24% JU 3% PC
30.000 % maltindale cycles

PELLE SETA
CATEGORY 8
100% Cowhide SPESSORE1,8-2 mm
First flower ANILINE TANNING
EN1021-1/2

ZERO
CATEGORY 8
750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % maltindale cycles