

Deep poltroncina Design Archirivolto

DEEP HOSPITALITY is a visitor chair with built-in armrests. It is also ideal for meeting areas, waiting areas, and dining areas.



SEAT & BACKREST

The seat and backrest are made entirely of cold-foamed polyurethane rubber with a metal core.

The chair is available with or without integrated armrests made of cold-foamed polyurethane and fully upholstered.

BASE

Various types of bases are available for this armchair:

1. 4-leg base in chrome-plated or painted metal
2. 4-leg steel base, Vintage model
3. 4-leg wooden base (natural, moka, walnut, or black)
4. 4-spoke swivel base in wood (natural, moka, walnut, or black)
5. Base in 12 mm steel wire, painted black or gold
6. Shop 4-spoke base on feet
7. Leggera 4-spoke base on feet or on casters (model R05)
8. "Leggera" 5-spoke aluminum base on wheels (R05)

ACCESSORIES

Dual-tread wheels with a diameter of 65 mm, available in standard or rubber-tired versions, can be free-rolling [standard] or self-braking.

Black polypropylene writing tablet with panic release, compatible with the 4-leg or sled-base versions



DIMENSIONS

- | | |
|--|-----------------------------|
| 1 . Armchair with or without arms 4 metal legs | L55/43 P 57/46 H77/46 |
| 2 . Armchair with or without arms 4 Vintage legs | L55/43 P 57/46 H77/46 |
| 3 . Armchair with or without arms base 4 spokes Shop | L60/43 P 60/46 H76/86-45/55 |
| 4 . Armchair with or without arms rod frame | L55/43 P 57/46 H77/46 |
| 5 . Armchair with or without arms 4 wooden spokes | L70/43 P 70/46 H77/46 |
| 6 . Armchair with or without arms 4 spokes base on casters or feet | L70/43 P 70/46 H80/90-45/55 |
| 7 . Armchair with or without arms 5 spokes on casters | L70/43 P 70/46 H80/90-45/55 |
| 8 . Armchair with or without arms 4 wooden legs | L55/43 P 60/46 H78/47 |

UPHOLSTERYES

LASER

CATEGORY2

560 gr/mtl
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

VELOURS

CATEGORY3

611 gr/mtl
100% Poliestere
Oeko test
50.000 +/- 10% cicli Maltindale

PELLE PREMIUM UP/ELEGANCE

CATEGORY7

100% Pelle bovina Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

ECOPELLE

CATEGORY2

630 g/lin.m
83% PVC 17% Sintetico
Classe 1
30.000 +/- 10% cicli Maltindale

ECOPELLE SOUL

CATEGORY3

760 gr/mt2
Superficie 100% POLIURETANO,
Base Poliestere 85%, 17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

MONOCHROME SETT **camira**

CATEGORY7

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

JET

CATEGORY3

365 +/- 5% g/lin.m
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

COCOON

CATEGORY5

980 gr/mtl
43% viscosa 33% cotone 24% li-pl
35.000 +/- 10% cicli Maltindale

BOUCLET **RUBELLI**

CATEGORY7

860 g/lin.m
40% PC, 25% PL, 20% VI, 15% CO
Classe 1, EN 1021-1/2
50.000 % cicli Maltindale

ONE RECICLE

CATEGORY3

525 gr/mt2
100% recycled polyester
CLASSE 1IM
100.000 CICLI

LANA

CATEGORY5

500 gr/mt2
75% Lana, 25% poliammide
Classe 1
100.000 cicli Maltindale

VELLUTO DECONTRACTE' **RUBELLI**

CATEGORY7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10% VI
40.000 % cicli Maltindale

LYRA

CATEGORY3

550 g/lin.m
100% Poliestere
Classe 1
60.000 +/- 10% cicli Maltindale

GLAMOUR

CATEGORY5

700 g/lin.m
100% Poliestere Recycled
EN 1021-1/2
80.000 % cicli Maltindale

HORO **RUBELLI**

CATEGORY7

495 g/lin.m
44% PL 29% CO 24% JU 3% PC
30.000 % cicli Maltindale

CHILI

CATEGORY3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- cicli Maltindale

TECHNICOLOUR **kvadrat**

CATEGORY5

430 g/lin. M
100% new English wool, worsted
80.000 % cicli Maltindale
Ecolabel
Classe 1

PELLE SETA

CATEGORY8

100% Pelle bovina SPESSORE 1,8-2 mm
Primo fiore CONCIA ALL'ANILINA
EN1021-1/2

DREAM

CATEGORY3

375 gr/mtl
100% Poliestere tinto in massa
melange effetto bouclè
OEKO TEST
Classe 1 - 100.000 +/- cicli Maltindale

MAIN LINE **camira**

CATEGORY5

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

ZERO

CATEGORY8

750 g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cicli Maltindale

Deep poltroncina Design Archirivolto

Quinti®

MELANGE

CATEGORY3

390 g/lin.m

100% Trevira CS

Classe 1

80.000 +/- 10% cicli Maltindale

PELLE

CATEGORY5/6

620 g/lin.m

100% Pelle bovina

Classe 1, EN 1021-1/2

SEAT CERTIFICATES

- IIM fire resistance certification
- Complies with the CAM Ministerial Decree
- EN 16139

SEAT CRITERIA GPP

All materials used in the manufacture of the product are low-emitting, in accordance with the UNI EN 16000-9 standard, with emissions below 500 µg/m³.

- Plastics
- Painted metals

For this reason as well, the product offered complies with the requirements set forth in the CAM Ministerial Decree.

DISASSEMBLY

DEEP has been designed to allow for disassembly at the end of its useful life, so that its parts and components can be reused, recycled, or recovered for energy purposes.

USE & MAINTENANCE

To ensure optimal care of the products and to preserve the characteristics of the materials from which they are made, a few simple precautions are necessary.

FABRICS

Cleaning: Refer to the care and washing instructions provided in the fabric information sheet of the color chart. Use: It is recommended to handle with care, as the fabrics can be torn or cut.

LEATHER

Cleaning: Clean with a damp white cloth soaked in water only. Use high-quality leather cleaning products, carefully following the manufacturer's instructions. If in doubt, test the product on an inconspicuous area to check the results, waiting at least 24 hours to see if any issues arise.

Use: Please remember that leather is a delicate material; therefore, we recommend handling it with care.

PLASTICS

Cleaning: Plastic surfaces should generally be cleaned with a soft, damp cloth soaked in water. The use of dry cloths is not recommended, as rubbing with them could cause the plastic surface to become electrostatically charged, attracting dust. For stubborn stains, you may dilute a small amount of mild liquid soap in water. Under no circumstances should you use acetone, trichloroethylene, ammonia, or detergents containing even a small amount of these substances, as they can dull the surface's shine.

Avoid all abrasive substances under any circumstances, such as powdered detergents, abrasive pastes, scouring pads, or rough sponges.

Use: Avoid dragging objects across the surfaces that could scratch the material. Also, keep in mind that plastic materials cannot withstand direct heat sources on their surface.

METALS

Cleaning: Both metal surfaces—whether made of steel or aluminum—and painted surfaces should be cleaned with a soft, damp cloth soaked in warm water. For stubborn stains, you may dilute a small amount of mild liquid soap in water. Always dry the surface after cleaning with a soft cloth or chamois. Do not use creams or pastes to clean steel; do not use chlorine, bleach, or other harsh detergents. We do not recommend using abrasive pastes, scouring pads, or abrasive sponges, as they can scratch metal surfaces. Use: Be careful with food stains such as coffee, cola, and fruit juices, which can leave permanent stains on surfaces.

QUINTI guarantees that the products will retain their characteristics for 6 years from the date of delivery, subject to normal wear and tear and provided they are used in accordance with the instructions provided. QUINTI will replace, at no cost, any product found to be non-compliant with this warranty, without assuming any further liability of any kind. This warranty does not apply to components, external accessories, or materials supplied by the purchaser and applied to the products for the purpose of customizing them. To ensure optimal maintenance of the products and to preserve the characteristics of the materials from which they are made, a few simple precautions are necessary.

All seating products offered are SAFE in accordance with EU Regulation 2023/988 on General Product Safety (GPSR), reinforced by UNI EN certifications.

The company assumes no liability in the event of improper use (such as standing on the product or using it as a step stool, or rocking it in a way that could compromise its operation and the user's safety). To lift or move the product, grip the supporting structure firmly. The product must not be subjected to off-center loads; it is designed for use under normal conditions, supported on all four legs or on the base.

