



IFIKAT ♦ CERTIFICATE ♦ 認證證書 ♦ CERTIFICADO ♦ СЕРТИФИКАТ

CERTIFICATE

No. Z2 066213 0141 Rev. 01

Holder of Certificate: **Tiptiptap OÜ**
Iru, Jõelähtme vald
Saha-Loo tee 8
74206 Harjumaa
ESTONIA

Certification Mark:



Product: **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713282363-11

Valid until: 2028-07-25

Date, 2023-09-29

(Ulrich Sommer)

CERTIFICATE

No. Z2 066213 0141 Rev. 01

Model(s):

RS001, RS002, RS003, RS100, RS101, RS102, RS103, RS105, RS106, RS107, RS108, RS109, RS110, RS110-2, RS110-2L, RS111, RS112, RS112-1, RS112-2, RS115, RS116, RS116-1, RS117, RS118, RS119, RS120, RS121, RS122, RS123, RS124, RS125 S, RS125 L, RS127, RS128, RS130, RS201, RS201 S, RS210, RS211, RS212, RS213, RS310, RS 310-1, RS310-2, Z201

Parameters:

RS001	L/W/H: 1.1 / 0.63 / 0.6 m
RS002	L/W/H: 2.86 / 1.25 / 0.60 m
RS003	L/W/H: 2.52 / 1.79 / 0.96 m
RS100	L/W/H: 3.17 / 1.63 / 2.15 m
RS101	L/W/H: 0.10 / 0.95 / 1.77 m
RS102	L/W/H: 1.63 / 0.10 / 2.15 m
RS103	L/W/H: 1.63 / 1.63 / 2.15 m
RS105	L/W/H: 2.80 / 1.15 / 1.30 m
RS106	L/W/H: 2.59 / 0.95 / 2.15 m
RS107	L/W/H: 2.59 / 0.95 / 2.15 m
RS108	L/W/H: 4.18 / 2.24 / 2.15 m
RS109	L/W/H: 2.50 / 1.65 / 2.36 m
RS110	L/W/H: 2.27 / 1.99 / 2.42 m
RS110-2	L/W/H: 2.65 / 2.33 / 2.42 m
RS110-2L	L/W/H: 2.65 / 2.33 / 1.70 m
RS111	L/W/H: 2.52 / 0.99 / 2.20 m
RS112	L/W/H: 2.55 / 1.00 / 2.22 m
RS112-1	L/W/H: 0.99 / 0.95 / 2.22 m
RS112-2	L/W/H: 1.65 / 0.95 / 2.22 m
RS115	L/W/H: 1.64 / 1.64 / 2.16 m
RS116	L/W/H: 1.64 / 1.64 / 2.16 m
RS116-1	L/W/H: 2.20 / 2.20 / 2.16 m
RS117	L/W/H: 3.54 / 0.95 / 2.15 m
RS118	L/W/H: 2.46 / 1.64 / 2.16 m
RS119	L/W/H: 3.14 / 1.64 / 2.16 m
RS120	L/W/H: 2.53 / 2.82 / 2.16 m
RS121	L/W/H: 6.26 / 3.99 / 2.16 m
RS122	L/W/H: 3.54 / 0.95 / 2.41 m
RS123	L/W/H: 4.02 / 2.07 / 2.16 m
RS124	L/W/H: 1.70 / 1.70 / 1.62 m
RS125S	L/W/H: 6.51 / 3.80 / 2.16 m
RS125L	L/W/H: 6.51 / 4.34 / 2.16 m
RS127	L/W/H: 4.78 / 4.49 / 2.16 m
RS128	L/W/H: 6.31 / 6.32 / 2.15 m
RS130	L/W/H: 17.25 / 5.65 / 2.41 m
RS201	L/W/H: 1.45 / 0.95 / 1.30 m
RS201S	L/W/H: 0.73 / 0.72 / 0.96 m
RS210	L/W/H: 2.80 / 2.49 / 2.41 m
RS211	L/W/H: 3.79 / 3.60 / 2.41 m
RS212	L/W/H: 0.95 / 0.95 / 1.85 m
RS213	L/W/H: 7.59 / 5.15 / 2.17m
RS310	L/W/H: 7.46 / 6.43 / 2.86 m
RS310-1	L/W/H: 7.90 / 6.87 / 2.86 m



Product Service

CERTIFICATE

No. Z2 066213 0141 Rev. 01

RS310-2 L/W/H: 9.55 / 7.98 / 3.66 m
Z201 L/W/H: 3.52 / 0.95 / 2.41 m

**Tested
according to:**

EN 1176-1:2017