Product

CERTIFICATE

No. Z2 17 03 96285 001

Holder of Certificate: **LLC Atrix**
St. Borkovskaya, d. 16
445024 Togliatti
RUSSIAN FEDERATION

Production Facility(ies): 96285

Certification Mark:

Product: **Playground equipment**

Model(s): **RMF series**

Parameters: Made of EPDM (15 mm EPDM layer and EPDM deco elements, hollow, reinforced with 10 mm fiberglass sharp)

Models and technical data, please see attachment.

Tested according to: EN 1176-1:2008

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 713084943-2

Valid until: 2022-03-14

Date, 2017-03-23 (Jens Biesenack)

TÜV SÜD Product Service GmbH · Zertifizierstelle · Ridlerstraße 65 · 80339 München · Germany

CERTIFICAT ◆ CERTIFICADO ◆ СЕРТИФИКАТ ◆ 認証証書 ◆ ATE
READYMADE Verlässlichkeit für Architekten

ATE ◆ 認証証書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Attachment to Certificate No. Z2 17 03 96285 001

Product

Models and technical data of combination playground equipment
Types: RMF

Measurements (overall) in mm:

Model:	Length x Width x Height;	critical falling height
RMF 1.01:	230 x 230 x 200 mm;	200 mm
RMF 1.03:	230 x 230 x 400 mm;	400 mm
RMF 2.03:	390 x 390 x 450 mm;	450 mm
RMF 3.02:	1870 x 1870 x 330 mm;	330 mm
RMF 3.03:	2260 x 2260 x 330 mm;	330 mm
RMF 4.01:	1750 x 1350 x 850 mm;	800 mm
RMF 4.02:	1900 x 1450 x 950 mm;	800 mm
RMF 4.04:	1850 x 1450 x 950 mm;	950 mm
RMF 4.05:	2900 x 2200 x 850 mm;	800 mm
RMF 4.07:	1700 x 1350 x 800 mm;	800 mm
RMF 4.08:	1850 x 1450 x 950 mm;	950 mm
RMF 4.10:	1800 x 1450 x 850 mm;	800 mm
RMF 4.11:	1800 x 1450 x 850 mm;	800 mm
RMF 4.12:	1800 x 1800 x 520 mm;	500 mm
RMF 4.13:	1800 x 1450 x 800 mm;	800 mm
RMF 4.14:	1750 x 1450 x 1000mm;	800 mm
RMF 4.17:	1850 x 1350 x 850 mm;	800 mm
RMF 4.18:	1800 x 1800 x 500 mm;	500 mm
RMF 4.20:	1850 x 1450 x 1000 mm;	850 mm
RMF 4.21:	2300 x 1800 x 700 mm;	700 mm
RMF 4.25:	1800 x 1450 x 1000 mm;	800 mm
RMF 4.27:	1800 x 1350 x 800 mm;	800 mm
RMF 4.31:	1750 x 1350 x 850 mm;	800 mm
RMF 4.34:	5000 x 1500 x 550 mm;	550 mm
RMF 4.35:	1750 x 1700 x 900 mm;	800 mm
RMF 4.37:	1800 x 1800 x 700 mm;	700 mm
RMF 4.39:	1750 x 1350 x 850 mm;	850 mm
RMF 4.40:	405 x 405 x 900 mm;	900 mm
RMF 4.41:	870 x 800 x 470 mm;	470 mm
RMF 4.42:	405 x 405 x 700 mm;	700 mm
RMF 4.43:	405 x 405 x 700 mm;	700 mm
MF 4.44:	1750 x 1350 x 850 mm;	850 mm
MF 4.45:	405 x 405 x 600 mm;	600 mm
MF 4.46:	405 x 405 x 700 mm;	700 mm
MF 4.50:	405 x 405 x 900 mm;	900 mm
MF 4.51:	405 x 405 x 900 mm;	900 mm
MF 4.53:	1800 x 1800 x 650 mm;	650 mm
MF 4.54:	1750 x 1350 x 850 mm;	850 mm
MF 4.56:	1800 x 1800 x 520 mm;	500 mm
MF 4.59:	1750 x 1350 x 900 mm;	850 mm

ate, 2017-03-23

READYMADE Verlässlichkeit für Architekten