KATANA



100% SYNTHETIC

SPORT

API SP / JASO MA2

PAO & ESTER TECHNOLOGY

Available viscosity grades :

5W-40 / 10W-30 / 10W-40 / 10W-50 / 10W-60 / 15W-50

KATANA is a 100% synthetic 4-stroke motorcycle engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. It offers excellent protection even at full power and guarantees the best engine efficiency at high revs. Ideal for roadsters, trail bikes and sporty GTs, it promotes sharper revs and smooth, fast gear changes.

PACKING UNITS :



TECHNICAL DATA :

TEST	METHOD	TYPICAL VALUES						MEASURE UNITS
		5W-40	10W-30	10W-40	10W-50	10W-60	15W-50	
Density at 20°C	ASTM D4052	0,853	0,857	0,856	0,857	0,856	0,859	g/cm^3
Viscosity at 40°C	ASTL D445 or ASTM D7279	80,2	72,4	88	120,7	162	125,7	Mm^2/s
Viscosity at 100°C	ASTL D445 or ASTM D7279	13,27	11,18	13,52	17,8	23,49	18,3	Mm^2/s
Viscosity Index (VIE)	ASTM D2270	168	146	156	164	175	163	-
Pour point	ASTM D97	-45	-30	-33	-33	-33	-27	°C
Flash point	ASTM D92	236	212	248	228	252	260	°C
TBN	ASTM D2896	7,1	7,1	7,1	7,1	7,1	7,1	mg KOH/g

IPONE

Chemin La Meunière 13480 CABRIES – TÉL : +33 (0)4 42 94 05 65
info@ipone.fr - https://www.ipone.com/