KATANA

OFF-ROAD



100% SYNTHETIC

SPORT

API SP / JASO MA2

PAO & ESTER TECHNOLOGY

Available viscosity grades :

10W-40 / 10W-50 / 10W-60

KATANA OFF-ROAD is a 100% synthetic 4-stroke motorcycle engine oil made of high-quality polyalphaolefins (PAOs), esters and additives. Designed to offer very high off-road performance, it guarantees maximum protection under heavy load and excellent clutch control. Ideal for cross, enduro and enduro trail bikes, it promotes sharper revs and smooth, fast gear changes.

PACKING UNITS :



TECHNICAL DATA :

TEST	METHOD	TYPICAL VALUES			MEASURE UNITS
		10W-40	10W-50	10W-60	
Density at 20°C	ASTM D4052	0,867	0,872	0,856	g/cm^3
Viscosity at 40°C	ASTL D445 or ASTM D7279	86	106	161,8	Mm^2/s
Viscosity at 100°C	ASTL D445 or ASTM D7279	13,82	18,1	23,49	Mm^2/s
Viscosity Index (VIE)	ASTM D2270	169	190	175	-
Pour point	ASTM D97	-42	-42	-42	°C
Flash point	ASTM D92	252	224	264	°C
TBN	ASTM D2896	7,4	7,4	7,4	mg KOH/g

IPONE

Chemin La Meunière 13480 CABRIES – TÉL : +33 (0)4 42 94 05 65
info@ipone.fr - https://www.ipone.com/