R4000



SEMI-SYNTHETIC +

ADVANCED

ESTER TECHNOLOGY

API SP / JASO MA2

Available viscosity grades:

10W-30 / 10W-40 / 10W-50 / 15W-50 / 20W-50

R4000 is a semi-synthetic 4-stroke motorcycle engine oil made of high-quality esters and additives. Designed to provide long-lasting engine protection, it extends engine life and reduces oil consumption. It is suitable for all engine sizes and is the ideal choice for riders looking for a reliable, high-performance solution for their bike.

PACKING UNITS :



TECHNICAL DATA :

TEST	METHOD	TYPICAL VALUES					MEASURE UNIT
		10W-30	10W-40	10W-50	15W-50	20W-50	
Density at 20°C	ASTM D4052	0,87	0,866	0,869	0,869	0,882	g/cm^3
Viscosity at 40°C	ASTL D445 or ASTM D7279	74,8	95,7	122,6	133,5	163,8	Mm^2/s
Viscosity at 100°C	ASTL D445 or ASTM D7279	11,3	13,9	18	18	18,5	Mm^2/s
Viscosity Index (VIE)	ASTM D2270	143	148	163	150	127	-
Pour point	ASTM D97	-33	-33	-33	-30	-33	°C
Flash point	ASTM D92	232	232	232	248	258	°C
TBN	ASTM D2896	8,3	7,1	8,3	8,3	8,3	mg KOH/g

IPONE

Chemin La Meunière 13480 CABRIES – TÉL : +33 (0)4 42 94 05 65
info@ipone.fr - https://www.ipone.com/