

AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV
= ISO 9001 =

OGGETTO DELLA CERTIFICAZIONE: Sviluppo, produzione e commercializzazione di tessuti tecnici in fibra di vetro e in altre fibre COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =

OBJECT OF CERTIFICATION:
Development, manufacture and trade of technical fabrics made of fiberglass and of other fibers

# TECHNICAL SPECIFICATION

# ARTICLE 0098-A

ARTICLE DESCRIPTION				
<b>THREADS</b> SP 04/02/10 (UNI EN 1049-2)	Warp	16 ± 1 yarns / dm (leno)		
	Weft	8,5 ± 1 yarns / dm		
<b>MESH WIDTH</b> SP 04/02/11	Measured between yarn midpoints	approx. 12,5 x 11,8 mm		
WEIGHT	Raw mesh	78 g/m² ± 5%		
SP 04/02/12 (ISO 3374)	Finished mesh	98 g/m² ± 5%		

#### MAIN FEATURES

MAIN APPLICATION (S)	Wall plaster reinforcement.		
COMPOSITION	Fiberglass		approx. 80 %
COMPOSITION	Alkali resistant finish		approx. 20 %
RESISTANCE TO TENSILE		Breaking strength	Elongation
STRENGTH	Warp	Average value 1650 N/5 cm	4,5 % ± 1
SP 04/02/13 (ISO 4606)	Weft	Average value 1400 N/5 cm	4,5 % ± 1
	1	· ·	

### STANDARD PACKAGING

Mesh width 1000 mm - roll length 50 m - on cardboard core and in polythene

1 pallet of 110/130/120 cm contains 40 rolls i.e. 2000 m<sup>2</sup>

### NOTES

Specifications (SP) are the internal version of the national norms reported in brackets. The SP's differ from the norms for a few necessary modification of the procedures which do not influence the test results. A copy of the SP's is available on request.

Above data are based on our experience. They are liable to amendments and should be verified by the customer in case of special uses. In order to verify that the technical data sheet in the hands of the customer is updated, its date should be reported on the order.

**UPDATED 07/01/2009** 

PLANT MNG.



