

GAVAZZI

AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV
= ISO 9001 =
OGGETTO DELLA CERTIFICAZIONE:
Sviluppo, produzione e commercializzazione
di tessuti tecnici in fibra di vetro e in altre fibre

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =
OBJECT OF CERTIFICATION:
Development, manufacture and trade of technical
fabrics made of fiberglass and of other fibers

TECHNICAL SPECIFICATION

ARTICLE 1260-A

ARTICLE DESCRIPTION

THREADS SP 04/02/10 (UNI EN 1049-2)	Warp	12 ± 1 yarns / dm (leno)
	Weft	6,2 ± 1 yarns / dm
MESH WIDTH SP 04/02/11	Measured between yarn midpoints	approx. 16,7 x 16,1 mm
WEIGHT SP 04/02/12 (ISO 3374)	Raw mesh	260 g/m² ± 5%
	Finished mesh	305 g/m² ± 5%

MAIN FEATURES

MAIN APPLICATION (S)	Reinforcement of concrete floor foundation and resin floorings. Fiberglass mesh for asphalt reinforcement.		
COMPOSITION	Fiberglass		approx. 87 %
	Alkali resistant finish		approx. 13 %
RESISTANCE TO TENSILE STRENGTH SP 04/02/13 (ISO 4606)	Breaking strength		Elongation
	Warp	Average value 3200 N/5 cm	4,0 % ± 1
	Weft	Average value 3200 N/5 cm	4,0 % ± 1

STANDARD PACKAGING

Mesh width 1000 mm - roll length 50 m - on cardboard core and in polythene

1 pallet of 110/130/120 cm contains 16 rolls i.e. 800 m²

NOTES

Specifications (SP) are the internal version of the national norms reported in brackets. The SP's differ from the norms for a few necessary modification of the procedures which do not influence the test results. A copy of the SP's is available on request.

Above data are based on our experience. They are liable to amendments and should be verified by the customer in case of special uses. In order to verify that the technical data sheet in the hands of the customer is updated, its date should be reported on the order.

UPDATED 07/01/2009

PLANT MNG.

