GAVAZZI TESSUTI TECNICI S.p.A. S.U.
Sede Centrale / Headquarter:
Via Gavazzi, 3 – 23801 Calolziocorte (LC) - ITALIA
Tel. +39 0341 641051 r.a. – Fax +39 0341 633004 / +39 0341 644823
E-mail: info@gavazzispa.it – www.gavazzispa.it

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ CERTIFICATO DA DNV GL = ISO 9001 =

Oggetto della Certificazione:
Sviluppo, produzione e commercializzazione di tessuti tecnici in fibra di vetro e in altre fibre.

TECHNICAL SPECIFICATION		**GAVADES**	
Water-based adhesive for fiberglass wall-coverings GAVATEX			
ARTICLE DESCRIPTION			
CONSISTENCY	Creamy paste		
COLOUR	White	**DRY SOLID CONTENT**	23 %
DENSITY	1,04 g/cm³	**pH**	8,5
BROOKFIELD VISCOSITY	100 mPa . s	6 Rotor – rpm 5	
STORAGE	Avoid storing for a long period at temperature under 0° C .		
INFLAMMABILITY	no	**HEALTH AZARD**	no
APPLICATION DATA AT +23°C AND 50% R.H.			
APPLICATION TEMPERATURE RANGE		From + 10°C to + 35°C	
TIME	**WAITING**	From 0 to 10 minutes	
	OPEN	Maximum 30 minutes	
	SETTING	Approx. 6-8 hours	
	FINAL SETTING	Approx. 48 hours	
FINAL PERFORMANCE DATA			
RESISTANCE TO	**AGEING**	Excellent	
	TEMPERATURE	Max +80°C	
	DAMP	Good	
	MOULD	Good	
CONSUMPTION	Depends on the surface on which it is applied , approx. consider 300-400 g/m²		
STANDARD PACKAGING			
1 palet 80/120/120 cm contains 33 buckets i.e. 660 kg net – 705 kg gross			
NOTES			
Above date are based on our experience. They are liable to amendments and should be verified by the custode in case of special use. In order to verify that the tecnica data sheet in the hands of the custode is updated. Its date should be reported on the order.			
UPDATED 06/09/2018		**TECHNICAL MNG.** Signed on original copy	