



GAVAZZI TESSUTI TECNICI S.p.A. S.U.

Sede Centrale / Headquarter:

Via Gavazzi, 3 - 23801 Calolziocorte (LC) – ITALIA

Tel. +39 0341 641051 r.a. - Fax +39 0341 633004 / +39 0341 644823

E-mail: info@gavazzispa.it - www.gavazzispa.it

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL
= ISO 9001 =**

Oggetto della Certificazione:

Sviluppo, produzione e commercializzazione
di tessuti tecnici in fibra di vetro e in altre fibre

APPLICATION INSTRUCTION GAVATEX CLASS

ATTENTION

Check the product before application

Any defect should be claimed at this stage

Application of the product implies acceptance of the same

When covering adjacent surfaces, use only rolls with identical serial number, printed on the outside of the box

SURFACE PREPARATION:

The surface must be perfectly dry, clean and stable

Remove old wall-coverings which could come off

In case of highly absorbent walls, it is recommended to treat the surface with GAVADES adhesive diluted with 50%-70% water

APPLICATION:

Prepare the fabric allowing for 5-10 cm in excess of the height of the wall

To reach class B-s1,d0 to fire reaction

Spread evenly **GAVADES** diluted with 10% water on the wall by means of a roller

To obtain a better aesthetic effect, spread on the dry fabric a new layer of GAVADES diluted with 30% water by means of a roller

Consumption 200-350 g/m²

To reach class A1 to fire reaction

Mix **KERABOND white** cementitious glue - by Mapei with 35% water to obtain a homogeneous mixture

Use a mixer to avoid lumps formation

After 5-10 minutes mix again and then spread evenly by means of a putty knife

Consumption: 1100 g/m² ±10%

Apply the fabric and press with a trowel from the center towards the edges to draw off air bubbles and to improve adherence

Join the fabric rolls side by side without overlapping them

Trim the exceeding fabric using a cutter.

FINISHING AND PAINTING:

When the glue is dry apply two layers of paint

It is recommended to use acrylic or washable paints, glossy or matt water-based enamels

Suitable colours and finishing techniques offer a wide range of decorative effects in order to achieve a rich variety of harmonious patterns in every environment

Sede legale / Registered Office: Viale Elvezia 12 - 20154 Milano - Italia / Cap.Soc. € 12.300.000 i.v. / Reg. Imp. (MI) / C.F. / P.I. IT 02672970130 / REA MI 1892085

Uff. Comm. Italia /Italy Sales Office:

20154 Milano

Viale Elvezia 12

Tel. +39 02 313345

Fax +39 02 34535822

Polo Logistico / Main Warehouse:

23801 Calolziocorte(LC)

Via Alcide De Gasperi

Tel. +39 0341 634466

Fax +39 0341 631700

Stabilimenti Produttivi/Production Plants:

24034 Cisano Bergamasco(BG)

Via delle Industrie 3

Tel. +39 035 4364072

Fax +39 035 4381913

20862 Arcore(MB)

Via Monte Cervino 66

Tel. +39 039 6014474

Fax +39 039 6015626