

GAVAZZI TESSUTI TECNICI S.p.A. S.U.

Sede Centrale / Headquarter: Via Gavazzi, 3 - 23801 Calolziocorte (LC) - ITALIA Tel. +39 0341 641051 r.a. - Fax +39 0341 633004 / +39 0341 644823

E-mail: info@gavazzispa.it - www.gavazzispa.it

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ CERTIFICATO DA DNV GL = ISO 9001 =

Oggetto della Certificazione:

Sviluppo, produzione e commercializzazione di tessuti tecnici in fibra di vetro e in altre fibre

APPLICATION INSTRUCTION GAVATEX ACUSTIC

ATTENTION

Check the product before application

Any defect should be claimed at this stage

Application of the product implies acceptance of the same

When covering adjacent surfaces, use only rolls with identical serial number, printed on the outside of the box

SURFACE PREPARATION:

The surface must be perfectly dry, clean and stable

Remove old wall-coverings which could come off

In case of highly absorbent walls, it is recommended to treat the surface with GAVADES adhesive diluted with 50%-70% water

APPLICATION:

Prepare the fabric allowing for 5-10 cm in excess of the height of the wall

GAVATEX ACUSTIC1 is fire-proof, class B-s1,d0

Spread evenly **GAVADES** diluted with 10% water on the wall by means of a roller To obtain a better aesthetic effect, spread on the dry fabric a new layer of GAVADES diluted with 30% water

by means of a roller

Consumption 350-600 g/m².

Apply the fabric and press with a trowel from the center towards the edges to draw off air bubbles and to improve adherence

Join the fabric rolls side by side without overlapping them

Trim the exceeding fabric using a cutter.

FINISHING AND PAINTING:

When the glue is dry apply two layers of paint

It is recommended to use acrylic or washable paints, glossy or matt water-based enamels.

Suitable colors and finishing techniques offer a wide range of decorative effects in order to achieve a rich variety o harmonious patterns in every environment

Tel. +39 035 4364072 Tel. +39 039 6014474 Fax +39 035 4381913 Fax +39 039 6015626