

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ **CERTIFICATO DA DNV** = ISO 9001 =

OGGETTO DELLA CERTIFICAZIONE: OBJECT OF CERTIFICATION: Sviluppo, produzione e commercializzazione

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001 =

Development, manufacture and trade of technical di tessuti tecnici in fibra di vetro e in altre fibre fabrics made of fiberglass and of other fibers

DECLARATION OF PERFORMANCE	DOP n. 1 - 0155R-A - v.02	
UNIVERSAL IDENTIFICATION PRODUCT CODE - TYPE	CE - 0155R-A	
ARTICLE	0155R-A	
EUROPEAN ASSESSMENT DOCUMENT	EAD 040016-01-0404	
EUROPEAN TECHNICAL ASSESSMENT	ETA 18/1026	
MANUFACTURER	GAVAZZI TESSUTI TECNICI S.P.A (s.u.) Via Gavazzi 3, 23801 Calolziocorte (LC) - Italy	
TECHNICAL ASSESSMENT BODY	ITC/CNR	
NOTIFIED BODY	ITC/CNR n° 0970	
ASSESSMENT SYSTEM AND VERIFICATION OF THE PERFORMANCE CONSISTENCY OF THE BUILDING PRODUCT	SYSTEM 2+	

MAIN APPLICATION (S)	Wall plaster reinforcement				
MESH WIDTH	Net light 6		6,5 x 6,5 mm ± 5 %	6,5 x 6,5 mm ± 5 %	
	Measured between yarn midpoints 8,0 x 7,1 mm ± 5 %				
% NETWORK COVERAGE	2	29 % ± 5 %			
WEIGHT	Raw mesh		120 g/m ² ± 5 %		
	Finished mesh		150 g/m ² ± 5 %		
REACTION TO FIRE CLASSIFICATION	N.A.				
RELEASE DANGEROUS SUBSTANCES	N.A.				
VALUE OF PCS	N.A.				
COMPOSITION	Fiberglass			80,0 % ± 3	
	Alkali resistant finish		20,0 % ± 3		
RESISTANCE TO TENSILE STRENGTH		Breaking strength		Elongation	
	Warp	Average value 35 N/mm		4,5 % ± 1	
	Weft	Average value 41 N/mm		5,0 % ± 1	
AFTER AGING WITH ALKALI	Warp	≥ 20 N/mm e residue ≥ 50 %			
	Weft	≥ 20 N/mm			
THICKNESS	0,40 ± 0,1 mm				

NOTE

By issuing the order it is recommended that customer communicates the date of the Declaration of Performance in his possession, in order to verify if updated.

The performance of the above mentioned product conforms to all declared performances. This declaration of responsibility is issued in accordance with EU Regulation n. 305/2011, under the sole responsibility of the above mentioned manufacturer.

Calolziocorte, 15/07/2022



