

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ CERTIFICATO DA DNV GL = ISO 9001 = OGGETTO DELLA CERTIFICAZIONE: Sviluppo, produzione e commercializzazione di tessuti tecnici in fibra di vetro e in altre fibre di tessuti tecnici in fibra di vetro e in altre fibre

COMPANY WITH

QUALITY SYSTEM

CERTIFIED BY DNV GL

= ISO 9001 =

OBJECT OF CERTIFICATION:

TECHNICAL SPECIFICATION ARTICLE 0560T07 **ARTICLE DESCRIPTION** Warp 48,8 ± 1 yarns / dm THREADS SP 04/02/10 (UNI EN 1049-2) Weft 38 ± 1 yarns / dm **MESH WIDTH** Measured between yarn approx. 2 x 2,6 mm SP 04/02/11 midpoints Raw mesh 59 g/m² ± 6 % WEIGHT SP 04/02/12 (ISO 3374) **Finished mesh** $87 \text{ g/m}^2 \pm 6 \%$ MAIN FEATURES MAIN APPLICATION (S) Heat-fastening scrim for hot-temperature coupling Fiberglass approx. 68 % COMPOSITION Heat-fastening glue (Eva Ethylene Vinyl Acetate) approx. 32 % STORAGE Store the material at a temperature < 50° C (122° F) in the original packaging , protecting it from atmospheric agents.

Usage is recommended within 12 months from delivery date. NOTES

Specifications (SP) are the internal version of the national norms reported in brackets. The SP's differ from the norms for a few necessary modification of the procedures which do not influence the test results. A copy of the SP's is available on request.

Above data are based on our experience. They are liable to amendments and should be verified by the customer in case of special uses. In order to verify that the technical data sheet in the hands of the customer is updated, its version date should be reported on the order.

TECHNICAL MNG.

¥L.

Version 1 of 12/09/2022