

Sede centrale / Headquarter
Via Gavazzi, 3
23801 Calolziocorte (LC), Italia
Tel. +39 0341 641051 | Fax +39 0341 633004

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001-ISO 50001

GAVAZZI TESSUTI TECNICI S.p.A. s.u.

TECHNICAL	SPECIFICATION

**ARTICLE B0130-A** 

ARTICLE DESCRIPTION					
THREADS	Warp	16 ± 1 yarns/dm (leno)			
SP 04/02/10 (UNI EN 1049-2)	Weft	4 ± 0,5 yarns / dm			
<b>MESH WIDTH</b> SP 04/02/11	Measured between yarn midpoints	approx. 25 x 25 mm			
WEIGHT	Raw mesh	112 g/m² ± 10 %			
SP 04/02/12 (ISO 3374)	Finished mesh	137 g/m <sup>2</sup> ± 10 %			

## **MAIN FEATURES**

COMPOSITION	Fiber Basalt		approx. 82 %
COMPOSITION	Alkali resistant finish		approx. 18 %
		Breaking strength	Elongation
RESISTANCE TO TENSILE STRENGTH  SP 04/02/13 (ISO 4606)	Warp	Average value 48 kN/m	5,5 % ± 1
	Weft	Average value 32 kN/m	4,5 % ± 1

## NOTES

Specifications (SP) are the internal version of the national norms reported in brackets. The SP's differ from the norms for a few necessary modification of the procedures which do not influence the test results. A copy of the SP's is available on request.

Above data are based on our experience. They are liable to amendments and should be verified by the customer in case of special uses. In order to verify that the technical sheet version in the hands of the customer is updated, its version should be reported on the order.

Version 1 of 10/06/2024

TECHNICAL MNG Signed on original copy

