

Sede centrale / Headquarter
Via Gavazzi, 3
23801 Calolziocorte (LC), Italia
Tel. +39 0341 641051 | Fax +39 0341 633004
info@gavazzispa.it | www.gavazzispa.it

TECHNICAL SPECIFICATION		GAVADES	
Water-I	based adhesive for fibe	rglass wall-coverings	GAVATEX
	ARTICLE DI	ESCRIPTION	
CONSISTENCY	Creamy paste		
COLOUR	White	DRY SOLID CONTENT	23 %
DENSITY	1,04 g/cm ³	рН	8,5
BROOKFIELD VISCOSITY	100 mPa . s	6 Rotor – rpm 5	
STORAGE	Avoid storing for a long po	eriod at temperature under 0° C .	
INFLAMMABILITY	no	HEALTH AZARD	no
APP	PLICATION DATA A	T +23°C AND 50%	R.H.
APPLICATION TEMPERATURE RANGE		From + 10°C to + 35°C	
TIME	WAITING	From 0 to 10 minutes	
	OPEN	Maximum 30 minutes	
	SETTING	Approx. 6-8 hours	
	FINAL SETTING	Approx. 48 hours	
	FINAL PERFO	RMANCE DATA	
RESISTANCE TO	AGEING	Excellent	
	TEMPERATURE	Max +80°C	
	DAMP	Good	
	MOULD	Good	
CONSUMPTION	Depends on the surface on which it is applied , approx. consider 300-400 g/m²		
	STANDARD	PACKAGING	
	1 palet 80/120/120 cm conta	ains 24 buckets i.e. 480 kg	net
	NO	TES	
special use.	r experience. They are liable to a		•
Version 1 o	f 24/06/2024	TECHNICAL MN	G Signed on original copy