

Sede centrale / Headquarter
Via Gavazzi, 3
23801 Calolziocorte (LC), Italia
Tal ±39 0341 641051 | Fay ±39 0341 63301

COMPANY WITH
MANAGEMENT SYSTEN
CERTIFIED BY DNV
ISO 9001-ISO 50001

GAVAZZI TESSUTI TECNICI S.p.A. s.u.

ARTICLE 0159R

ARTICLE DESCRIPTION				
THREADS SP 04/02/10 (UNI EN 1049-2)	Warp	28 ± 1 yarns / dm (leno)		
	Weft	13,5 ± 1 yarns / dm		
MESH WIDTH SP 04/02/11	Measured between yarn midpoints	approx. 7,1 x 7,7 mm		
WEIGHT SP 04/02/12 (ISO 3374)	Raw mesh	122 g/m ² ± 5 %		

MAIN FEATURES

COMPOSITION	Fiberglass		approx. 100 %
RESISTANCE TO TENSILE STRENGTH SP 04/02/13 (ISO 4606)		Breaking strength	Elongation
	Warp	Average value 1380 N/5 cm	3,5 % ± 1
	Weft	Average value 1750 N/5 cm	3,5 % ± 1

STANDARD PACKAGING

Mesh width 1000 mm - roll length to be defined - on cardboard core and in polythene

NOTES

Specifications (SP) are the internal version of the national norms reported in brackets. The SP's differ from the norms for a few necessary modification of the procedures which do not influence the test results. A copy of the SP's is available on request.

Above data are based on our experience. They are liable to amendments and should be verified by the customer in case of special uses. In order to verify that the technical data sheet in the hands of the customer is updated, its version should be reported on the order.

Version 2 of 19/09/2024

TECHNICAL MNG. Signed on original copy

