

Sede centrale / Headquarter Via Gavazzi, 3 23801 Calolziocorte (LC), Italia Tel. +39 0341 641051 | Fax +39 0341 633004

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV

GAVAZZI TESSUTI TECNICI S.p.A. s.u.

TECHNICAL SPECIFICATION		ARTICLE 0073T07	
	ARTICLE DESCRIP	PTION	
THREADS SP 04/02/10 (UNI EN ISO 7211-2)	Warp	50 ± 1 yarns / dm (leno)	
	Weft	20 ± 1 yarns / dm	
MESH WIDTH SP 04/02/11	Measured between yarn midpoints	approx. 4 x 5 mm	
WEIGHT SP 04/02/12 (ISO 3374)	Raw mesh	61 g/m ² ± 6 %	
	Finished mesh	81 g/m ² ± 6 %	
	MAIN FEATUR	ES	
MAIN APPLICATION (S)	Heat-fastening scrim for hot-temperature coupling		
COMPOSITION	Fiberglass		approx. 75 %
	Heat-fastening glue (Eva Ethylene Vinyl Acetate)		approx. 25 %
	STORAGE		
Store the material at a temperature suggestion	< 50° C (122° F) in the original processing the recommended within 12 months	packaging, protecting it from s from delivery date.	n atmospheric agents.
	NOTES		
Specifications (SP) are the internal ver a few necessary modification of the pro request.	sion of the national norms repor cedures which do not influence t	ted in brackets. The SP's d the test results. A copy of	iffer from the norms f the SP's is available
Above data are based on our experien- of special uses. In order to verify that to be reported on the order.	ce. They are liable to amendmen the technical data sheet in the ha	nts and should be verified lands of the customer is upon	by the customer in ca dated, its version shou

Version 2 of 27/05/2025

TECHNICAL MNG. Signed on original copy

