

GAVAZZI TESSUTI TECNICI S.p.A. s.u.
Sede centrale / Headquarter
Via Gavazzi, 3
23801 Calolziocorte (LC), Italia
Tel. +39 0341 641051 | Fax +39 0341 633466
info@gavazzispa.it | www.gavazzispa.it

INSTALLATION METHOD GAVATEX COLOUR

WARNINGS

Check the product before application, any defects must be reported immediately while continuing the installation implies acceptance of the product the color shade may vary from batch to batch Check the color tone and batch number, handle with care and avoid folding.

SUBSTRATE PREPARATION:

Surfaces must be dry, clean and stable remove old wallpapers that may detach for highly absorbent surfaces, apply a primer coat with GAVADES adhesive diluted with 50% water.

ADHESION:

Prepare the fabric panels taking into account the pattern ratio and always allowing 5-10 cm more than the wall height lay the panels applying them "head-to-tail", that is: the second panel must be laid upside down compared to the first and so on, to reduce any color shade issues the fabric rolls must be used according to the sequence of the batch number printed on the package spread evenly with a roller GAVADES diluted with 10% water apply the fabric and press lightly with a spatula from the center to the edges to expel any air bubbles and ensure perfect adhesion place the panels edge to edge without overlapping, avoid glue overflow that could stain and discolor the fabric, immediately wash any excess glue with a damp cloth and trim the excess fabric with a utility knife.

CLEANING:

Cleaning can be done with water only or with the addition of a neutral detergent, do not use bleach-based detergents.