

DECLARATION OF PERFORMANCE	DOP n. 1 - 0148R-A - v.04
UNIVERSAL IDENTIFICATION PRODUCT CODE - TYPE	CE - 0148R-A
ARTICLE	0148R-A
EUROPEAN ASSESSMENT DOCUMENT	EAD 040016-01-0404
EUROPEAN TECHNICAL ASSESSMENT	ETA 18/1026
MANUFACTURER	GAVAZZI TESSUTI TECNICI S.P.A (s.u.) Via Gavazzi 3, 23801 Calolziocorte (LC) - Italy
TECHNICAL ASSESSMENT BODY	ITC/CNR
NOTIFIED BODY	ITC/CNR n° 0970
ASSESSMENT SYSTEM AND VERIFICATION OF THE PERFORMANCE CONSISTENCY OF THE BUILDING PRODUCT	SYSTEM 2+

ARTICLE DESCRIPTION (EAD 040016-01-0404)			
MAIN APPLICATION (S)	Wall plaster reinforcement		
MESH WIDTH	Net light	4,5 x 3,5 mm ± 5 %	
	Measured between yarn midpoints	5,9 x 4,0 mm ± 5 %	
% NETWORK COVERAGE	34 % ± 5 %		
WEIGHT	Raw mesh	120 g/m² ± 5 %	
	Finished mesh	148 g/m² ± 5 %	
REACTION TO FIRE CLASSIFICATION	N.A.		
RELEASE DANGEROUS SUBSTANCES	N.A.		
VALUE OF PCS	N.A.		
COMPOSITION	Fiberglass	81,1 % ± 3	
	Alkali resistant finish	18,9 % ± 3	
RESISTANCE TO TENSILE STRENGTH	Breaking strength		Elongation
	Warp	Average value 40 N/mm	5,0 % ± 1
	Weft	Average value 36 N/mm	4,5 % ± 1
AFTER AGING WITH ALKALI	Warp	≥ 20 N/mm e residue ≥ 50 %	
	Weft	≥ 20 N/mm e residue ≥ 50 %	
NOTE			
By issuing the order it is recommended that customer communicates the date of the Declaration of Performance in his possession, in order to verify if updated.			

The performance of the above mentioned product conforms to all declared performances. This declaration of responsibility is issued in accordance with EU Regulation n. 305/2011, under the sole responsibility of the above mentioned manufacturer.

Calolziocorte, 09/03/2026

Technical Manager Signed on original copy

