

GAVAZZI TESSUTI TECNICI S.p.A.  
Sede centrale / Headquarter  
Via Gavazzi, 3  
23801 Calolziocorte (LC), Italia  
Tel. +39 0341 641051  
info@gavazzispa.it | www.gavazzispa.it

|                                                                                                  |                                                                                                 |
|--------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>DECLARATION OF PERFORMANCE</b>                                                                | <b>DOP n. 1 - 0148A14 - v.03</b>                                                                |
| <b>UNIVERSAL IDENTIFICATION PRODUCT CODE - TYPE</b>                                              | <b>CE – 0148A14</b>                                                                             |
| <b>ARTICLE</b>                                                                                   | <b>0148A14</b>                                                                                  |
| <b>EUROPEAN ASSESSMENT DOCUMENT</b>                                                              | <b>EAD 040016-01-0404</b>                                                                       |
| <b>EUROPEAN TECHNICAL ASSESSMENT</b>                                                             | <b>ETA 18/1026</b>                                                                              |
| <b>MANUFACTURER</b>                                                                              | <b>GAVAZZI TESSUTI TECNICI S.P.A (s.u.)<br/>Via Gavazzi 3, 23801 Calolziocorte (LC) - Italy</b> |
| <b>TECHNICAL ASSESSMENT BODY</b>                                                                 | <b>ITC/CNR</b>                                                                                  |
| <b>NOTIFIED BODY</b>                                                                             | <b>ITC/CNR n° 0970</b>                                                                          |
| <b>ASSESSMENT SYSTEM AND VERIFICATION OF THE PERFORMANCE CONSISTENCY OF THE BUILDING PRODUCT</b> | <b>SYSTEM 2+</b>                                                                                |

| ARTICLE DESCRIPTION (EAD 040016-01-0404)                                                                                                                       |                                 |                            |                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------|--------------------|
| MAIN APPLICATION (S)                                                                                                                                           |                                 | Wall plaster reinforcement |                    |
| MESH WIDTH                                                                                                                                                     | Net light                       |                            | 4,5 x 3,5 mm ± 5 % |
|                                                                                                                                                                | Measured between yarn midpoints |                            | 5,9 x 4,0 mm ± 5 % |
| % NETWORK COVERAGE                                                                                                                                             |                                 | 34 % ± 5 %                 |                    |
| WEIGHT                                                                                                                                                         | Raw mesh                        |                            | 120 g/m² ± 5 %     |
|                                                                                                                                                                | Finished mesh                   |                            | 148 g/m² ± 5 %     |
| REACTION TO FIRE CLASSIFICATION                                                                                                                                |                                 | N.A.                       |                    |
| RELEASE DANGEROUS SUBSTANCES                                                                                                                                   |                                 | N.A.                       |                    |
| VALUE OF PCS                                                                                                                                                   |                                 | N.A.                       |                    |
| COMPOSITION                                                                                                                                                    | Fiberglass                      |                            | 81,1 % ± 3         |
|                                                                                                                                                                | Alkali resistant finish         |                            | 18,9 % ± 3         |
| RESISTANCE TO TENSILE STRENGTH                                                                                                                                 |                                 | Breaking strength          | Elongation         |
|                                                                                                                                                                | Warp                            | Average value 40 N/mm      |                    |
|                                                                                                                                                                | Weft                            | Average value 36 N/mm      |                    |
| AFTER AGING WITH ALKALI                                                                                                                                        | Warp                            | ≥ 20 N/mm e residue ≥ 50 % |                    |
|                                                                                                                                                                | Weft                            | ≥ 20 N/mm e residue ≥ 50 % |                    |
| NOTE                                                                                                                                                           |                                 |                            |                    |
| By issuing the order it is recommended that customer communicates the date of the Declaration of Performance in his possession, in order to verify if updated. |                                 |                            |                    |

The performance of the above mentioned product conforms to all declared performances. This declaration of responsibility is issued in accordance with EU Regulation n. 305/2011, under the sole responsibility of the above mentioned manufacturer.

**Calolziocorte, 09/03/2026**

**Technical Manager** Signed on original copy