

NONWOVENS FOR CLOTHING, PROTECTIVE CLOTHING AND UPHOLSTERY
PRODUCT CATEGORY CLASSIFICATION: UN CPC 27922

PCR 2011:06

VERSION 4.0.0 FOR OPEN CONSULTATION. DO NOT USE OR CITE

VALID UNTIL 20XX-YY-ZZ

**DRAFT PCR FOR OPEN
CONSULTATION**

INTRODUCTION TO OPEN CONSULTATION

This draft PCR is available for open consultation until 2023-10-01. Feel free to forward the draft to any other stakeholder you might think is relevant, including colleagues and other organisations.

We are interested in comments from stakeholders on:

- General
 - o Alignment with PCRs available in other programmes for type III environmental declarations, industry-specific LCA guides or similar.
- Scope of PCR
 - o Product category definition and description
 - o Classification of product category using CPC codes
- Goal and scope, life cycle inventory and life cycle impact assessment
 - o Functional unit/declared unit
 - o System boundary
 - o Allocation rules
 - o Data quality requirements
 - o Recommended databases for generic data
 - o Impact categories and impact assessment methodology
- Additional information

Comments may be sent directly to the PCR Moderator (contact details available in Section 1). There is a template for comments on www.environdec.com that may be used.

For questions about the PCR, please contact the PCR moderator. For general questions about the International EPD® System, EPD or PCR development, please contact the Secretariat via pcr@environdec.com.

TABLE OF CONTENTS

Introduction to open consultation.....	2
1 Introduction	4
2 General information	5
2.1 Administrative information	5
2.2 Scope of PCR.....	5
3 PCR review and background information.....	7
3.1 Open consultation	7
3.2 PCR review	7
3.3 Existing PCRs for the product category	8
3.4 Reasoning for development of PCR.....	9
3.5 Underlying studies used for PCR development.....	9
4 Goal and scope, life cycle inventory and life cycle impact assessment	10
4.1 Declared UNIT.....	10
4.2 Technical specification, lifespan and reference service life (RSL)	10
4.3 System boundary	10
4.4 System diagram	13
4.5 Cut-off rules.....	13
4.6 Allocation rules	14
4.7 Data quality requirements and selection of data	15
4.8 Environmental performance indicators.....	18
4.9 Including multiple products in the same EPD.....	18
5 Content and format of EPD.....	20
5.1 EPD languages	20
5.2 Units and quantities	20
5.3 Use of images in EPD	21
5.4 EPD reporting format.....	21
6 List of abbreviations.....	28
7 References.....	29
8 Version history of PCR	30

1 INTRODUCTION

This document constitutes Product Category Rules (PCR) developed in the framework of the International EPD® System: a programme for type III environmental declarations¹ according to ISO 14025:2006, ISO 14040:2006, ISO 14044:2006, and product-specific standards such as EN 15804 and ISO 21930 for construction products. Environmental Product Declarations (EPD) are voluntary documents for a company or organisation to present transparent, consistent and verifiable information about the environmental performance of their products (goods or services).

The rules for the overall administration and operation of the programme are the General Programme Instructions (GPI), publicly available at www.environdec.com. A PCR complements the GPI and the normative standards by providing specific rules, requirements and guidelines for developing an EPD for one or more specific product categories (see Figure 1). A PCR should enable different practitioners using the PCR to generate consistent results when assessing products of the same product category.




Figure 1 The hierarchy between PCRs, standards and other documents. EN 15804 and ISO 21930 are normative standards for construction products only.

Within the present PCR, the following terminology is adopted:

- The term “shall” is used to indicate what is obligatory, i.e. a requirement.
- The term “should” is used to indicate a recommendation, rather than a requirement. Any deviation from a “should” requirement shall be justified in the PCR development process.
- The terms “may” or “can” is used to indicate an option that is permissible.

For definitions of further terms used in the document, see the normative standards.

A PCR is valid for a pre-determined period of time to ensure that it is updated at regular intervals. The latest version of the PCR is available at www.environdec.com. Stakeholder feedback on PCRs is very much encouraged. Any comments on this PCR may be sent directly to the PCR Moderator and/or the Secretariat during its development or during its period of validity.


Any references to this document shall include the PCR registration number, name and version.

The programme operator maintains the copyright of the document to ensure that it is possible to publish, update, and make it available to all organisations to develop and register EPDs. Stakeholders participating in PCR development should be acknowledged in the final document and on the website.

¹ Type III environmental declarations in the International EPD® System are referred to as EPDs, Environmental Product Declarations.

2 GENERAL INFORMATION

2.1 ADMINISTRATIVE INFORMATION

Name:	Nonwovens for clothing, protective clothing and upholstery
Registration number and version:	2011:06, version 4.0.0
Programme:	 The International EPD® System
Programme operator:	EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden. Website: www.environdec.com E-mail: info@environdec.com
PCR Moderator:	Paolo Simon Ostan, paolo.simon@mail.com
PCR Committee:	MIKO S.r.l, Asahi KASEI Corp. - M&I SBU Car Interior Division, Sage Automotive Interiors, Dr. Paolo Simon Ostan, Quota Sette S.r.l.
Date of publication and last revision:	<i>To be added by the Secretariat</i>
Valid until:	<i>To be added by the Secretariat</i>
Schedule for renewal:	<p>A PCR is valid for a pre-determined time period to ensure that it is updated at regular intervals. When the PCR is about to expire, the PCR Moderator shall initiate a discussion with the Secretariat how to proceed with updating the PCR and renewing its validity.</p> <p>A PCR may also be updated without prolonging its period of validity, provided significant and well-justified proposals for changes or amendments are presented.</p> <p>See www.environdec.com for the latest version of the PCR.</p> <p>When there has been an update of the PCR, the new version should be used to develop EPDs. The old version may however be used for 90 days after the publication date of the new version, as long as the old version has not expired.</p>
Standards and documents conformance:	General Programme Instructions of the International EPD® System, version 4.0, based on ISO 14025 and ISO 14040/14044
PCR language(s):	At the time of publication, this PCR was available in English. If the PCR is available in several languages, these are available at www.environdec.com . In case of translated versions, the English version takes precedence in case of any discrepancies.

2.2 SCOPE OF PCR

2.2.1 PRODUCT CATEGORY DEFINITION AND DESCRIPTION

This document provides Product Category Rules (PCR) for the assessment of the environmental performance of Nonwovens for clothing, protective clothing and upholstery (for different purposes other than building and agricultural materials) and the declaration of this performance by an EPD. The product category corresponds to UN CPC 27922 Nonwovens.

This PCR specifies the requirements for the LCA study and for the format and content of the EPD relevant to nonwovens used for

NONWOVENS FOR CLOTHING, PROTECTIVE CLOTHING AND UPHOLSTERY
PRODUCT CATEGORY CLASSIFICATION: UN CPC 27922

clothing, protective clothing and upholstery as for example applications to furniture, automotive interiors and other similar uses, mainly as substitutes for leather and hide. Both laminated (e.g. nonwoven with a foam as support) and non-laminated products are included in the scope of the PCR. In particular the ISIC-CPC's classification is:

- Division: 27 - Textile articles other than apparel
 - Group: 279 - Textiles n.e.c.
 - Class: 2792 - Felt and nonwovens
 - **Subclass: 27922 - Nonwovens**

The product group and CPC code shall be specified in the EPD. (CPC 27922).

2.2.2 GEOGRAPHICAL SCOPE

This PCR may be used globally.

2.2.3 EPD VALIDITY

An EPD based on this PCR shall be valid for a 5-year period starting from the date of the verification report ("approval date"), or until the EPD has been de-registered from the International EPD® System.

An EPD shall be updated and re-verified during its validity if changes in technology or other circumstances have led to:

- an increase of 10% or more of any of the declared indicators of environmental impact,
- errors in the declared information, or
- significant changes to the declared product information, content declaration, or additional environmental, social or economic information.

If such changes have occurred, but the EPD is not updated, the EPD owner shall contact the Secretariat to de-register the EPD.

3 PCR REVIEW AND BACKGROUND INFORMATION

This PCR was developed in accordance with the PCR development process described in the GPI of the International EPD® System, including open consultation and review.

3.1 OPEN CONSULTATION

3.1.1 VERSION 1.0, 2.0

Previous versions were available for open consultation via www.environdec.com.

3.1.2 VERSION 3.0

This PCR was available for open consultation from 2017-04-21 until 2017-06-21, during which any stakeholder was able to provide comments by posting on the PCR forum on www.environdec.com or by contacting the PCR moderator.

Stakeholders were invited via e-mail or other means to take part in the open consultation and were encouraged to forward the invitation to other relevant stakeholders.

3.1.3 VERSION 4.0

This PCR was available for open consultation from 2023-08-01 until 2023-10-01, during which any stakeholder was able to provide comments by contacting the PCR Moderator and/or the Secretariat.

Stakeholders were invited via e-mail or other means to take part in the open consultation and were encouraged to forward the invitation to other relevant stakeholders. The following stakeholders provided comments during the open consultation and agreed to be listed as contributors in the PCR and at www.environdec.com.

- *List of stakeholder names and affiliation (to be added after the open consultation).*

3.2 PCR REVIEW

3.2.1 VERSION 1.0 AND 2.0

Previous versions were reviewed by the Technical Committee of the International EPD® System.

3.2.2 VERSION 3.0

PCR review panel:	The Technical Committee of the International EPD® System. A full list of members is available at www.environdec.com . The review panel may be contacted via info@environdec.com . Members of the Technical Committee were requested to state any potential conflict of interest with the PCR Committee, and if there were conflicts of interest they were excused from the review.
Chair of the PCR review:	Filippo Sessa
Review dates:	2018-05-28 until 2018-10-12

3.2.3 VERSION 4.0

PCR review panel:	The Technical Committee of the International EPD® System. A full list of members is available at www.environdec.com . The review panel may be contacted via info@environdec.com .
-------------------	--

	Members of the Technical Committee were requested to state any potential conflict of interest with the PCR Committee, and if there were conflicts of interest they were excused from the review.
Chair of the PCR review:	<i>To be added by the Secretariat</i>
Review dates:	<i>To be added by the Secretariat</i>

3.3 EXISTING PCRS FOR THE PRODUCT CATEGORY

As part of the development of this PCR, existing PCRs and other internationally standardized methods that could potentially act as PCRs were considered to avoid unnecessary overlaps in scope and to ensure harmonisation with established methods of relevance for the product category. The existence of such documents was checked among the following EPD programmes and international standardisation bodies:

- International EPD® System. www.environdec.com.
- EPD Norway
- IBU
- PEP ecopassport®
- EarthSure
- EDF
- KEITI Environmental Declaration of Product
- JEMAI EcoLeaf
- JEMAI CFP Program
- UL Environment
- ASTM International EPD Program
- NSF International National Center for Sustainability Standards EPD
- SM Transparency Report Program
- FPInnovations EPD Program on wood building products
- ICC Evaluation Service Environmental Product Declaration Program
- Carbon Leadership Forum PCRs
- BRE Global EN EPD Verification Scheme
- DAPcons®
- SCS Global Services

Table 1 lists the identified PCRs and other standardized methods.

Table 1 Existing PCRs and other internationally standardized methods that were considered to avoid overlap in scope and to ensure harmonisation with established methods.

NAME OF PCR/STANDARD	PROGRAMME/ STANDARDISATION BODY	REGISTRATION NUMBER, VERSION NUMBER/DATE OF PUBLICATION	SCOPE
FABRICS	International EPD® System	PCR 2022:04 VERSION 1.0.1, 2022-08-24	No overlap in scope

The following PCR documents for other types of nonwoven products exist in the International EPD® System:

- PCR 2016:06 - Nonwoven wipes

3.4 REASONING FOR DEVELOPMENT OF PCR

This PCR was developed to enable publication of EPDs for this product category based on ISO 14025, ISO 14040/14044. The PCR enables different practitioners to generate consistent results when assessing the environmental impact of products of the same product category, and thereby it supports comparability of products within a product category.

3.5 UNDERLYING STUDIES USED FOR PCR DEVELOPMENT

The methodological choices made during the development of this PCR (declared/functional unit, system boundary, allocation methods, impact categories, data quality rules, etc.) were primarily based on the following underlying studies:

- Simon Ostan P., 2018. Life Cycle Assessment (LCA) PES microfiber nonwoven Dinamica® Auto, Dinamica® Auto Pure, Dinamica® Auto Stretch, Dinamica® Wide, rev. 3 – September 2018.
- Simon Ostan P., 2022. Life Cycle Assessment (LCA) PES microfiber nonwoven Dinamica® Nabuk Plus, rev. 2 – April 2022

4 GOAL AND SCOPE, LIFE CYCLE INVENTORY AND LIFE CYCLE IMPACT ASSESSMENT

The goal of this section is to provide specific rules, requirements and guidelines for developing an EPD for the product category as defined in Section 2.2.1.

4.1 DECLARED UNIT

The declared unit shall be:

- for unlaminated materials: 1 m² of product with unit weight in g/m²
- for laminated materials: 1 m² of finished product with unit weight in g/m² and thickness in mm and a complete description for each lamination materials including the type of the material with weight in g/m² and thickness in mm.

The declared unit shall be stated in the EPD. The environmental impact shall be given per declared unit.

This PCR uses a declared unit instead of a functional unit as all functional and qualitative aspects are not possible to capture in the same unit. These aspects should be taken into consideration when comparing EPDs based on this PCR.

4.2 TECHNICAL SPECIFICATION, LIFESPAN AND REFERENCE SERVICE LIFE (RSL)

Not applicable for this product category.

4.3 SYSTEM BOUNDARY

The scope of this PCR and EPDs based on it is cradle-to-gate plus end-of-life

The system boundary is limited to "cradle to gate plus end-of-life", excluding the product distribution and the use phase since Nonwovens for clothing and upholstery can be consider, in general, as an intermediate products and they need further processes before they can be used for the final application. They are usually manufactured to be used in a lot of different applications and sectors (e.g. furniture, automotive, clothing, etc.) and the use phase can potentially be very complex and generally unknow by the manufacturer.

4.3.1 LIFE-CYCLE STAGES

For the purpose of different data quality rules and for the presentation of results, the life cycle of the product is divided into three life cycle stages:

- Upstream processes (from cradle-to-gate)
- Core processes (from gate-to-gate)
- Downstream processes (from gate-to-grave)

In the EPD, the environmental performance associated with each of the three life-cycle stages above shall be reported separately and in aggregated form. The processes included in the scope of the PCR and belonging to each life cycle stage are described in Sections 4.3.1.1–4.3.1.3.

The three life-cycle stages above may be subdivided into modules (i.e. manufacturing of components and production of packaging for the upstream stage, manufacturing of nonwovens and dyeing and finishing operations for the core stage) and the environmental performance associated with each of the modules may be reported separately. In the results table it shall be clear which life-cycle stages (upstream, core and downstream) each of the modules is associated with.

4.3.1.1. Upstream processes

The following unit processes are part of the product system and shall be classified as upstream processes:

- extraction and processing of raw materials,

NONWOVENS FOR CLOTHING, PROTECTIVE CLOTHING AND UPHOLSTERY
PRODUCT CATEGORY CLASSIFICATION: UN CPC 27922

- recycling processes of secondary materials from other product life cycles,
- manufacturing processes for components (e.g. polymers, fibres),
- manufacturing of additives (salts, catalyst, surfactant, dyestuffs, adhesives, etc.),
- manufacturing of semi-finished goods (laminations materials, etc.),
- production of distribution and consumer packaging for the final product,
- transport of raw materials and components along the upstream supply chain,
- generation of electricity and production of fuels, steam and other energy carriers used in upstream processes.

Upstream processes not listed may also be included. All elementary flows at resource extraction shall be included, except for the flows that fall under the general cut-off rule in Section 4.5.

For modelling of infrastructure and capital goods, see Section 4.3.2.

4.3.1.2. Core processes

The following unit processes are part of the product system and shall be classified as core processes:

- transportation of materials, components and semi-finished goods to the manufacturing of the product under study,
- input materials handling,
- manufacturing of nonwovens,
- dyeing and finishing operations,
- lamination process²
- ordinary maintenance activities, more frequent than every three years,
- end-of-life treatment of manufacturing waste and wastewater, even if carried out by third parties, including transportation,
- generation of electricity and production of fuels, steam and other energy carriers used in core processes.

Core processes not listed may also be included. Manufacturing of a minimum of 99% of the total weight of the declared product including packaging shall be included.

The following processes shall not be included:

- business travel of personnel,
- travel to and from work by personnel, and
- production of distribution and consumer packaging for components, additives and semi-finished goods.

For modelling of infrastructure and capital goods, see Section 4.3.2.

4.3.1.3. Downstream processes

The following unit processes are part of the product system and shall be classified as downstream processes:

- end-of-life treatment of the used product and its packaging, including transportation, and
- generation of electricity and production of fuels, steam and other energy carriers used in downstream processes.

For modelling of infrastructure and capital goods, see Section 4.3.2.

² if applicable. If the product can be sold without the lamination phase then this process can be omitted.

4.3.2 INFRASTRUCTURE AND CAPITAL GOODS

In general, the production and end-of-life processes of infrastructure or capital goods³ used in the product system should not be included within the system boundaries. They may be included when infrastructure and capital goods are known to be relevant in terms of their environmental impact, or when a generic LCI dataset includes infrastructure/capital goods, and it is not possible, within reasonable effort, to subtract the data on infrastructure/capital goods from this dataset. If an infrastructure/capital good is produced with the intention to be used one or a few times only (e.g., a manufacturing plant or machinery constructed to produce only one product), this infrastructure/capital good shall be included.

The inclusion or exclusion of infrastructure/capital goods shall be transparently described for upstream, core and downstream processes in the LCA report and in the EPD.

If infrastructure/capital goods are included, the following disclaimer shall be included in the results sections of the LCA report and in the EPD:

The results of the impact categories abiotic depletion of minerals and metals may be highly uncertain in LCAs that include capital goods/infrastructure in generic datasets, in case infrastructure/capital goods contribute greatly to the total results. This is because the LCI data of infrastructure/capital goods used to quantify these indicators in currently available generic datasets sometimes lack temporal, technological and geographical representativeness. Caution should be exercised when using the results of these indicators for decision-making purposes.

4.3.3 OTHER BOUNDARY SETTING

4.3.3.1. Boundary towards nature

Boundaries to nature are defined as where the flows of material and energy resources leave nature and enter the technical system (i.e. the product system). Emissions cross the system boundary to nature when they are emitted to air, soil or water.

4.3.3.2. Boundary towards other technical systems

Boundaries towards other technical systems define the flow of materials and components to/from the product system under study and from/to other product systems. Processes of waste processing shall be assigned to the product system that generates the waste until the end-of-waste state is reached. The above outlined principle means that the generator of the waste shall carry the full environmental impact until the point in the product life cycle in which the end-of-waste criteria are fulfilled.

See Section 4.6.2 for further guidance.

4.3.3.3. Temporal boundary

The temporal boundary defines the time period for which the life cycle inventory data is recorded, e.g. for how long emissions from waste deposits are accounted. As default, the time period over which inputs to and outputs from the product system is accounted for shall be 100 years from the year that the LCA model best represents, considering the representativeness of the inventory data. This year shall, as far as possible, represent the year of the publication of the EPD.

4.3.3.4. Geographical boundary

The geographical boundary defines the geographical coverage of the LCA. This shall reflect the physical reality of the product under study, accounting for the representativeness of technology, input materials and input energy.

³ Examples of infrastructure and capital goods are the building in which the studied product or upstream materials or components are produced, machinery used in the manufacturing of the product or its materials or components, or vehicles used in transports in the product system. For example, if the EPD is on wind power, the power plant itself is considered the studied product and not infrastructure/capital goods. However, the buildings and machinery that make the wind turbine components are considered infrastructure/capital goods. Similarly, if the EPD is on a means of transport, the vehicle is considered the studied product and not infrastructure/capital goods.

4.4 SYSTEM DIAGRAM




Figure 2 System diagram illustrating the processes that shall be included in the product system, divided into upstream, core and downstream processes. The illustration of processes to include may not be exhaustive.

4.5 CUT-OFF RULES

A cut-off rule of 1% shall be applied. In other words, the included inventory data (not including inventory data of processes that are explicitly outside the system boundary as described in Section 4.3) shall together give rise to at least 99% of the results of any of the environmental impact categories. Also, 99% of the mass of the product content and 99% of the energy use of the product life cycle shall be accounted for. The cut-off of inventory data should, however, be avoided, and all available inventory data shall be used.

The cut-off of inventory data, based on the above cut-off rule, should be an output of a sensitivity analysis, alone or in combination with expert judgment based on experience of similar product systems. Furthermore, the cut-off shall be possible to be verify in the

verification process, hence the exclusion of inventory data based on the cut-off rule shall be documented in the LCA report, and the EPD developer shall provide the information the verifier considers necessary to verify the cut-off.

4.6 ALLOCATION RULES

Allocation can be divided into allocation of co-products, i.e. allocation of unit processes that generate several products, and allocation of waste, i.e. allocation of unit processes that generate materials that are, for example, landfilled recovered, recycled or reused, and which require further processing to cease being waste and become products (see criteria for end-of-waste state in Section 4.6.2).

The principles for allocation of co-products and allocation of waste are described separately in the following subsections

4.6.1 CO-PRODUCT ALLOCATION

The following hierarchy of allocation methods shall be followed for co-product allocation:

1. Allocation shall be avoided, if possible, by dividing the process to be allocated into sub-processes and collecting the inventory data for each sub-process.
2. If allocation cannot be avoided, the inventory data should be partitioned between the different co-products in a way that reflects the underlying physical relationships between them, i.e. allocation should reflect the way in which the inventory data changes if the quantities of delivered co-products change.
3. If a physical relationship between the inventory data and the delivery of co-products cannot be established, the inventory data should be allocated between the co-products in a way that reflects other relationships between them. For example, inventory data might be allocated between co-products in proportion to their economic values. If economic allocation is used, a sensitivity analysis exploring the influence of the choice of the economic value shall be included in the LCA report.

For key processes in the product system, Table 2 provides specific allocation guidance. For processes not listed the most suitable allocation procedure shall be used and documented.

PROCESS	MAIN PRODUCT AND CO-PRODUCTS	ALLOCATION METHOD
Raw nonwoven production	Nonwoven product 1 Nonwoven product 2 . . Nonwoven product "n"	Energy and mass flows related to the whole site production shall be allocated to Nonwoven product 1, 2...n. by mass when production processes are the same for all the products and no dedicated stages are carried out for a specific product. Otherwise input and output shall be allocated in proportion to the economic value of the products (*)
Dyeing and finishing processes	Nonwoven product 1 Nonwoven product 2 . . Nonwoven product "n"	Energy and mass flows related to the whole site production shall be allocated to Nonwoven product 1, 2...n. by mass when dyeing and finishing processes are the same for all the products and no dedicated stages are carried out for a specific product. Otherwise input and output shall be allocated in proportion to the economic value of the products (*)

Table 2 Allocation method for key processes in the product system

(*) If the economical allocation is used, a specific sensitivity analysis shall be provided to the verifier and the monitoring of the relationship between results and current economic value shall be documented and updated. The allocation method shall be justified and described in the LCA report. In case an allocation different from the physical relationship allocation is used, it shall be declared in the EPD.

4.6.2 ALLOCATION OF WASTE TREATMENT PROCESSES

Allocation of waste shall follow the polluter pays principle and its interpretation in EN 15804: "processes of waste processing shall be assigned to the product system that generates the waste until the end-of-waste state is reached." The end-of-waste state is reached when all the following criteria for the end-of-waste state are fulfilled (adapted from EN 15804):

- the recovered material, component or product is commonly used for specific purposes;
- a market or demand, identified e.g. by a positive economic value, exists for such a recovered material, component or product;

- the recovered material, component or product fulfils the technical requirements for the specific purposes and meets the existing legislation and standards applicable to products; and
- the use of the recovered material, product or construction element will not lead to overall adverse environmental or human health impacts.

The above outlined principle means that the generator of the waste shall carry the full environmental impact until the point in the product life cycle in which the end-of-waste criteria are fulfilled. Waste may have a negative economic market value, and then the end-of-waste stage is typically reached after (part of) the waste processing and further refinement, at the point at which the waste no longer has a negative market value. This allocation method is (in most cases) in line with a waste generator's juridical and financial responsibilities. See the GPI for further information and examples.

4.7 DATA QUALITY REQUIREMENTS AND SELECTION OF DATA

Life cycle inventory data are classified into specific data and generic data, where the latter can be selected generic data or proxy data. The data categories are defined as follows:

- specific data (also referred to as "primary data" or "site-specific data"):
 - data gathered from the actual manufacturing plant where product-specific processes are carried out;
 - actual data from other parts of the life cycle traced to the product under study, for example site-specific data on the production of materials or generation of electricity provided by contracted suppliers, and transportation data on distances, means of transportation, load factor, fuel consumption, etc., of contracted transportation providers; and
 - LCI data from databases on transportation and energyware that is combined with actual transportation and energy parameters as listed above.
- generic data (sometimes referred to as "secondary data"), divided into:
 - selected generic data: data (e.g. commercial databases and free databases) that fulfil prescribed data quality requirements for precision, completeness, and representativeness (see below Section 4.7.1),
 - proxy data: data (e.g. commercial databases and free databases) that do not fulfil all of the data quality requirements of "selected generic data".

Specific data shall be used for the core processes. Specific data shall be used for upstream and downstream processes, when available, otherwise generic data may be used. Generic data should be used in cases in which they are representative for the purpose of the EPD, e.g. for bulk and raw materials on a spot market, if there is a lack of specific data on the final product or if a product consists of many components.

4.7.1 RULES FOR USING GENERIC DATA

For generic data to be classified as "selected generic data", the following requirements apply:

- datasets shall be based on attributional LCA modelling (e.g., not be based on marginal data and not include credits from system expansion),
- the reference year shall be as current as possible and should be representative for the validity period of the EPD (5 years),
- the 1% cut-off rule (as described in Section A.3.3 of the GPI) shall be met on the level of the product system,
- datasets shall represent average values for a specific reference year; however, how data are generated could vary, e.g. over time, and then they should have the form of a representative annual average value for a specified reference period (such deviations shall be justified and declared in the EPD), and
- the representativeness of the data shall be assessed to be better than $\pm 5\%$, in terms of the environmental impact calculated on the basis of the data, of data that is fully representative for the given temporal, technological and geographical context.

If selected generic data that meets the above data quality requirements are not available, proxy data may be used. The environmental impacts associated with proxy data shall not exceed 10% of the overall environmental impact of the product system.

The EPD may include a data quality declaration to demonstrate the share of specific data, selected generic data and proxy data contributing to the results of the environmental impact indicators.

4.7.2 EXAMPLES OF DATABASES FOR GENERIC DATA

Table 3 lists examples of databases and datasets to be used for generic data. Please note that a data quality assessment shall be performed also for data listed in the table, and that other data that fulfil the data quality requirements may also be used.

PROCESS	GEOGRAPHICAL SCOPE	DATASET	DATABASE
Plastics	Global/European	-	Ecoinvent Industry data
Energy mixes	Regional	-	Ecoinvent
Transport	Global/European	-	Ecoinvent

Table 3 Examples of databases and datasets to use for generic data.

4.7.3 DATA QUALITY REQUIREMENTS AND OTHER MODELLING GUIDANCE PER LIFE-CYCLE STAGE

Below are further data quality requirement per life-cycle stage. Exceptions to the requirements may be accepted, if justified in the EPD; such exceptions are subject to the approval by the verifier on a case-to-case basis.

4.7.3.1. Upstream processes

- Data referring to processes upstream in a supply chain over which the EPD owner has direct management control shall be specific and collected on site.
- Data referring to processes of a supplier of main parts, packaging, or main auxiliaries should be requested from the supplier as specific data, as well as infrastructure, where relevant.
- Data on transport of main parts and components along the supply chain to a distribution point (e.g. a stockroom or warehouse) where the final delivery to the manufacturer can take place, should be specific and based on the actual transportation mode, distance from the supplier, and vehicle load.
- In case specific data is lacking, selected generic data may be used. If this is also lacking, proxy data may be used (see Section 4.7).
- For upstream processes modelled with specific data, generation of electricity used shall be accounted for in this priority:
 1. Specific electricity mix as generated, or purchased from an electricity supplier, demonstrated by a Guarantee of Origin or similar as provided by the electricity supplier.
 2. Residual electricity mix of the electricity supplier on the market.
 3. Residual electricity mix on the market⁴.
 4. Electricity consumption mix on the market⁵.

The residual electricity mix is the mix when all contract-specific electricity that has been sold to other customers has been subtracted from the total consumption mix.

“The market” in the above hierarchy shall be defined as being the (residual or consumption) grid mix of the country where the electricity is used, with exceptions for specified countries for which a sub-national electricity grid mix shall be used: Australia, Brazil, Canada, China, India, and USA.

The mix of electricity used in upstream processes shall be documented in the EPD, where relevant.

- Packaging: specific data shall be used for production of consumer packaging, if the production is under the direct control of the EPD owner or if the environmental impact of the production is more than 10% of the declared results in any of the

⁴ The composition of the residual grid mixes on the market are available for all EU countries and a few additional European countries through the Association for Issuing Bodies (AIB) at <https://www.aib-net.org/facts/european-residual-mix>.

⁵ For electricity markets without trade of Guarantees of Origin (or similar), the residual mix will, however, be identical to the consumption mix.

environmental performance indicators. In other cases, generic data may be used. When consumer packaging shows the organization's logo, the LCA report should report the exerted/non-exerted direct control on the production of consumer packaging by the organization.

4.7.3.2. Core processes

- Transport from the final delivery point of raw materials, chemicals, main parts, and components (see above regarding upstream processes) to the manufacturing plant/place of service provision should be based on the actual transportation mode, distance from the supplier, and vehicle load, if available.
- Goods: Specific data shall be used for the assembly of the product and for the manufacture of main parts as well as for on-site generation of steam, heat, electricity, etc., where relevant.
- Services: Specific data shall be used for the consumption of materials, chemicals, steam, heat, electricity, etc., necessary for execution of the service
- For electricity used in the core processes, generation of electricity used shall be accounted for in this priority:
 1. Specific electricity mix as generated, or purchased from an electricity supplier, demonstrated by a Guarantee of Origin or similar as provided by the electricity supplier.
 2. Residual electricity mix of the electricity supplier on the market.
 3. Residual electricity mix on the market⁶.
 4. Electricity consumption mix on the market⁷. This option shall not be used for electricity used in processes over which the manufacturer (EPD owner) has direct control, as long as the composition of the residual grid mix has been publicly disclosed⁸.

The residual electricity mix is the mix when all contract-specific electricity that has been sold to other customers has been subtracted from the total consumption mix.

"The market" in the above hierarchy shall be defined as being the (residual or consumption) grid mix of the country where the electricity is used, with exceptions for specified countries for which a sub-national electricity grid mix shall be used: Australia, Brazil, Canada, China, India, and USA.

The mix of electricity used in the core processes shall be documented in the EPD, where relevant.

- Waste treatment processes of manufacturing waste should be based on specific data, if available.

4.7.3.3. Downstream processes

- Scenarios for the end-of-life stage shall be technically and economically practicable and compliant with current regulations in the relevant geographical region based on the geographical scope of the EPD. Key assumptions regarding the end-of-life stage scenario shall be documented in the LCA report.

For end-of-life treatment of automotive refer to Dir. 2000/53/CE - ELV (End of Life Vehicles) only for European Union's countries. A 100% incineration scenario shall be used if no specific or generic end-of-life data for the product and market is available.

- The use of electricity in the region/country where the product and packaging end-of-life takes place (as specified in the geographical scope of the EPD) shall be accounted for in the following priority:
 1. Residual electricity mix on the market⁹.

⁶ The composition of the residual grid mixes on the market are available for all EU countries and a few additional European countries through the Association for Issuing Bodies (AIB) at <https://www.aib-net.org/facts/european-residual-mix>.

⁷ For electricity markets without trade of Guarantees of Origin (or similar), the residual mix will, however, be identical to the consumption mix.

⁸ If the composition of the residual grid mix has not been publicly disclosed, the second or third options in the above hierarchy are not feasible and thus the fourth option is the only remaining option (if the first option is not chosen).

⁹ The composition of the residual grid mixes on the market are available for all EU countries and a few additional European countries through the Association for Issuing Bodies (AIB) at <https://www.aib-net.org/facts/european-residual-mix>.

2. Electricity consumption mix on the market¹⁰.

The residual electricity mix is the mix when all contract-specific electricity that has been sold to other customers has been subtracted from the total production mix.

“The market” in the above hierarchy shall be defined as being the (residual or consumption) grid mix of the country where the electricity is used, with exceptions for specified countries for which a sub-national electricity grid mix shall be used: Australia, Brazil, Canada, China, India, and USA.

The mix of electricity used in the downstream processes shall be documented in the EPD, where relevant.

4.7.4 DATA QUALITY DECLARATION

EPDs may include a declaration of the quality of data used in the LCA calculations.

4.8 ENVIRONMENTAL PERFORMANCE INDICATORS

The EPD shall declare the default environmental performance indicators and their methods as described at the website (www.environdec.com/indicators), which includes both inventory indicators and indicators of potential environmental impact. The source and version of the impact assessment methods and characterisations factors used shall be reported in the EPD.

In addition to the mandatory default environmental performance indicators, one additional indicator may be reported in the EPD in the section of environmental impacts. Please, see Section 5.4.5.

Also, other indicators may be declared, if justified, see Section 5.4.5.

If the default list of environmental performance indicators and methods at the www.environdec.com/indicators is updated, the previous version of the list is valid in parallel to the new version during a transition period of at least 90 days, as described at the website.

Apart from inventory indicators (such as the required and optional inventory indicators listed at www.environdec.com/indicators), other inventory data may also be declared in the EPD, if relevant and useful for EPD users. Such data shall not be declared in the main body of the EPD, but in an annex.

4.9 INCLUDING MULTIPLE PRODUCTS IN THE SAME EPD

4.9.1 MULTIPLE PRODUCTS FROM THE SAME COMPANY

Several sets of results, reflecting different products, are not allowed to be declared in the same EPD. However, similar products from a single or several manufacturing sites covered by the same PCR and manufactured by the same company with the same major steps in the core processes may be grouped and thereby included in the same EPD. For such an EPD, there are three options:

- For each indicator, declare the average results of the included products. This average shall be weighted according to the production volumes of the included products, if relevant. In this option, the average content shall be declared in the content declaration.
- Declare the results of one of the included products – a representative product. The choice of the representative product shall be justified in the EPD, using, where applicable, statistical parameters. For example, the choice may be based on production volumes. In this option, the content of the representative product shall be declared in the content declaration.
- For each indicator, declare the highest result of the included products (i.e., the results of a “worst-case product”, which may be the results of one or several of the included products). In this option, the content declaration shall include the lowest amounts of recycled and biogenic content of the included products and their packaging, respectively, and the information on environmental and hazardous properties of substances shall reflect the highest share and most hazardous such substances contained in the any of the included products.

¹⁰ For electricity markets without trade of Guarantees of Origin (or similar), the residual mix will, however, be identical to the consumption mix.

The first two options are only possible if none of the declared environmental impact indicator results differ by more than 10% between any of the included products. The third option is possible also if variations are larger than 10%.

The option chosen shall be clearly described in the EPD.

4.9.2 SECTOR EPDS

The International EPD® System allows for an industry association to develop an EPD in the form of a Sector EPD. A Sector EPD declares the average product of multiple companies in a clearly defined sector in a clearly defined geographical area. Products covered in a sector EPD shall follow the same PCR and the same declared/functional unit shall be applied.

Any communication of the results from a Sector EPD should contain the information that the results are based on averages obtained from the sector as defined in the EPD. The communication shall not claim that the sector EPD results are representative for a certain manufacturer or its product.

The following information shall also be included in a Sector EPD:

- a list of the contributing manufacturers that the Sector EPD covers,
- a description of how the selection of the sites/products has been done and how the average has been determined, and
- a statement that the document covers average values for an entire or partial product category (specifying the percentage of representativeness) and, hence, the declared product is an average that is not available for purchase on the market.

5 CONTENT AND FORMAT OF EPD

EPDs based on this PCR shall contain the information described in this section. Flexibility is allowed in the formatting and layout provided that the EPD still includes the prescribed information. A generic template for EPDs is available at www.environdec.com.

The EPD content shall:

- be in line with the requirements and guidelines in ISO 14020 (Environmental labels and declarations – General principles),
- be verifiable, accurate, relevant and not misleading, and
- not include rating, judgements or direct comparison with other products¹¹.

An EPD should be made with a reasonable number of pages for the intended audience and use.

The content of EPDs published in machine-readable format shall correspond with the content of the underlying EPD.

5.1 EPD LANGUAGES

EPDs should be published in English but may also be published in additional languages. If the EPD is not available in English, it shall contain an executive summary in English including the main content of the EPD. This summary is part of the EPD and, thus, also subject to the verification process.

5.2 UNITS AND QUANTITIES

The following requirements apply for units and quantities:

- The International System of Units (SI units) shall be used where available, e.g., kilograms (kg), Joules (J) and metres (m). Reasonable multiples of SI units may be decided in the PCR to improve readability, e.g., grams (g) or megajoules (MJ). The following exceptions apply:
 - Resources used for energy input (primary energy) should be expressed as kilowatt-hours (kWh) or megajoules (MJ), including renewable energy sources, e.g., hydropower, wind power and geothermal power.
 - Water use should be expressed in cubic metres (m³)
 - Temperature should be expressed in degrees Celsius (°C),
 - Time should be expressed in the units most practical, e.g., seconds, minutes, hours, days or years.
 - Results of the environmental performance indicators shall be expressed in the units prescribed by the impact assessment methods, e.g. kg CO₂ equivalents.
- Three significant figures¹² should be adopted for all results. The number of significant digits shall be appropriate and consistent.
- Scientific notation may be used, e.g. 1.2E+2 for 120, or 1.2E-2 for 0.012.
- The thousand separator and decimal mark in the EPD shall follow one of the following styles (a number with six significant figures shown for illustration):
 - SI style (French version): 1 234,56
 - SI style (English version): 1 234.56

In case of potential confusion or intended use of the EPD in markets where different symbols are used, the EPD shall state what symbols are used for thousand separator and decimal mark.

- Dates and times presented in the EPD should follow the format in ISO 8601. For years, the prescribed format is YYYY-MM-DD, e.g., 2017-03-26 for March 26th, 2017.

¹¹ Therefore, results of normalization are not allowed to be reported in the EPD.

¹² Significant figures are those digits that carry meaning contributing to its precision. For example with two significant digits, the result of 123.45 shall be displayed as 120, and 0.12345 shall be displayed as 0.12. In scientific notation, these two examples would be displayed as 1.2*10² and 1.2*10⁻².

- The result tables shall:
 - Only contain values or the letters “ND” (Not Declared). It is not possible to specify ND for mandatory indicators. ND shall only be used for voluntary parameters that are not quantified because no data is available.¹³
 - Contain no blank cells, hyphens, less than or greater than signs or letters (except “ND”).
 - Use the value “0” only for parameters that have been calculated to be zero.
 - Footnotes shall be used to explain any limitation to the result value.

5.3 USE OF IMAGES IN EPD

Images used in the EPD, especially pictures featured on the cover page, may in themselves be interpreted as an environmental claim. Images such as trees, mountains, wildlife that are not related to the declared product shall therefore be used with caution and in compliance with national legislation and best available practices in the markets in which the EPD is intended to be used.

5.4 EPD REPORTING FORMAT

The reporting format of the EPD shall include the following sections:

- Cover page (see Section 5.4.1)
- Programme information (see Section 5.4.2)
- Product information (see Section 5.4.3)
- Content declaration (see Section)
- Environmental performance (see Section 5.4.5)
- References (see Section 5.4.9)

The following sections may be included:

- Additional environmental information (see Section 5.4.6)
- Additional social and economic information (see Section 5.4.7)

The following sections shall be included, if relevant:

- Differences versus previous versions (see Section 5.4.8)
- Executive summary in English (see Section 5.4.10)

5.4.1 COVER PAGE

The cover page shall include:

- Product name and image
- Name and logotype of EPD owner
- The text “Environmental Product Declaration” and/or “EPD”
- Programme: The International EPD® System, www.environdec.com
- Programme operator: EPD International AB
- Logotype of the International EPD® System
- EPD registration number as issued by the programme operator¹⁴

¹³ This requirement does not intend to give guidance on what indicators are mandated (“shall”) or voluntary.

¹⁴ The EPD shall not include a “registration number” if such is provided by the certification body, as this may be confused with the registration number issued by the programme operator.

NONWOVENS FOR CLOTHING, PROTECTIVE CLOTHING AND UPHOLSTERY
PRODUCT CATEGORY CLASSIFICATION: UN CPC 27922

- Date of publication (issue): 20XX-YY-ZZ
- Date of revision: 20XX-YY-ZZ, when applicable
- Date of validity; 20XX-YY-ZZ
- A note that “An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com.”
- A statement of conformity with ISO 14025.
- For EPDs covering multiple products: a statement that the EPD covers multiple products and a list of all products covered by the EPD.
- For Sector EPDs: a statement that the EPD is a Sector EPD.

In the case of EPDs registered through a regional hub (a regional or national programme based on and fully aligned with the International EPD® System through an agreement with the programme operator), “Programme”, “Programme operator”, and “Logotype” shall be expanded to include a reference to the regional programme and the organisation responsible for it.

Where applicable, the cover page shall also include the following information:

- Information about dual registration of EPD in another programme, such as registration number and logotype.
- A statement of conformity with other standards and methodological guides.

5.4.2 PROGRAMME INFORMATION

The programme information section of the EPD shall include:

- Address of programme operator: *EPD International AB, Box 210 60, SE-100 31 Stockholm, Sweden, E-mail: info@environdec.com*
- The following statement on the requirements for comparability of EPDs, adapted from ISO 14025: “EPDs within the same product category but from different programmes may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison.”
- A statement that the EPD owner has the sole ownership, liability and responsibility of the EPD
- Information about verification¹⁵ and the PCR in a table with the following format and contents:

Accountabilities for PCR, LCA and independent, third-party verification
Product Category Rules (PCR)
PCR: <name, registration number, version and UN CPC code(s)>
PCR review was conducted by: <name and organisation of the review chair, and information on how to contact the chair through the programme operator>
Life cycle assessment (LCA)
LCA accountability: <name, organization>
Third-party verification

¹⁵ If the EPD has been verified by an approved individual verifier who has received contractual assistance from a certification body that is not accredited, this certification body shall not be included in this table.

<p>Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:</p> <p><input type="checkbox"/> EPD verification by individual verifier</p> <p>Third-party verifier: <i><name, organisation, and signature of the third-party verifier></i></p> <p>Approved by: The International EPD® System</p>
<p>OR</p>
<p>Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:</p> <p><input type="checkbox"/> EPD verification by accredited certification body</p> <p>Third-party verification: <i><name, organisation></i> is an approved certification body accountable for the third-party verification</p> <p>The certification body is accredited by: <i><name of accreditation body & accreditation number, where applicable></i></p>
<p>OR</p>
<p>Independent third-party verification of the declaration and data, according to ISO 14025:2006 via:</p> <p><input type="checkbox"/> EPD verification by EPD Process Certification*</p> <p>Internal auditor: <i><name, organisation></i></p> <p>Third-party verification: <i><name, organisation></i> is an approved certification body accountable for third-party verification</p> <p>Third-party verifier is accredited by: <i><name of accreditation body & accreditation number, where applicable></i></p> <p>*For EPD Process Certification, an accredited certification body certifies and reviews the management process and verifies EPDs published on a regular basis. For details about third-party verification procedure of the EPDs, see GPI v4, Section 7.5.</p>
<p>Procedure for follow-up of data during EPD validity involves third-party verifier¹⁶:</p> <p><input type="checkbox"/> Yes <input type="checkbox"/> No</p>

5.4.3 PRODUCT INFORMATION

The product information section of the EPD shall include:

- address and contact information of the EPD owner,
- description of the organisation. This may include information on products- or management system-related certifications (e.g. ISO 14024 Type I environmental labels, ISO 9001- and 14001-certificates and EMAS-registrations) and other relevant work the organisation wants to communicate (e.g. SA 8000, supply-chain management and social responsibility),
- name and location of production site,

¹⁶ Procedure for follow-up the validity of the EPD is at minimum required once a year with the aim of confirming whether the information in the EPD remains valid or if the EPD needs to be updated during its validity period (see Sections 7.3.2 and 7.4.9 of the GPI). The follow-up can be organized entirely by the EPD owner or together with the original verifier via an agreement between the two parties. In both approaches, the EPD owner is responsible for the procedure being carried out. If a change that requires an update (see Section 6.5 of the GPI) is identified, the EPD shall be re-verified by a verifier.

- product identification by name, and an unambiguous identification of the product by standards, concessions or other means,
- identification of the product according to the UN CPC scheme system. Other relevant codes for product classification may also be included, e.g.
 - Common Procurement Vocabulary (CPV),
 - United Nations Standard Products and Services Code® (UNSPSC),
 - Classification of Products by Activity (NACE/CPA),
 - Australian and New Zealand Standard Industrial Classification (ANZSIC), or
 - Global Trade Item Number (GTIN).
- a description of the product,
- a description of the technical purpose of the product, including its application/intended use,
- a description of the background system, including the main technological aspects,
- for EPDs covering multiple products: a description of the selection of products/sites, a list of contributing manufacturers (if Sector EPD), etc. (see Section 4.9),
- geographical scope of the EPD, i.e., for which geographical location(s) of use and end-of-life the product's performance has been calculated,
- declared unit,
- a short description of the underlying LCA-based information, such as cut-off rules, data quality, allocation methods, and other methodological choices and assumptions,
- declaration of the year(s) covered by the data used for the LCA calculation and other relevant reference years,
- reference to the main database(s) for generic data and LCA software used, if relevant,
- system diagram of the processes included in the LCA, divided into the life cycle stages,
- description of the EPD system boundary: cradle-to-gate plus end-of-life,
- information on which life-cycle stages are not considered (if any), with a justification of the omission,
- Physical properties and technical performances of the product, linked to the specific use of the nonwoven:
 - weight, in g/m²
 - thickness, in mm
 - tensile strength, in N
 - tear strength, in N,
 - abrasion resistance with Martindale, in cycles
 - flammability, in speed mm/min.
 - colour fastness to light, in grey scale

Other specifications are voluntary. For applications different than the above, the parameters shall be specified in the EPD.

- references to any relevant websites for more information or explanatory materials.

This section may also include:

- name and contact information of organisation carrying out the underlying LCA study,

5.4.4 CONTENT DECLARATION

The content declaration section shall declare the weight of one unit of product, as purchased, and contain information about the content of the product in the form of a list of materials and chemical substances including information on their environmental and hazardous properties. The gross weight of each material/substance shall be declared, including a minimum of 99% of the materials/substances in one unit of product.

The content declaration does not apply to proprietary materials and substances covered by exclusive legal rights including patent and trademarks. In general, an indication that a product is “free” of a specific hazardous material or substance should be done with caution and only when relevant, following the rules in ISO 14021 on self-declared environmental claims.

Information on the hazardous properties of materials and chemical substances should follow the requirements given in the latest revision of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS),¹⁷ issued by the United Nations or national or regional applications of the GHS. As an example, the following regulations should be used for EPDs intended to be used in the European Union:

- Regulation (EC) No 1907/2006 of the European parliament and of the council of 18 December 2006 concerning the Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH); and
- Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling, and packaging of substances and mixtures.

5.4.4.1. Information about recycled materials

When a product is made in whole or in part with recycled materials the recycled material content shall be reported as proportion, by mass, of recycled fibres in the product¹⁸. Evaluation methodology shall be undertaken in accordance with ISO 14021.

The provenance of the materials (pre-consumer or post-consumer) shall be presented in the EPD as part of the content declaration.

To avoid any misunderstanding about which material that may be considered “recycled material”, the guidance given in ISO 14021 shall be considered. In brief, the standard states that:

- only pre-consumer or post-consumer materials (scraps) shall be considered in the accounting of the recycled materials, and
- materials coming from scrap reutilisation (such as rework, regrind, or scrap generated in a process and capable of being reclaimed within the same process that generated it) shall not be considered as recycled content.

5.4.5 ENVIRONMENTAL PERFORMANCE

Below subsections list the mandatory environmental performance indicators to declare in the EPD. LCA results based on additional indicators may be declared, if they are relevant for the product category, their inclusion is justified in the EPD, appropriate methods¹⁹ are used, and the results are verifiable. If the additional indicators appear to the reader to display duplicate information, the EPD shall contain an explanation of the differences between the declared indicators.

5.4.5.1. Environmental impacts

The EPD shall declare the environmental impact indicators, per declared unit, per life-cycle stage and in aggregated form, using the default impact categories, impact assessments methods and characterisation factors available at www.environdec.com/indicators.

In addition to the mandatory default environmental impact indicators, the following indicator may be reported in the EPD:

- GWP100, CML 2001 baseline. Version: January 2016. Original reference: IPCC 2013.

If the indicator is reported in the EPD the following statement shall be reported:

“This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product and packaging. As such, the indicator is identical to GWP-total except that the CF for biogenic CO₂ is set to zero”

The source and version of the impact assessment methods and characterisation factors used shall be reported in the EPD.

¹⁷ The GHS document is available at www.unece.org.

¹⁸ the total mass of the product does not include any pigments, dyes and other chemicals that potentially remain in the product after its production. Only the weight of the fibers and/or polymeric or natural based materials shall be considered.

¹⁹ If any of the following impact categories are declared in the EPD, the corresponding characterisation methods listed in EN 15804 should be used: particulate matter emissions, ionizing radiation (human health), eco-toxicity (freshwater), human toxicity (cancer effects), human toxicity (non-cancer effects) and land use related impacts/soil quality. If these impact categories and characterisation methods are used, the corresponding disclaimers listed in EN 15804 shall be declared in the EPD.

The main life-cycle stages (upstream, core and downstream) may be subdivided into modules (i.e. manufacturing of components and production of packaging for the upstream stage, manufacturing of nonwovens and dyeing and finishing operations for the core stage) and the environmental impacts associated with each of the modules may be reported separately. In the results table it shall be clear which life-cycle stages (upstream, core and downstream) each of the modules is associated with.

Alternative regional life cycle impact assessment methods and characterisation factors may be calculated and displayed in addition to the default list. If so, the EPD shall contain an explanation of the differences between the declared sets of indicators, as they may appear to the reader to display duplicate information.

5.4.5.2. Use of resources

The EPD shall declare the mandatory indicators for resource use listed at www.environdec.com/indicators per declared unit, per life-cycle stage and in aggregated form.

The EPD may declare the other optional indicators for resource use listed at www.environdec.com/indicators per declared unit, per life-cycle stage and in aggregated form.

The main life-cycle stages (upstream, core and downstream) may be subdivided into modules (i.e. manufacturing of components and production of packaging for the upstream stage, manufacturing of nonwovens and dyeing and finishing operations for the core stage) and the use of resources associated with each of the modules may be reported separately. In the results table it shall be clear which life-cycle stages (upstream, core and downstream) each of the modules is associated with.

5.4.5.3. Waste production and output flows

Waste generated along the whole life cycle production chains shall be treated following the technical specifications described in the GPI. The EPD may declare the optional indicators for waste production and output flows as listed at www.environdec.com/indicators per declared unit, per life-cycle stage and in aggregated form.

The main life-cycle stages (upstream, core and downstream) may be subdivided into modules (i.e. manufacturing of components and production of packaging for the upstream stage, manufacturing of nonwovens and dyeing and finishing operations for the core stage) and waste production and output flows associated with each of the modules may be reported separately. In the results table it shall be clear which life-cycle stages (upstream, core and downstream) each of the modules is associated with.

5.4.6 ADDITIONAL ENVIRONMENTAL INFORMATION

An EPD may declare additional environmentally relevant information, in addition to the LCA results of the section on environmental performance results. The additional environmental information may cover various aspects of specific relevance for the product, for example:

- information regarding the production technology, the production site, the characteristics of production territory, supply/delivery information and other factors such as impacts on biodiversity and noise production,
- the release of dangerous substances into indoor air, soil, and water during the use stage,
- instructions for proper use of the product, e.g. to minimise energy or water consumption or to improve the durability of the product,
- instructions for proper maintenance and service of the product, e.g. to minimise energy or water consumption or to improve the durability of the product,
- information on key parts of the product that determine its durability,
- information on recycling including, e.g. suitable procedures for recycling the entire product or selected parts and the potential environmental benefits gained,
- information on a suitable method of reuse of the product (or parts of the products) and procedures for disposal as waste at the end of its life cycle,
- information regarding disposal of the product, or inherent materials, and any other information considered necessary to minimise the product's end-of-life impacts, and
- a more detailed description of an organisation's overall environmental work, in addition to the information listed under Section 5.4.3, such as:

- the existence of any type of organised environmental activity, and
- information on where interested parties may find more details about the organisation's environmental work.

Any additional environmental information declared shall be substantiated and verifiable, and be derived using appropriate methods and be specific, accurate, not misleading, and relevant to the specific product. Quantitative information is preferred over qualitative information.

The additional environmental information shall not include LCA results, with some exceptions:

- If the EPD owner wants to display results of several scenarios for use or end-of-life stages, the most representative scenario (for the geographical scope of the EPD) shall be declared in the section on environmental performance results, and the other scenarios shall be declared in the section on additional environmental information.
- The LCA results of an alternative modelling approach may be declared as additional environmental information, if such an alternative modelling approach is explicitly allowed by the applicable PCR or the GPI. According to this PCR, alternative GWP-biogenic results may be declared, which considers the effect of long-term storage of biogenic carbon (see next bullet point).
- Additional information may be included in order to satisfy particular customer needs or requests (e.g. the trend of environmental performances in the years, the energy saving in the production phase).
- The additional environmental information may include information on permanent (more than 100 years) storage of biogenic carbon, either in the product, in a landfill, or as a consequence of applying carbon capture and storage (CCS) to the incineration of biogenic carbon, and how this would influence GWP-biogenic results if the GWP-biogenic indicator would allow consideration of such storage.

5.4.7 ADDITIONAL SOCIAL AND ECONOMIC INFORMATION

The EPD may also include other relevant social and economic information as additional and voluntary information. This may be product information or a description of an organisation's overall work on social or economic sustainability, such as activities related to supply chain management or social responsibility.

Any additional social and economic information declared shall be substantiated and verifiable, and be derived using appropriate methods and be specific, accurate, not misleading, and relevant to the specific product. Quantitative information is preferred over qualitative information.

5.4.8 DIFFERENCES VERSUS PREVIOUS VERSIONS

For EPDs that have been updated, the following information shall be included:

- a description of the differences versus previously published versions, and
- a revision date on the cover page.

5.4.9 REFERENCES

A reference section shall be included, including a list of all sources referred to in the EPD, including the GPI (including version number), and PCR (registration number, name, and version) used to develop the EPD.

5.4.10 EXECUTIVE SUMMARY IN ENGLISH

The executive summary, if included (see Section 5.1), shall contain relevant summarised information related to the programme, product, environmental performance, information related to pre-certified EPDs, and information related to sector EPDs. Besides this, further information may be added such as additional environmental, social or economic information, references as well as differences versus previous EPD versions.

6 LIST OF ABBREVIATIONS

ANZSIC	Australian and New Zealand Standard Industrial Classification
CPC	Central product classification
CPV	Common procurement vocabulary
EPD	Environmental product declaration
GPI	General Programme Instructions
GTIN	Global trade item number
ISO	International Organization for Standardization
LCA	Life cycle assessment
LCI	Life cycle inventory
NACE/CPA	Classification of products by activity
ND	Not declared
PCR	Product category rules
REACH	Restriction of chemicals
RSL	Reference service life
SI	The International System of Units
UN	United Nations
UNSPSC	United Nations standard products and services code

7 REFERENCES

CEN (2019) EN 15804:2012+A2:2019, Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products.

EPD International (2021) General Programme Instructions for the International EPD® System. Version 4.0, dated 2021-03-29.
www.environdec.com.

ISO (2000) ISO 14020:2000, Environmental labels and declarations – General principles.

ISO (2004) ISO 8601:2004 Data elements and interchange formats – Information interchange – Representation of dates and times.

ISO (2006a) ISO 14025:2006, Environmental labels and declarations – Type III environmental declarations – Principles and procedures.

ISO (2006b) ISO 14040:2006, Environmental management – Life cycle assessment – Principles and framework.

ISO (2006c) ISO 14044: 2006, Environmental management – Life cycle assessment – Requirements and guidelines.

ISO (2014) ISO 14046:2014, Environmental management – Water footprint – Principles, requirements and guidelines.

ISO (2015a) ISO 14001:2015, Environmental management systems – Requirements with guidance for use.

ISO (2015b) ISO 9001:2015, Quality management systems – Requirements.

ISO (2016a) ISO 21067-1:2016, Packaging – Vocabulary – Part 1: General terms.

ISO (2016b) ISO 14021:2016, Environmental labels and declarations - Self-declared environmental claim (Type II environmental labelling).

ISO (2018a) ISO 14024:2018, Environmental labels and declaration – Type I environmental labelling – Principles and procedures.

ISO (2018b) ISO/TS 14067:2018, Greenhouse gases – Carbon footprint of products – Requirements and guidelines for quantification and communication.

8 VERSION HISTORY OF PCR

VERSION 1.1, 2011-07-05

- Original version.

VERSION 1.2, 2013-10-30

- Editorial changes and use of the latest PCR template
- Added link to UN CPC home page
- Added missing requirement that a maximum of three significant digits should be used when reporting results
- Update of the document to General Programme Instructions, version 2.01
 - General introduction and General information
 - Electricity production (data quality rules)
 - Indicators for environmental performance
 - EPD Validity
 - Content of the EPD

VERSION 2.0, 2014-05-16

- Extended validity with three years
- Updated General Introduction and administrative information
- Updated reference to latest PCR Basic Module
- Minor editorial changes

VERSION 3.0, 2018-10-19

- Minor editorial changes
- Updated reference to latest PCR Basic Module
- Extended validity with three years
- Clarifications on product description added in 2.2.1
- Specifications on voluntary end-of-life treatments added in 4.3.1.3
- New basic module used in order to ensure that the latest programme instructions and other best practices for PCR development are followed.

VERSION 3.01, 2019-09-06

- Clarified terms of use
- Editorial changes

VERSION 3.0.2, 2022-09-28

- The validity of this PCR has been extended until 2023-09-01, as an updating process has been initiated.

VERSION 4.0.0, 2023-MM-DD

To be added

DRAFT

© EPD INTERNATIONAL AB 2023

YOUR USE OF THIS MATERIAL IS SUBJECT TO THE GENERAL TERMS OF USE PUBLISHED ON BY EPD INTERNATIONAL AB:S HOMEPAGE AT [HTTPS://WWW.ENVIRONDEC.COM/CONTACT/GENERAL-TERMS-OF-USE/](https://www.environdec.com/contact/general-terms-of-use/). IF YOU HAVE NOT REGISTERED AND ACCEPTED EPD INTERNATIONAL AB:S THE GENERAL TERMS OF USE, YOU ARE NOT AUTHORIZED TO EXPLOIT THIS WORK IN ANY MANNER.

COVER IMAGE © *TO BE ADDED BY THE SECRETARIAT IN THE PCR*

