

## DELTA UP

DELTA UP advanced managerial chair with mesh backrest and with an essential line provides great performances in terms of functionality and comfort.

1



2



3



4



## DIMENSIONS

1 . 2 . 3 Operative chair without headrest.  
4 . Operative chair with headrest.

L 68/50 P68/46 HT 102/115 HS 45/58

L 68/50 P68/46 HT 122/135 HS 45/58

## DELTA UP

### SEAT & BACKREST

---

Delta Up operative managerial chair with mesh backrest with Updown height adjustment ( **A** ).  
High resistance black polypropylene frame.  
Polyester fireproof mesh which can be standard (Goal) or shimmed (Gabriel).

### OPTIONAL

**B.** Lumbar support adjustable in height.

**B.** Lumbar adjustable 3D support.

**C.** Upholstered headrest adjustable in height.



The seat is made of high resistance polypropylene with 2 steel bars inside.

### OPTIONAL

1. Seat sideshift

### PADDING

---

The seat is in crushproof polyurethane rubber. Density 40, thickness 5cm.

Also available in the fireproof version. CERTIFICATION 1IM.

## DELTA UP

### **MECHANISM**

---

Delta Up is characterized by a Self Synchron Mechanism lockable in 5 different positions. The gas column is corresponding to DIN 4550 norm and exceed the 4° level.

### **BASE**

---

Delta Up is available with two types of 5 spoke bases on castors. (standard in black nylon with double tread and diameter 65 mm):

1. Black polypropylene "Loop" Base [d. 680 mm]
2. Polished aluminium "LOOP" Base in alluminio lucido [d. 680 mm]

Optional with the same holding pin diam 11mm:

1. Rubber castors, black (R06) o grey with carter chromo (R07),
2. Rubber castors and with brake (R06A),
3. Rubber white or black "polo" castors with central hole
4. Black nylon feet (R08)

### **ARMRESTS**

---

1. Fixed black polypropylene armrests.
2. Black polypropylene armrests with height adjustment.
3. Black polypropylene armrests with height and depth adjustment with soft polyurethane Pad
4. Black polypropylene armrests with 3D adjustment with soft polyurethane Pad.
5. Black polypropylene aluminium with carter armrests with 3D adjustment and polyurethane Pad.

### **CERTIFICATIONS**

---

1. EN1335-A
2. CERTIFICATION 1IM
3. CAM

### **WARRANTY**

---

All Quinti products are covered by 5 years warranty.

Quinti products are entirely manufactured in Italy, certificated n° 290.058.V

## DELTA UP

### UPHOLSTERY

**CREPE'****CATEGORY 1**

350 gr/mtl  
100% Polyester Class 1 ,EN1021/1-2  
50.000 +/- 10% cycles

**BIO-EXPO****CATEGORY 2**

300 gr/mt2  
100% Propitex FR bacteriostatic  
Class 1UNI EN ISO 354:2003  
100.000 +/- 10% cycles Martindale

**EXTREME****CATEGORY 2**

350 gr/mtl  
100% Xtreme FR  
Class 1 , EN 1021-1/2  
100.000 +/- 10% cycles Martindale

**LASER****CATEGORY 2**

560 gr/mtl  
100% Polyester FR  
Class 1  
80.000 +/- 10% cycles Martindale

**ECOPELLE****CATEGORY 2**

630 gr/mt2  
83% PVC, 17% Synthetic  
ISO 379-DIN75200-CSERF4/83 10%  
cycles Martindale

**ERA****CATEGORY 3**

448 gr/mtl  
100% Trevira CS  
Class 1UNI EN ISO 354:2003  
100.000 +/- 10% cycles Martindale

**LASER PLUS****CATEGORY 3**

630 gr/mtl  
100% Polyester FR Trevira  
Classe1 , 4.000 +/- cycles Martindale

**ECOPELLE SOUL****CATEGORY 3**

760 gr/mt2  
Superficies 100% POLIURETANO,  
Base Polyester 85%,17% Cotton  
EN1021-1/BS5852 PART 1  
>100.000 EN ISO 5470-2

**GABRIEL MESH**

510 gr. gr/mtl  
100% Polyester / Polyester  
BS EN 1021-1:2014  
70.000 / rub

**MELANGE****CATEGORY 3**

390 g/lin.m  
100% Trevira CS  
Class 1  
80.000 +/- 10% cycles Martindale

**JET****CATEGORY 3**

365 +/- 5% g/lin.m  
100% Polyester FR  
Class 1  
80.000 +/- 10% cycles Martindale

**ECOPELLE SISTEMA PRO****CATEGORY 3**

710 gr/mt2  
Surface 93% PVC  
Base Polyester 28%  
CLASSE1  
100.000 CICLI

**ECOPELLE VITAX****CATEGORY 3**

850 gr/mt2  
Surface 98% PVC 2% PU  
Base cotton 100%  
CLASSE 1  
100.000 CICLI

**ONE RECICLE****CATEGORY 3**

525 gr/mt2  
100% recycled polyester  
Base cotton 100%  
CLASSE 1IM  
100.000 CICLI

**LANA****CATEGORY 5**

500 gr/mt2  
75% Lana, 25% polyamide  
Class 1  
100.000 cycles Martindale

**PELLE****CATEGORY 5/6**

620 g/lin.m  
100% Cow leather  
Class 1, EN 1021-1/2

**PIED POULE****CATEGORY 6**

550 g/lin.m  
66% cotton, 34% Polyester  
35.000 % cycles Martindale

**EUROPOST 2****CATEGORY 6**

710 g/lin.m  
63% PU, 16% CO, 21% PL  
Ini1975 CLASS1emme,UNI9175/FA  
50.000% cycles Martindale

**PREMIUM /ELEGANCE****CATEGORY 7**

100% First quality cow leather  
Thickness 1,2/1,4 mm  
EN1021-1/2

**STEELCUT TRIO****CATEGORY 7**

770 g/lin.m  
90% New wool worsted, 10% Nylon  
Class 1, EN 1021-1/2  
100.000 % cycles Martindale

**REMIX****CATEGORY 7**

415 g/lin.m  
90% New wool worsted, 10% Nylon  
Class 1, EN 1021-1/2  
100.000 % cycles Martindale

**VELLUTO DECONTRACTE'****CATEGORY 7**

590 g/lin.m  
19% CO, 61% PC,10% PL, 10%VI  
40.000 % cycles Martindale

**MERIT****CATEGORY 7**

500g/lin.m  
76% Polyester Recycled  
24% Polyester  
EN 1021-1/2  
85.000 % cycles Martindale

**VELLUTO****CATEGORY 8**

600 g/lin.m  
100.000 % PL Flame retardant

**PELLE SOFT****CATEGORY 8**

100% Cow leather Thickness,8-2 mm  
Aniline treatment – First quality  
EN1021-1/2

## DELTA UP

### **GOAL MESH**

350 gr/ mq  
100% Polyester CL. 1  
100.000 Martindale cycles

---

## **USAGE AND MAINTENANCE**

---

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

### **FABRICS**

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easily.

### **WOODS**

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

### **METALS**

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth of deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

### **WARRANTY**

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.